



SBR0220T5

**0.2A SBR<sup>®</sup>  
Super Barrier Rectifier**

**Features**

- Low Forward Voltage Drop
- Superior Reverse Avalanche Capability
- Patented Super Barrier Rectifier Technology
- Soft, Fast Switching Capability
- 150°C Operating Junction Temperature
- **Lead Free Finish, RoHS Compliant**
- **“Green” Molding Compound (No Br, Sb)**

**Mechanical Data**

- Case: SOD-523
- Case Material: Molded Plastic, “Green” Molding compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Polarity Indicator: Cathode Band
- Terminals: Finish – Matte Tin annealed over Alloy 42 leadframe. Solderable per MIL-STD-202, Method 208 **(e3)**
- Marking Information: See Page 3
- Ordering Information: See Page 3
- Weight: 0.002 grams (approximate)

**Maximum Ratings** @ T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	20	V
Working Peak Reverse Voltage	V <sub>RWM</sub>		
DC Blocking Voltage	V <sub>RM</sub>		
RMS Reverse Voltage	V <sub>R(RMS)</sub>	14	V
Average Rectified Output Current (See Figure 1)	I <sub>O</sub>	0.2	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I <sub>FSM</sub>	5	A
Maximum Thermal Resistance	R <sub>θJA</sub>	400	°C/W
Thermal Resistance Junction to Soldering (Note 1)			
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-65 to +150	°C

**Electrical Characteristics** @ T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 2)	V <sub>(BR)R</sub>	20	-	-	V	I <sub>R</sub> = 400 μA
Forward Voltage Drop	V <sub>F</sub>	-	0.37	0.41	V	I <sub>F</sub> = 0.1A, T <sub>J</sub> = 25°C
			0.34	0.38		I <sub>F</sub> = 0.1A, T <sub>J</sub> = 85°C
			0.43	0.47		I <sub>F</sub> = 0.2A, T <sub>J</sub> = 25°C
			0.41	0.45		I <sub>F</sub> = 0.2A, T <sub>J</sub> = 85°C
Leakage Current (Note 2)	I <sub>R</sub>	-	-	40	μA	V <sub>R</sub> = 20V, T <sub>J</sub> = 25°C
			-	0.5	mA	V <sub>R</sub> = 20V, T <sub>J</sub> = 85°C

Notes: 1. FR-4 PCB, 2 oz. Copper, minimum recommended pad layout per <http://www.diodes.com/datasheets/ap02001.pdf>.  
2. Short duration pulse test used to minimize self-heating effect.

NEW PRODUCT






Fig. 1 Typical Forward Characteristics




Fig. 2 Typical Reverse Characteristics




Fig. 3 Typical Total Capacitance





Fig. 4  $V_R$  vs  $T_A$

**Package Outline Drawing**






<b>SOD-523</b>		
Dim	Min	Max
A	1.50	1.70
B	1.10	1.30
C	0.25	0.35
D	0.70	0.90
E	0.10	0.20
G	0.55	0.65
All Dimensions in mm		



**SBR0220T5**

**Marking, Polarity, Weight & Ordering Information**

<b>SBR0220T5</b>	Case Style		Marking	Weight
	 Top View	 Back View		0.002g (approx.)

Ordering Information	Date Code
SBR0220T5-7 3000/Tape & Reel	22 = Product Type Marking Code

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.