

Raychem Corporation

300 Constitution Drive
Menlo Park, CA 94025
800-227-4856
FAX 800-227-4866

Raychem

PolySwitch®
PTC Devices
Resettable Fuse

PRODUCT: RUE250U

DOCUMENT: SCD 22793
PCN: 613961
REV LETTER: I
REV DATE: AUGUST 31, 1999
PAGE NO.: 1 OF 1

Specification Status: RELEASED

Electrical Rating

Voltage: 30V MAX
Current: 40A MAX

Lead Material:

20 AWG Tin/Lead Plated Copper

Marking:

None




TABLE I. DIMENSIONS:

	A		B		C	D	E	
	MIN	MAX	MIN	MAX	TYPICAL	MIN	MIN	MAX
mm:	7.1	8.1	--	2.8	5.0	7.6	15.0	16.8
in*:	(0.28)	(0.32)	--	(0.11)	(0.2)	(0.3)	(0.59)	(0.66)

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS:

I HOLD	CURRENT RATINGS						TIME TO TRIP	RESISTANCE		ONE-HOUR POST-TRIP RESISTANCE STANDARD TRIP	NOMINAL TRIPPED POWER DISSIPATION
	AMPS 20°C HOLD	AMPS AT 0°C HOLD	AMPS AT 20°C TRIP	AMPS AT 50°C HOLD	AMPS AT 50°C TRIP	AMPS AT 20°C HOLD		AMPS AT 20°C TRIP	SECONDS AT 20°C, 8A MAX		
2.5	--	--	2.5	4.9	2.0	3.7	5.0	0.031	0.044	0.080	1.75

Reference Documents:

PS300

Precedence:

This specification takes precedence over documents referenced herein.

Effectivity:

Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION:

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

