



# RO2053

## 310.0 MHz SAW Resonator



TO39-3 Case

- **Ideal for 310 MHz Transmitters**
- **Low Series Resistance**
- **Quartz Stability**
- **Rugged, Hermetic, Low-Profile TO39 Case**

The RO2053 is a true one-port, surface-acoustic-wave (SAW) resonator in a low-profile TO39 case. It provides reliable, fundamental-mode, quartz frequency stabilization of fixed-frequency transmitters operating at 310 MHz. The RO2053 is designed specifically for AM transmitters used in automotive-keyless-entry applications operating in the USA under FCC Part 15, in Canada under DoC RSS-210, and in Italy.

### Absolute Maximum Ratings

Rating	Value	Units
CW RF Power Dissipation	+0	dBm
DC Voltage Between Any Two Pins	±30	VDC
Case Temperature	-40 to +85	°C

### Electrical Characteristics

Characteristic	Sym	Notes	Minimum	Typical	Maximum	Units				
Center Frequency (+25 °C)	Absolute Frequency	$f_C$	2, 3, 4, 5	309.900		310.100	MHz			
	Tolerance from 310.000 MHz	$\Delta f_C$						±100	kHz	
Insertion Loss	IL	2, 5, 6		3.1	5.0	dB				
Quality Factor	Unloaded Q	$Q_U$	5, 6, 7							
	50 $\Omega$ Loaded Q	$Q_L$						3,500		
Temperature Stability	Turnover Temperature	$T_O$	6, 7, 8	37	52	67	°C			
	Turnover Frequency	$f_O$						$f_C + 8.4$	kHz	
	Frequency Temperature Coefficient	FTC						0.037	ppm/°C <sup>2</sup>	
Frequency Aging	Absolute Value during the First Year	$ f_A $	1		≤10		ppm/yr			
DC Insulation Resistance between Any Two Pins		5	1.0				M $\Omega$			
RF Equivalent RLC Model	Motional Resistance	$R_M$	5, 7, 9							
	Motional Inductance	$L_M$						43	78	$\Omega$
	Motional Capacitance	$C_M$						260.257		$\mu$ H
	Pin 1 to Pin 2 Static Capacitance	$C_O$	5, 6, 9	2.2	2.5	2.8	pF			
Transducer Static Capacitance	$C_P$	5, 6, 7, 9		2.2			pF			
Test Fixture Shunt Inductance	$L_{TEST}$	2, 7		105			nH			
Lid Symbolization (in Addition to Lot and/or Date Codes)	RFM RO2053									



### CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

#### Notes:

1. Frequency aging is the change in  $f_C$  with time and is specified at +65°C or less. Aging may exceed the specification for prolonged temperatures above +65°C. Typically, aging is greatest the first year after manufacture, decreasing significantly in subsequent years.
2. The center frequency,  $f_C$ , is measured at the minimum insertion loss point,  $IL_{MIN}$ , with the resonator in the 50  $\Omega$  test system (VSWR ≤ 1.2:1). The shunt inductance,  $L_{TEST}$ , is tuned for parallel resonance with  $C_O$  at  $f_C$ . Typically,  $f_{OSCILLATOR}$  or  $f_{TRANSMITTER}$  is less than the resonator  $f_C$ .
3. One or more of the following United States patents apply: 4,454,488 and 4,616,197 and others pending.
4. Typically, equipment designs utilizing this device require emissions testing and government approval, which is the responsibility of the equipment manufacturer.
5. Unless noted otherwise, case temperature  $T_C = +25^\circ\text{C} \pm 2^\circ\text{C}$ .
6. The design, manufacturing process, and specifications of this device are subject to change without notice.
7. Derived mathematically from one or more of the following directly measured parameters:  $f_C$ , IL, 3 dB bandwidth,  $f_C$  versus  $T_C$ , and  $C_O$ .
8. Turnover temperature,  $T_O$ , is the temperature of maximum (or turnover) frequency,  $f_O$ . The nominal frequency at any case temperature,  $T_C$ , may be calculated from:  $f = f_O [1 - FTC (T_O - T_C)^2]$ . Typically, *oscillator*  $T_O$  is 20°C less than the specified *resonator*  $T_O$ .
9. This equivalent RLC model approximates resonator performance near the resonant frequency and is provided for reference only. The capacitance  $C_O$  is the static (nonmotional) capacitance between pin1 and pin 2 measured at low frequency (10 MHz) with a capacitance meter. The measurement includes case parasitic capacitance with a floating case. For usual grounded case applications (with ground connected to either pin 1 or pin 2 and to the case), add approximately 0.25 pF to  $C_O$ .


# 310.0 MHz

# SAW Resonator

## Electrical Connections

This one-port, two-terminal SAW resonator is bidirectional. The terminals are interchangeable with the exception of circuit board layout.


Pin	Connection
1	Terminal 1
2	Terminal 2
3	Case Ground




## Typical Test Circuit

The test circuit inductor,  $L_{TEST}$ , is tuned to resonate with the static capacitance,  $C_O$  at  $F_C$ .

### Electrical Test:




### Power Test:




## Typical Application Circuits

### Typical Low-Power Transmitter Application:




### Typical Local Oscillator Application:




## Temperature Characteristics

The curve shown on the right accounts for resonator contribution only and does not include oscillator temperature characteristics.




## Equivalent LC Model

The following equivalent LC model is valid near resonance:



## Case Design



Dimensions	Millimeters		Inches	
	Min	Max	Min	Max
A		9.30		0.366
B		3.18		0.125
C	2.50	3.50	0.098	0.138
D	0.46 Nominal		0.018 Nominal	
E	5.08 Nominal		0.200 Nominal	
F	2.54 Nominal		0.100 Nominal	
G	2.54 Nominal		0.100 Nominal	
H		1.02		0.040
J	1.40		0.055	