

B13a FEMALE HEADER RIGHT ANGLE

PITCH: 2.0mm

SPECIFICATIONS

Material

Insulator: PBT, glass reinforced, rated UL 94V-0

Contact: Phosphor Bronze

Electrical

Current Rating: 1 Amp



Contact Resistance: 30 mΩ max.

Insulation Resistance: 3000MΩ min.



Dielectric Withstanding Voltage: 500 V AC for 1 minute

Operating Temperature: -40°C to +105°C



♦ **Mating Suggestion:** C27, C28, C29 & C30 series.





(TYPE C)



RECOMMENDED P.C.B LAYOUT



(TYPE A)



(TYPE B)



RECOMMENDED P.C.B LAYOUT

HOW TO ORDER:

B13a - 1 - 2 - 3 - 4 - 5

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.INSULATOR HEIGHT	5.INSULATOR COLOR
SINGLE ROW 1*2 - 1*40 DUAL ROW 2*2 - 2*40	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	A: TYPE A B: TYPE B C: TYPE C	1. BLACK