

Temperature Measurement

B57500

Probe Assemblies

M 500

Applications


- Air sensor for air conditioning (not for use in evaporator)

Features

- Thermistor with epoxy resin encapsulation
- PVC-insulated wires (black) with tinned ends, AWG 26, $T_{max} = 105\text{ °C}$

Options

Alternative resistance ratings, rated temperatures, resistance tolerances and wire lengths, AWG 22 or AWG 24 available on request



Dimensions in mm

Delivery mode

Bulk

Climatic category (IEC 60068-1)		30/100/56	
Max. power at 25 °C	P_{25}	60	mW
Resistance tolerance	$\Delta R_N/R_N$	± 3 %	
Rated temperature	T_N	25	°C
B value tolerance	$\Delta B/B$	± 0,5 %	
Dissipation factor (in air)	δ_{th}	approx. 3	mW/K
Thermal cooling time constant (in air)	τ_c	approx. 20	s
Heat capacity	C_{th}	approx. 60	mJ/K
Insulation resistance ($V = 100\text{ Vdc}$)	R_{is}	> 100	MΩ
Test voltage ($t = 1\text{ s}$)	V_T	1,25	kVAC

R_{25}	No. of R/T characteristic	$B_{25/100}$	Ordering code
Ω		K	
10 k	8016	3988	B57500M0103A005

Note

Only to use in dry environmental conditions.





Reliability data

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature T: 100 °C t: 1000 h	< 2 %	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: 40 °C Relative humidity of air: 93 % Duration: 56 days	< 2 %	No visible damage
Storage in coldness		Storage at lower category temperature T: - 30 °C t: 1000 h	< 2 %	No visible damage
Rapid temperature cycling (in air)	IEC 60068-2-14	Lower test temperature: - 30 °C Upper test temperature: 100 °C Time to change from lower to upper temperature: < 30 s Number of cycles: 1000 Medium: air	< 2 %	No visible damage
Vibration resistance	IEC 60068-2-6	Frequency range: 5 to 500 Hz Amplitude: 7,5 mm/2 g Duration: 3 × 8 h	< 3 %	No visible damage
Long-term stability (empirical value)		T: 100 °C t: 10 000 h	< 3 %	No visible damage
Voltage proof test		1250 Vac; 1 s		No flashover
Insulation test		The sensors are placed in a vessel containing metallic balls of 1 mm diameter (with total immersed head). The applied voltage is 100 Vdc.		Above 100 MΩ

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse nicht lieferbar sein. Bitte beachten Sie die Lieferbedingungen. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft zu erhalten.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained herein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronic Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise stated.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the representatives of the nearest sales office.

Due to technical requirements components may contain dangerous substances. For information on the handling of these substances also contact one of our Sales Offices.