



SKYWORKS®

DATA SHEET

AA280-25, AA280-25LF: GaAs IC 5-Bit Digital Attenuator 0.5 dB LSB 300 kHz–2 GHz

Features

- Attenuation 0.5 dB steps to 15.5 dB with high accuracy
- Low DC power consumption
- Low-cost SOIC-16 plastic package
- Available lead (Pb)-free and RoHS-compliant MSL-1 @ 260 °C per JEDEC J-STD-020

Description


The AA280-25 is a 5-bit, GaAs IC FET digital attenuator in a low-cost SOIC-16 package. This attenuator has an LSB of 0.5 dB and a total attenuation of 15.5 dB. The AA280-25 is particularly suited where high attenuation accuracy, low insertion loss and low intermodulation products are required. Typical applications include cellular radio, wireless data, wireless local loop and other gain level control circuits.

NEW

Skyworks offers lead (Pb)-free, RoHS (Restriction of Hazardous Substances)-compliant packaging.



Pin Out



Electrical Specifications at -40 °C to +85 °C (0, -5 V)


Parameter ⁽¹⁾	Condition	Frequency	Min.	Typ.	Max.	Unit
Insertion loss ⁽²⁾		300 kHz–0.5 GHz		1.1	1.3	dB
		300 kHz–1.0 GHz		1.4	1.7	dB
		300 kHz–2.0 GHz		1.7	2.0	dB
Attenuation range				15.5		dB
Attenuation accuracy ⁽²⁾		300 kHz–1.0 GHz	$\pm (0.2 + 3\% \text{ of Attenuation setting in dB})$			dB
		300 kHz–2.0 GHz	$\pm (0.4 + 3\% \text{ of Attenuation setting in dB})$			dB
VSWR (I/O) ⁽³⁾		300 kHz–2.0 GHz		1.4:1	1.8:1	
Switching characteristics	10/90% or 90%/10% RF 50% CTL to 90%/10% RF $T_{\text{RISE}} = 1 \text{ ns}$, BW = 500 MHz			15		ns
Rise, fall				25		ns
On, off				25		mV
Video feedthru						
Input power for 1 dB compression		0.5–2.0 GHz	24	29		dBm
		0.05 GHz	17	22		dBm
Intermodulation intercept point (IP3)	For two-tone input power 5 dBm	0.5–2.0 GHz	44	50		dBm
		0.05 GHz	35	40		dBm
Thermal resistance				85		°C/W
Control voltages	$V_{\text{Low}} = 0 \text{ to } 0.2 \text{ V @ } 20 \mu\text{A max.}$ $V_{\text{High}} = -5 \text{ V @ } 300 \mu\text{A max.}$					

1. All measurements made in a 50 Ω system, unless otherwise specified.


2. Attenuation referenced to insertion loss.

3. Input/Output.


Typical Performance Data (0, -5 V)




Insertion Loss vs. Frequency



VSWR vs. Frequency (25 °C)




IP3 vs. Attenuation and Temperature




VSWR vs. Frequency (85 °C)

Compression Point vs. Attenuation, Voltage, and Temperature


Attenuation State	Control Voltage (V)	Input Power @ 1 dB Compression		
		25 °C (dBm)	85 °C (dBm)	-40 °C (dBm)
Ins. loss	-5	28.3	28.1	29.1
0.5 dB	-5	28.5	28.3	29.4
1 dB	-5	28.7	28.7	29.6
2 dB	-5	28.4	28.3	29.1
4 dB	-5	32.9	32.9	33.9
8 dB	-5	36.8	36.8	36.8
15.5 dB	-5	32.7	32.1	32.8




VSWR vs. Frequency (-40 °C)




Attenuation Accuracy vs. Frequency (25 °C)




Attenuation Phase Accuracy vs. Frequency (25 °C)




Attenuation Accuracy vs. Frequency (85 °C)



Attenuation Phase Accuracy vs. Frequency (85 °C)




Attenuation Accuracy vs. Frequency (-40 °C)




Attenuation Phase Accuracy vs. Frequency (-40 °C)


Typical Performance Data (0, -3 V)




Insertion Loss vs. Frequency




Attenuation Accuracy vs. Frequency (25 °C)




VSWR vs. Frequency (25 °C)




Attenuation Accuracy vs. Frequency (85 °C)



Attenuation Phase Accuracy vs. Frequency (25 °C)



Attenuation Accuracy vs. Frequency (-40 °C)




IP3 vs. Attenuation and Temperature

Truth Table

V ₁	V ₂	V ₃	V ₄	V ₅	V ₆	V ₇	V ₈	Attenuation J ₁ -J ₂
0.5 dB Bit	1 dB Bit	2 dB Bit		4 dB Bit		8 dB Bit		
-5	-5	-5	0	-5	0	-5	0	Reference I.L.
0	-5	-5	0	-5	0	-5	0	0.5 dB
-5	0	-5	0	-5	0	-5	0	1 dB
-5	-5	0	-5	-5	0	-5	0	2 dB
-5	-5	-5	0	0	-5	-5	0	4 dB
-5	-5	-5	0	-5	0	0	-5	8 dB
0	0	0	-5	0	-5	0	-5	15.5 dB max. atten.

SOIC-16



Compression Point vs. Attenuation, Voltage, and Temperature

Attenuation State	Control Voltage (V)	Input Power @ 1 dB Compression		
		25 °C (dBm)	85 °C (dBm)	-40 °C (dBm)
Ins. loss	-3	22.7	23.3	24.2
0.5 dB	-3	23.5	24.2	25.1
1 dB	-3	24.6	25	25.9
2 dB	-3	22.9	23.4	24.3
4 dB	-3	31.6	31.8	33.1
8 dB	-3	31	28.7	26.4
15.5 dB	-3	25	24.4	25

Absolute Maximum Ratings

Characteristic	Value
RF input power	2.0 W > 500 MHz 0/-8 V 0.5 W > 50 MHz 0/-8 V
Control voltage	+0.2 V, -8 V
Operating temperature	-40 °C to +85 °C
Storage temperature	-65 °C to +150 °C

Performance is guaranteed only under the conditions listed in the specifications table and is not guaranteed under the full range(s) described by the Absolute Maximum specifications. Exceeding any of the absolute maximum/minimum specifications may result in permanent damage to the device and will void the warranty.

CAUTION: Although this device is designed to be as robust as possible, ESD (Electrostatic Discharge) can damage this device. This device must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions must be employed at all times.

Recommended Solder Reflow Profiles

Refer to the [“Recommended Solder Reflow Profile”](#) Application Note.

Tape and Reel Information

Refer to the [“Discrete Devices and IC Switch/Attenuators Tape and Reel Package Orientation”](#) Application Note.

Copyright © 2002, 2003, 2004, 2005, Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com, are incorporated by reference.