

Kingbright

SURFACE MOUNT DISPLAY

Part Number: ACDA02-41SEKWA-F01

Super Bright Orange



Features

- 0.2 INCH DIGIT HEIGHT.
- LOW CURRENT OPERATION.
- EXCELLENT CHARACTER APPEARANCE.
- I.C. COMPATIBLE.
- MECHANICALLY RUGGED.
- PACKAGE :300PCS / REEL.
- GRAY FACE, WHITE SEGMENT.
- MOISTURE SENSITIVITY LEVEL : LEVEL 4.
- RoHS COMPLIANT.


Description

The Super Bright Orange device is made with InGaAlP (on GaAs substrate) light emitting diode chip.


Package Dimensions& Internal Circuit Diagram



DIG.1: 3,18



DIG.2: 8,13



Notes:

1. All dimensions are in millimeters (inches). Tolerance is $\pm 0.25(0.01)$ unless otherwise noted.
2. Specifications are subject to change without notice.
3. The gap between the reflector and PCB shall not exceed 0.25mm.



Selection Guide

Part No.	Dice	Lens Type	Iv (ucd) [1] @ 10mA		Description
			Min.	Typ.	
ACDA02-41SEKWA-F01	Super Bright Orange (InGaAlP)	WHITE DIFFUSED	8000	37200	Common Anode, Rt. Hand Decimal.

Note:

1. Luminous intensity/ luminous Flux: +/-15%.

Electrical / Optical Characteristics at TA=25°C

Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
λ_{peak}	Peak Wavelength	Super Bright Orange	610		nm	I _F =20mA
λ_D [1]	Dominant Wavelength	Super Bright Orange	601		nm	I _F =20mA
$\Delta\lambda_{1/2}$	Spectral Line Half-width	Super Bright Orange	29		nm	I _F =20mA
C	Capacitance	Super Bright Orange	15		pF	V _F =0V;f=1MHz
V _F [2]	Forward Voltage	Super Bright Orange	2.1	2.5	V	I _F =20mA
I _R	Reverse Current	Super Bright Orange		10	uA	V _R =5V

Notes:

1.Wavelength: +/-1nm.


2. Forward Voltage: +/-0.1V.

Absolute Maximum Ratings at TA=25°C





Parameter	Super Bright Orange	Units
Power dissipation	75	mW
DC Forward Current	30	mA
Peak Forward Current [1]	195	mA
Reverse Voltage	5	V
Operating / Storage Temperature	-40°C To +85°C	

Note:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.




Super Bright Orange ACDA02-41SEKWA-F01



ACDA02-41SEKWA-F01


Reflow Soldering Profile For Lead-free SMT Process.




NOTES:

1. We recommend the reflow temperature 245°C(+/-5°C). The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.


Recommended Soldering Pattern (Units : mm; Tolerance: ± 0.15)



Reel Dimension




Tape Specifications (Units : mm)



PACKING & LABEL SPECIFICATIONS

ACDA02-41SEKWA-F01



Inside LABEL Paste On The Tape-pipe

Kingbright	TYPE: ACDX02-41xxx	DATE
QTY: 300 PCS	CODE: xx	PASSED
XXXXXXXXXX-XXXX	FOCX	xx xx xx
LOT NO.	RoHs Compliant	Number OF FQC

Outside LABEL Paste On The BAG

ACDX02-41xxx	300 PCS	Number OF QA
	QAx	DATE
	xx xx xx	
	PASSED	
	RoHs Compliant	

Outside LABEL Paste On The 19#Box

BOX Number	xxxx	XX XX
ACDX02-41xxx	1800	x
	Number OF QA	
	DATE	
	QAx	
	xx xx xx	
	PASSED	
	RoHs Compliant	

Outside LABEL Paste On The 12-1#Box

ACDX02-41xxx	600 PCS	Number OF QA
	QAx	DATE
	xx xx xx	
	PASSED	
	RoHs Compliant	