



# SMD ISDN S Interface Hybrid



APC5568ds-5v

## ELECTRICAL SPECIFICATIONS @ 25°C

Turns Ratio +/-5%	Primary Inductance mH min	Leakage Inductance uH max	Primary DCR OHMS +/- 30%	Secondary DCR OHMS +/- 30%	Choke	
					Inductance per line mH nom	DCR per line OHMS
1CT:2	22	5.0	2.2	2.8	0.04	0.5

NOTES: ISOLATION PRI:SEC 1500VRMS  
 APPROVALS PENDING FOR IEC6950:A4:1996 AND EN60950:A4:1997  
 DESIGNED FOR USE WITH MOTOROLA MC145575 AND COLOGNE HFC-SXX  
 EXTERNAL RESISTORS R1 AND R1' REQUIRED FOR AMPLITUDE OPTIMIZATION. RECOMMENDED VALUE 560 OHMS

## MECHANICAL



NOTES: NOT TO SCALE  
 TOLERANCE +/- 0.2MM  
 ALL DIMENSIONS IN MM [INCHES]






## SMD ISDN S Interface Hybrid

APC5568ds-5v

### SCHEMATIC



©2003 Bel Fuse Inc. Specifications subject to change without notice. 05.20.03

#### CORPORATE

**Bel Fuse Inc.**  
206 Van Vorst Street  
Jersey City, NJ 07302  
Tel 201-432-0463  
Fax 201-432-9542  
www.belfuse.com

#### FAR EAST

**Bel Fuse Ltd.**  
8F / 8 Luk Hop Street  
San Po Kong  
Kowloon, Hong Kong  
Tel 852-2328-5515  
Fax 852-2352-3706  
www.belfuse.com

#### EUROPE

**Bel Stewart Connector**  
45/46 Riverside  
Medway City Estate  
Rochester, Kent ME2 4DP U.K.  
Tel 44-1634-722890  
Fax 44-1634-716677  
www.belfuse.com