

# Kingbright

## 1.6X0.8mm SMD CHIP LED LAMP

AP1608SURCK

HYPER RED


### Features

- 1.6mmX0.8mm SMT LED, 1.1mm THICKNESS.
- LOW POWER CONSUMPTION.
- WIDE VIEWING ANGLE.
- IDEAL FOR BACKLIGHT AND INDICATOR.
- VARIOUS COLORS AND LENS TYPES AVAILABLE.
- PACKAGE: 2000PCS / REEL.
- IN ACCORD WITH Kingbright ENVIRONMENTAL POLICY (DOCUMENT WI-QC-G-0442).
- RoHS COMPLIANT.

### Description

The Hyper Red source color devices are made with DH InGaAlP on GaAs substrate Light Emitting Diode.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.1(0.004)$  unless otherwise noted.
3. Specifications are subject to change without notice.



## Selection Guide

| Part No.    | Dice                | Lens Type   | Iv (mcd)<br>@ 20mA |      | Viewing<br>Angle |
|-------------|---------------------|-------------|--------------------|------|------------------|
|             |                     |             | Min.               | Typ. | 2 $\theta$ 1/2   |
| AP1608SURCK | HYPER RED (InGaAlP) | WATER CLEAR | 50                 | 150  | 120°             |

Note:

1.  $\theta$ 1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

## Electrical / Optical Characteristics at T<sub>A</sub>=25°C

| Symbol                | Parameter                | Device    | Typ. | Max. | Units | Test Conditions           |
|-----------------------|--------------------------|-----------|------|------|-------|---------------------------|
| $\lambda_{peak}$      | Peak Wavelength          | Hyper Red | 650  |      | nm    | I <sub>F</sub> =20mA      |
| $\lambda_D$           | Dominant Wavelength      | Hyper Red | 635  |      | nm    | I <sub>F</sub> =20mA      |
| $\Delta\lambda_{1/2}$ | Spectral Line Half-width | Hyper Red | 28   |      | nm    | I <sub>F</sub> =20mA      |
| C                     | Capacitance              | Hyper Red | 35   |      | pF    | V <sub>F</sub> =0V;f=1MHz |
| V <sub>F</sub>        | Forward Voltage          | Hyper Red | 1.95 | 2.5  | V     | I <sub>F</sub> =20mA      |
| I <sub>R</sub>        | Reverse Current          | Hyper Red |      | 10   | uA    | V <sub>R</sub> = 5V       |


## Absolute Maximum Ratings at T<sub>A</sub>=25°C

| Parameter                       | Hyper Red      | Units |
|---------------------------------|----------------|-------|
| Power dissipation               | 170            | mW    |
| DC Forward Current              | 30             | mA    |
| Peak Forward Current [1]        | 185            | mA    |
| Reverse Voltage                 | 5              | V     |
| Operating / Storage Temperature | -40°C To +85°C |       |

Note:






1. 1/10 Duty Cycle, 0.1ms Pulse Width.

# Kingbright




## Hyper Red

### AP1608SURCK



## AP1608SURCK


Reflow Soldering Profile For Lead-free SMT Process.




NOTES:

1. We recommend the reflow temperature 245°C(+/-5°C). The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

### Recommended Soldering Pattern (Units : mm)





### Tape Specifications (Units : mm)




# Kingbright

## PACKING & LABEL SPECIFICATIONS

## AP1608SURCK



|  |   |
|--|---|
| <b>Kingbright</b>  |   |
| P/NO: AP1608XXX  |   |
| QTY: 2,000pcs  | Q.C. <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">QC<br/>xx xx xx<br/>PASSED</span> |
| S/N: XXX   |   |
| CODE: XXX  |   |
| LOT NO:  |   |
| <br>xxxxxxxxxxxxxxxxxxxx |   |

### Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity/ luminous flux or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength: +/-1nm
2. Luminous Intensity/ Luminous Flux: +/-15%
3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.