



**Advanced Power
Electronics Corp.**

AP1802GU

Pb Free Plating Product


N-CHANNEL ENHANCEMENT MODE

POWER MOSFET

▼ Capable of 2.5V gate drive

▼ Lower on-resistance

▼ Surface mount package




BV_{DSS}	20V
$R_{DS(ON)}$	32m Ω
I_D	5.8A

Description

Advanced Power MOSFETs utilized advanced processing techniques to achieve the lowest possible on-resistance, extremely efficient and cost-effectiveness device.

The 2021-8 J-lead package provides good on-resistance performance and space saving like SC-70-6.



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	20	V
V_{GS}	Gate-Source Voltage	± 12	V
$I_D @ T_A = 25^\circ\text{C}$	Continuous Drain Current ³ , $V_{GS} @ 4.5\text{V}$	5.8	A
$I_D @ T_A = 70^\circ\text{C}$	Continuous Drain Current ³ , $V_{GS} @ 4.5\text{V}$	4.7	A
I_{DM}	Pulsed Drain Current ^{1,2}	20	A
$P_D @ T_A = 25^\circ\text{C}$	Total Power Dissipation	1.6	W
	Linear Derating Factor	0.013	W/ $^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$

Thermal Data

Symbol	Parameter	Value	Unit
R_{thj-a}	Thermal Resistance Junction-ambient ³ Max.	78	$^\circ\text{C}/\text{W}$



Electrical Characteristics@Tj=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min .	Typ .	Max .	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	20	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C, $I_D=1mA$	-	0.02	-	V/°C
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10V, I_D=6A$	-	-	27	mΩ
		$V_{GS}=4.5V, I_D=5A$	-	-	32	mΩ
		$V_{GS}=2.5V, I_D=3A$	-	-	50	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	0.5	-	1.2	V
g_{fs}	Forward Transconductance	$V_{DS}=5V, I_D=5A$	-	13	-	S
I_{DSS}	Drain-Source Leakage Current ($T_j=25^\circ C$)	$V_{DS}=20V, V_{GS}=0V$	-	-	1	uA
	Drain-Source Leakage Current ($T_j=70^\circ C$)	$V_{DS}=16V, V_{GS}=0V$	-	-	10	uA
I_{GSS}	Gate-Source Leakage	$V_{GS}=\pm 12V$	-	-	±100	nA
Q_g	Total Gate Charge ²	$I_D=5A$	-	9	15	nC
Q_{gs}	Gate-Source Charge	$V_{DS}=16V$	-	1.5	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	$V_{GS}=4.5V$	-	4	-	nC
$t_{d(on)}$	Turn-on Delay Time ²	$V_{DS}=10V$	-	9	-	ns
t_r	Rise Time	$I_D=1A$	-	10	-	ns
$t_{d(off)}$	Turn-off Delay Time	$R_G=3.3\Omega, V_{GS}=5V$	-	16	-	ns
t_f	Fall Time	$R_D=10\Omega$	-	5	-	ns
C_{iss}	Input Capacitance	$V_{GS}=0V$	-	620	990	pF
C_{oss}	Output Capacitance	$V_{DS}=20V$	-	120	-	pF
C_{rss}	Reverse Transfer Capacitance	$f=1.0MHz$	-	100	-	pF
R_g	Gate Resistance	$f=1.0MHz$	-	1.2	1.8	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ²	$I_S=1.3A, V_{GS}=0V$	-	-	1.2	V
t_{rr}	Reverse Recovery Time	$I_S=5A, V_{GS}=0V,$	-	20	-	ns
Q_{rr}	Reverse Recovery Charge	$dI/dt=100A/\mu s$	-	11	-	nC

Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- 3.Surface mounted on 1 in² copper pad of FR4 board , $t \leq 5sec$; 125 °C/W at steady state.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics




Fig 12. Gate Charge Circuit