



DUAL 300mA LDO REGULATORS

AP2402

General Description

The AP2402 series are dual positive voltage regulator ICs fabricated by CMOS process. Each of these ICs consists of a voltage reference, two error amplifiers, two resistor networks for setting output voltages. Each channel has a current limit circuit for current protection and a chip enable circuit with quick discharge function.

The AP2402 series feature high supply voltage ripple rejection, low dropout voltage, low noise, high output voltage accuracy, and low current consumption which make them ideal for use in various battery-powered devices. The chip-enable function allows the output of each channel to be turned on/off independently, greatly reducing the power consumption.

The AP2402 series have 2.5V/1.8V, 2.8V/1.8V and 2.8V/2.8V versions.

The AP2402 are available in SOT-23-6, TSOT-23-6 and DFN-2×2-8 packages.

Features

- Minimum Output Current Capability per Channel: 300mA
- High Output Voltage Accuracy: $\pm 2\%$
- Low Quiescent Current per Channel: 50 μ A Typical
- Low Standby Current: 0.1 μ A Typical
- High PSRR: 70dB Typical (f=1kHz)
- Extremely Low Noise: 30 μ Vrms (10Hz to 100kHz)
- Operating Temperature: -40 to 85°C
- Compatible with Low ESR Ceramic Capacitor

Applications

- Mobile Phones, Cordless Phones
- Wireless Communication Equipment
- Portable Games
- Cameras, Video Recorders
- Sub-board Power Supplies for Telecom Equipment
- Battery Powered Equipment



Figure 1. Package Types of AP2402




Pin Configuration


Figure 2. Pin Configuration of AP2402 (Top View)

Pin Description

Pin Number		Pin Name	Function
6-pin	8-pin		
1	7	V_{OUT2}	Output voltage 2
2	5	GND	Ground
3	3	CE2	On/Off control 2, logic high=enable; logic low=shutdown
4	2	CE1	On/Off control 1, logic high=enable; logic low=shutdown
5	1	V_{IN}	Input voltage
6	8	V_{OUT1}	Output voltage 1
	4, 6	NC	No connection



DUAL 300mA LDO REGULATORS

AP2402

Functional Block Diagram





Figure 3. Functional Block Diagram of AP2402



DUAL 300mA LDO REGULATORS

AP2402

Ordering Information



Package	Temperature Range	Output Voltages	Part Number		Marking ID		Packing Type
			Lead-Free	Green	Lead-Free	Green	
SOT-23-6	-40 to 85°C	2.5V/1.8V	AP2402A21KTR-E1	AP2402A21KTR-G1	EAA	GAA	Tape & Reel
		2.8V/1.8V	AP2402A31KTR-E1	AP2402A31KTR-G1	EAB	GAB	Tape & Reel
		2.8V/2.8V	AP2402A33KTR-E1	AP2402A33KTR-G1	EAC	GAC	Tape & Reel
TSOT-23-6	-40 to 85°C	2.5V/1.8V	AP2402A21KTTR-E1	AP2402A21KTTR-G1	S8A	L8A	Tape & Reel
		2.8V/1.8V	AP2402A31KTTR-E1	AP2402A31KTTR-G1	S8B	L8B	Tape & Reel
		2.8V/2.8V	AP2402A33KTTR-E1	AP2402A33KTTR-G1	S8C	L8C	Tape & Reel
DFN-2×2-8	-40 to 85°C	2.5V/1.8V	AP2402A21DNTR-E1	AP2402A21DNTR-G1	6A	DA	Tape & Reel
		2.8V/1.8V	AP2402A31DNTR-E1	AP2402A31DNTR-G1	6B	DB	Tape & Reel
		2.8V/2.8V	AP2402A33DNTR-E1	AP2402A33DNTR-G1	6C	DC	Tape & Reel

BCD Semiconductor's Pb-free products, as designated with "E1" suffix in the part number, are RoHS compliant. Products with "G1" suffix are available in green packages.

**DUAL 300mA LDO REGULATORS****AP2402****Absolute Maximum Ratings (Note 1)**

Parameter	Symbol	Value		Unit
Input Voltage	V_{IN}	6.5		V
Enable Input Voltage	V_{CE}	6.5		V
Output Current ($T_A=25^\circ\text{C}$)	$I_{OUT1}+I_{OUT2}$	700		mA
Power Dissipation ($T_A=25^\circ\text{C}$)	P_D	SOT-23-6	250	mW
Junction Temperature	T_J	150		$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65 to 150		$^\circ\text{C}$
Lead Temperature (Soldering, 10sec)	T_{LEAD}	260		$^\circ\text{C}$
ESD (Human Body Model)	ESD	6000		V
ESD (Machine Model)	ESD	200		V

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Input Voltage	V_{IN}		6	V
Operating Ambient Temperature Range	T_A	-40	85	$^\circ\text{C}$



DUAL 300mA LDO REGULATORS

AP2402

Electrical Characteristics

(Channel 1/Channel 2: $V_{IN}=V_{OUT}+1V$, $T_A=25^{\circ}C$, $C_{IN}=1\mu F$, $C_{OUT}=1\mu F$, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit	
Output Voltage Accuracy	$\Delta V_{OUT}/V_{OUT}$	Variation from specified V_{OUT} , $I_{OUT}=30mA$	-2		2	%	
Input Voltage	V_{IN}				6	V	
Maximum Output Current	$I_{OUT(Max)}$		300			mA	
Load Regulation	V_{RLOAD}	$1mA \leq I_{OUT} \leq 300mA$		10	60	mV	
Line Regulation	V_{RLINE}	$V_{OUT}+1V \leq V_{IN} \leq 6V$ $I_{OUT}=30mA$, $V_{CE}=V_{IN}$		0.01	0.2	%/V	
Dropout Voltage	V_{DROP}	$I_{OUT}=30mA$	$V_{OUT}=1.8V$		30	36	mV
			$V_{OUT}=2.5V$		20	24	
			$V_{OUT}=2.8V$		20	24	
		$I_{OUT}=100mA$	$V_{OUT}=1.8V$		100	120	
			$V_{OUT}=2.5V$		65	80	
			$V_{OUT}=2.8V$		65	80	
Quiescent Current	I_Q	$I_{OUT}=0mA$		50	90	μA	
Standby Current	I_{STD}	V_{CE} in OFF mode		0.1	1	μA	
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=1kHz $V_{IN}=V_{OUT}+1V$, $I_{OUT}=30mA$		70		dB	
Output Voltage Temperature Coefficient	$(\Delta V_{OUT}/V_{OUT})/\Delta T$	$I_{OUT}=30mA$, $-40^{\circ}C \leq T_A \leq 85^{\circ}C$		± 100		ppm/ $^{\circ}C$	
Current Limit	I_{LIMIT}	$V_{CE}=V_{IN}$		400		mA	
Short Circuit Current	I_{SHORT}	$V_{CE}=V_{IN}$, V_{OUT} short to GND		50		mA	
RMS Output Noise	V_{NOISE}	$10Hz \leq f \leq 100kHz$		30		μV_{rms}	
CE "High" Voltage		CE input voltage "High"	1.3		6	V	
CE "Low" Voltage		CE input voltage "Low"			0.4	V	
Thermal Shutdown				165		$^{\circ}C$	
Thermal Shutdown Hysteresis				30		$^{\circ}C$	



Typical Performance Characteristics




Figure 4. Ground Current vs. Output Current




Figure 5. Ground Current vs. Output Current




Figure 6. Ground Current vs. Output Current




Figure 7. Ground Current vs. Output Current



Typical Performance Characteristics (Continued)




Figure 8. Ground Current vs. Output Current




Figure 9. Ground Current vs. Output Current




Figure 10. Output Voltage vs. Output Current




Figure 11. Output Voltage vs. Output Current



Typical Performance Characteristics (Continued)




Figure 12. Output Voltage vs. Output Current




Figure 13. Output Voltage vs. Output Current




Figure 14. Output Voltage vs. Output Current




Figure 15. Output Voltage vs. Output Current



Typical Performance Characteristics (Continued)




Figure 16. Output Voltage vs. Output Current




Figure 17. Output Voltage vs. Output Current




Figure 18. Output Voltage vs. Output Current




Figure 19. Output Voltage vs. Input Voltage



DUAL 300mA LDO REGULATORS

AP2402

Typical Performance Characteristics (Continued)




Figure 20. Output Voltage vs. Input Voltage




Figure 21. Output Voltage vs. Input Voltage




Figure 22. Dropout Voltage vs. Output Current




Figure 23. Dropout Voltage vs. Output Current



DUAL 300mA LDO REGULATORS

AP2402

Typical Performance Characteristics (Continued)




Figure 24. Dropout Voltage vs. Output Current




Figure 25. Output Voltage vs. Case Temperature




Figure 26. Output Voltage vs. Case Temperature




Figure 27. Output Voltage vs. Case Temperature



Typical Performance Characteristics (Continued)




Figure 28. Quiescent Current vs. Input Voltage




Figure 29. Quiescent Current vs. Input Voltage




Figure 30. Quiescent Current vs. Input Voltage




Figure 31. Quiescent Current vs. Case Temperature



DUAL 300mA LDO REGULATORS

AP2402

Typical Performance Characteristics (Continued)




Figure 32. Quiescent Current vs. Case Temperature




Figure 33. Quiescent Current vs. Case Temperature




Figure 34. Line Transient
(Conditions: $I_{OUT}=50\text{mA}$, $C_{IN}=0.68\mu\text{F}$, $C_{OUT}=1\mu\text{F}$)




Figure 35. Line Transient
(Conditions: $I_{OUT}=50\text{mA}$, $C_{IN}=0.68\mu\text{F}$, $C_{OUT}=1\mu\text{F}$)



DUAL 300mA LDO REGULATORS

AP2402

Typical Performance Characteristics (Continued)




Figure 36. Load Transient
(Conditions: $V_{IN}=2.8V$, $I_{OUT}=10$ to $100mA$, $C_{IN}=C_{OUT}=1\mu F$)




Figure 37. Load Transient
(Conditions: $V_{IN}=3.5V$, $I_{OUT}=10$ to $100mA$, $C_{IN}=C_{OUT}=1\mu F$)




Figure 38. Cross Talk 1
(Conditions: channel 1 and 2 on, $I_{OUT1}=30mA$, $I_{OUT2}=10$ to $100mA$, $C_{IN}=C_{OUT}=1\mu F$)




Figure 39. Cross Talk 2
(Conditions: channel 1 and 2 on, $I_{OUT1}=10$ to $100mA$, $I_{OUT2}=30mA$, $C_{IN}=C_{OUT}=1\mu F$)



DUAL 300mA LDO REGULATORS

AP2402

Typical Performance Characteristics (Continued)




Figure 40. Enable Voltage vs. Output Voltage
(Conditions: $V_{CE1}=V_{CE2}=0$ to $2V$, $I_{OUT}=0mA$, $C_{IN}=C_{OUT}=1\mu F$)




Figure 41. Auto Discharge Function
(Conditions: $V_{CE1}=V_{CE2}=0$ to $2V$, $I_{OUT}=0mA$, $C_{IN}=C_{OUT}=1\mu F$)




Figure 42. PSRR vs. Frequency




Figure 43. PSRR vs. Frequency



Typical Performance Characteristics (Continued)




Figure 44. PSRR vs. Frequency




Figure 45. PSRR vs. Frequency




Figure 46. PSRR vs. Frequency




Figure 47. PSRR vs. Frequency



DUAL 300mA LDO REGULATORS

AP2402

Typical Performance Characteristics (Continued)




Figure 48. Power Dissipation vs. Case Temperature




Figure 49. Power Dissipation vs. Case Temperature



Typical Application




Figure 50. Typical Application of AP2402




DUAL 300mA LDO REGULATORS

AP2402

Mechanical Dimensions

SOT-23-6

Unit: mm(inch)








DUAL 300mA LDO REGULATORS

AP2402

Mechanical Dimensions (Continued)

TSOT-23-6

Unit: mm(inch)






DUAL 300mA LDO REGULATORS

AP2402

Mechanical Dimensions (Continued)

DFN-2x2-8

Unit: mm(inch)





BCD Semiconductor Manufacturing Limited

<http://www.bcdsemi.com>

IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

MAIN SITE

- Headquarters

BCD Semiconductor Manufacturing Limited

No. 1600, Zi Xing Road, Shanghai ZiZhu Science-based Industrial Park, 200241, China
Tel: +86-21-24162266, Fax: +86-21-24162277

- Wafer Fab

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd.

800 Yi Shan Road, Shanghai 200233, China
Tel: +86-21-6485 1491, Fax: +86-21-5450 0008

REGIONAL SALES OFFICE

Shenzhen Office

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd., Shenzhen Office
Room E, 5F, Noble Center, No.1006, 3rd Fuzhong Road, Futian District, Shenzhen,
518026, China
Tel: +86-755-8826 7951
Fax: +86-755-8826 7865

Taiwan Office

BCD Semiconductor (Taiwan) Company Limited
4F, 298-1, Rui Guang Road, Nei-Hu District, Taipei,
Taiwan
Tel: +886-2-2656 2808
Fax: +886-2-2656 2806

USA Office

BCD Semiconductor Corp.
30920 Huntwood Ave. Hayward,
CA 94544, USA
Tel : +1-510-324-2988
Fax: +1-510-324-2788