


NAiS

**POWER PhotoMOS RELAYS
with Internal Varistor**

PhotoMOS RELAYS

FEATURES



1. Power PhotoMOS relay with internal varistor

An internal varistor on the output side protects the output MOSFET from the reverse voltage from an external voltage surge or inductive load.

2. High capacity PhotoMOS relay

Supports control of minute loads to a maximum 3.0 A. Suitable for output control.

3. Supports both AC and DC

Bi-directional control so there is no need to differentiate according to the load as in conventional SSR's.

4. Can be placed on-board the 4-unit relay (power photoMOS relay type)

5. Ideal for inductive loads

Ideal for inductive loads such as motors, solenoids, and electro-magnetic contactors.

6. High sensitivity, low ON resistance

Can control a maximum 3.0 A load with a 5 mA input current. Low On resistance of 0.18 Ω (AQZ202V).

7. Compact slim-type 4-pin SIL

(W) 3.5×(L) 21.0×(H) 12.5 mm (W) .138×(L) .827×(H) .492 inch. The compact 73.5mm² size of the 4-pin SIL package allows high density mounting.

8. Sockets also available

9. Promoting the CE making (Please inquire for further details.)

TYPES

AC/DC type

Output rating		Part No.	Packing quantity	
Load voltage (Effective Vrms)	Load current		Inner carton	Outer carton
17 V AC	22 V DC	AQZ202V		
30 V AC	38 V DC	AQZ205V		
60 V AC	85 V DC	AQZ207V		
140 V AC	180 V DC	AQZ204V		

Note: Refer to the recommended load voltage.

RATING

AC/DC type

1) Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	AQZ202V	AQZ205V	AQZ207V	AQZ204V	Remarks
Input	LED forward current	I _F		50 mA			
	LED reverse voltage	V _R		3 V			
	Peak forward current	I _{FP}		1 A			f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}		75 mW			
Output	Load voltage	V _L	17 V	30 V	60 V	140 V	Effective Vrms
	DC		22 V	38 V	85 V	180 V	
	Continuous load current (Peak AC)	I _L	3.0 A	2.0 A	1.0 A	0.5 A	
	Peak load current	I _{peak}	9.0 A	6.0 A	3.0 A	1.5 A	100 ms (1 shot), V _L = DC
Power dissipation		P _{out}	1.6 W				
Total power dissipation		P _T	1.6 W				
I/O isolation voltage		V _{iso}	2,500 V AC				
Temperature limits	Operating	T _{opr}	−40°C to +85°C −40°F to +185°F				Non-condensing at low temperatures
	Storage	T _{stg}	−40°C to +100°C −40°F to +212°F				

2) Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	AQZ202V	AQZ205V	AQZ207V	AQZ204V	Remarks			
Input	LED operate current		I _{Fon}	1.0 mA			I _L = 100 mA V _L = 10 V				
	LED turn off current			3.0 mA			I _L = 100 mA V _L = 10 V				
Output	LED dropout voltage		I _F	0.4 mA			I _L = 100 mA V _L = 10 V				
	Typical			0.9 mA			I _F = 10 mA				
Transfer characteristics	Typical		V _F	1.16 V (1.25 V at I _F = 50 mA)				I _F = 10 mA			
	Maximum			1.5 V							
	On resistance		R _{on}	0.11 Ω	0.23 Ω	0.7 Ω	2.1 Ω	I _F = 10 mA			
	Maximum			0.18 Ω	0.34 Ω	1.1 Ω	3.2 Ω	I _L = Max. Within 1 s on time			
Off state leakage current			I _{Leak}	1 mA				I _F = 0 V _L = Max. DC			
Transfer characteristics	Switching speed	Turn on time*	T _{on}	2.46 ms	2.40 ms	1.12 ms	1.65 ms	I _F = 10 mA I _L = 100 mA V _L = 10 V			
				5.0 ms				I _F = 5 mA I _L = 100 mA V _L = 10 V			
		Turn off time*	T _{off}	5.64 ms	5.65 ms	2.57 ms	3.88 ms	I _F = 5 mA or 10 mA I _L = 100 mA V _L = 10 V			
				10.0 ms				I _F = 5 mA or 10 mA I _L = 100 mA V _L = 10 V			
	I/O capacitance		C _{iso}	0.8 pF				f = 1 MHz V _B = 0			
	Maximum			1.5 pF							
	Initial I/O isolation resistance		R _{iso}	1,000 MΩ				500 V DC			
	Maximum operating frequency		—	1.0 cps				I _F = 10 mA Duty factor = 50% I _L = Max., V _L = Max.			
Vibration resistance			Minimum	10 to 55 Hz at double amplitude of 3 mm				2 hours for 3 axes			
Shock resistance			Minimum	4,900 m/s ² {500 G}1 ms				3 times for 3 axes			

3) Internal varistor characteristics


Item	AQZ202V	AQZ205V	AQZ207V	AQZ204V
Varistor voltage	27 V	47 V	100 V	220 V
Maximum energy	0.5 J	1.0 J	2.0 J	4.5 J

Note: When using the relay to absorb the reverse voltage during inductive load switching, make sure the load is within the inductance range given in the internal varistor characteristics data below, rather than the energy resistance range for the internal varistor. Note, the inductance range will differ if the switching frequency is higher than the rate given for the characteristics data conditions.

Note: Recommendable LED forward current I_F = 5 to 10 mA.

For type of connection, see page 35.

*Turn on/off time




- For Dimensions, see Page 29.
- For Schematic and Wiring Diagrams, see Page 35.
- For Cautions for Use, see Page 40.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F




2. Load current vs. ambient temperature characteristics in adjacent mounting

I_L : Load current;
I_L (max.) : Maximum continuous load current



3.-1) On resistance vs. ambient temperature characteristics


LED current: 10 mA;
Continuous load current: 3.0 A (DC) (AQZ202V),
2.0 A (DC) (AQZ205V),



AQZ20OV


3.-{(2)} On resistance vs. ambient temperature characteristics

LED current: 10 mA;
Continuous load current: 3.0 A (DC) (AQZ202V),
2.0 A (DC) (AQZ205V),




4. Turn on time vs. ambient temperature characteristics

LED current: 10 mA;
Load voltage: 10 V (DC)
Continuous load current: 100 mA (DC)




5. Turn off time vs. ambient temperature characteristics

LED current: 10 mA;
Load voltage: 10 V (DC)
Continuous load current: 100 mA (DC)




6. LED operate vs. ambient temperature characteristics

Load voltage: 10 V (DC);
Continuous load current: 100 mA (DC)




7. LED turn off current vs. ambient temperature characteristics

Load voltage: 10 V (DC)
Continuous load current: 100 mA (DC)




8. LED dropout voltage vs. ambient temperature characteristics

Sample: all types; LED current: 5 to 50 mA




9. Voltage vs. current characteristics of output at MOS portion

Ambient temperature: 25°C 77°F




10. Off state leakage current

Ambient temperature: 25°C 77°F




11. LED forward current vs. turn on time characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC); Ambient temperature: 25°C 77°F




12. LED forward current vs. turn off time characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC); Ambient temperature: 25°C 77°F




13. Maximum operating frequency vs. load voltage/current characteristics

LED current: 10 mA
Ambient temperature: 25°C 77°F





14. Applied voltage vs. output capacitance characteristics

Frequency: 1 MHz;
Ambient temperature: 25°C 77°F



15. Data for internal varistor characteristic

Operating frequency: 1 Hz
No. of operations: 10^6 max.




ACCESSORY

mm inch


For more details, please consult our nearest office.

Socket Standard type




PA1a-PS

Self clinching type



PA1a-PS-H

PC board pattern (BOTTOM VIEW)
Standard typeTolerance: $\pm 0.1 \pm .004$