



BAV23A/C/S


SURFACE MOUNT SWITCHING DIODE

Features




- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance
- **Lead Free/RoHS Compliant (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT-23
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture sensitivity: Level 1 per J-STD-020C
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Polarity: See Diagrams Below
- Marking: See Diagrams Below & Page 2
- Weight: 0.008 grams (approximate)



| SOT-23 | | |
|----------------------|-------|-------|
| Dim | Min | Max |
| A | 0.37 | 0.51 |
| B | 1.20 | 1.40 |
| C | 2.30 | 2.50 |
| D | 0.89 | 1.03 |
| E | 0.45 | 0.60 |
| G | 1.78 | 2.05 |
| H | 2.80 | 3.00 |
| J | 0.013 | 0.10 |
| K | 0.903 | 1.10 |
| L | 0.45 | 0.61 |
| M | 0.085 | 0.180 |
| α | 0° | 8° |
| All Dimensions in mm | | |




Maximum Ratings @ T_A = 25°C unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|--|------------------------------------|-------------------|------|
| Repetitive Peak Reverse Voltage | V _{RRM} | 250 | V |
| Working Peak Reverse Voltage DC Blocking Voltage | V _{RWM} V _R | 200 | V |
| RMS Reverse Voltage | V _{R(RMS)} | 141 | V |
| Forward Continuous Current (Note 2) | I _{FM} | 400 | mA |
| Non-Repetitive Peak Forward Surge Current @ t = 1.0μs @ t = 100μs @ t = 10ms | I _{FSM} | 9.0 3.0 1.7 | A |
| Repetitive Peak Forward Surge Current (Note 2) | I _{FRM} | 625 | mA |
| Power Dissipation (Note 2) | P _d | 350 | mW |
| Thermal Resistance Junction to Ambient Air (Note 2) | R _{θJA} | 357 | °C/W |
| Operating and Storage Temperature Range | T _j , T _{STG} | -65 to +150 | °C |

Electrical Characteristics @ T_A = 25°C unless otherwise specified

| Characteristic | Symbol | Min | Max | Unit | Test Condition |
|--|--------------------|-----|-------------|----------|---|
| Reverse Breakdown Voltage (Note 1) | V _{(BR)R} | 250 | — | V | I _R = 100μA |
| Forward Voltage (Note 1) | V _F | — | 1.0 1.25 | V | I _F = 100mA I _F = 200mA |
| Reverse Current @ Rated DC Blocking Voltage (Note 1) | I _R | — | 100 | nA μA | T _j = 25°C T _j = 150°C |
| Total Capacitance | C _T | — | 5.0 | pF | V _R = 0, f = 1.0MHz |
| Reverse Recovery Time | t _{rr} | — | 50 | ns | I _F = I _R = 30mA, I _{rr} = 0.1 x I _R , R _L = 100Ω |

Notes: 1. Short duration test pulse used to minimize self-heating effect.
2. Part mounted on FR-4 board with recommended pad layout, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
3. No purposefully added lead.






Fig. 1 Typical Forward Characteristics




Fig. 2 Typical Reverse Characteristics




Fig. 3 Typical Capacitance vs. Reverse Voltage





Fig. 4 Power Dissipation Derating

Ordering Information (Note 4)

| Device | Packaging | Shipping |
|--|-----------|------------------|
| BAV23A-7-F BAV23C-7-F BAV23S-7-F | SOT-23 | 3000/Tape & Reel |

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



XXX = Product Type Marking Code (See Page 1)
 YM = Date Code Marking
 Y = Year ex: N = 2002
 M = Month ex: 9 = September

Date Code Key

| Year | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 |
|------|------|------|------|------|------|------|------|------|------|
| Code | M | N | P | R | S | T | U | V | W |

| Month | Jan | Feb | March | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |



IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.