



Continental Device India Limited

An IS/ISO 9002 and IECQ Certified Manufacturer

IS/ISO 9002  
Lic# QSC/L- 000019.2


## NPN SILICON PLANAR EPITAXIAL RF TRANSISTORS

BF494

BF495

TO-92

Plastic Package



## High Voltage Video Transistors

## ABSOLUTE MAXIMUM RATINGS(Ta=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	Value	UNITS
Collector Emitter Voltage	$V_{CEO}$	20	V
Collector Base Voltage	$V_{CBO}$	30	V
Emitter Base Voltage	$V_{EBO}$	5	V
Collector Current (DC)	$I_C$	30	mA
Collector Current(peak value)	$I_{CM}$	30	mA
Total Power dissipation up to Tamb = 25°C	$P_{tot}$	300	mW
Operating And Storage Junction Temperature Range	$T_j, T_{stg}$	-55 to +150	°C


## THERMAL RESISTANCE

Junction to ambient	$R_{th(j-a)}$	420	K/W
---------------------	---------------	-----	-----

## ELECTRICAL CHARACTERISTICS (Ta=25°C Unless Otherwise Specified)

DESCRIPTION	SYMBOL	TEST CONDITION	Min	Max	UNITS
Collector Cut- off Current	$I_{CBO}$	$V_{CB}=20V, I_E=0$		500	nA
Collector Cut - off Current	$I_{CBO}$	$V_{CB}=20V, I_E=0$ Ta =150 °C		4.0	μA
EmitterCut off Current	$I_{EBO}$	$V_{EB}=4V, I_C=0$		500	nA
Base Emitter Voltage	$V_{BE(ON)}$	$V_{CE}=10V, I_C=1mA$	0.65	0.74	V
DC Current Gain	$h_{FE}$	$I_C=1mA, V_{CE}=10V$			
BF494	$h_{FE}$	$I_C=1mA, V_{CE}=10V$	67	221	
BF494A			200	500	
BF494B			110	215	
BF 495			35	125	
BF 495C			65	135	
BF 495D			40	85	

NPN SILICON PLANAR EPITAXIAL RF TRANSISTORS



BF494  
BF495

TO-92  
Plastic Package

ELECTRICAL CHARACTERISTICS (Ta=25°C Unless Specified Otherwise)



DESCRIPTION	SYMBOL	TEST CONDITION	Min	Max	UNITS
DYNAMIC CHARACTERISTICS					
Transition Frequency	$f_T$	$I_C=1\text{mA}$ , $V_{CE}=10\text{V}$	120		MHz
Feedback Capacitance	$C_{re}$	$V_{CE}=10\text{V}$ , $I_C=1\text{mA}$ $f=4.5\text{MHz}$		1.0	pF
* $V_{BE}$ decreases by about 1.7mV/K with increasing temperature.					

**BF494**  
**BF495**

**TO-92**  
**Plastic Package**

## TO-92 Plastic Package


### TO-92 Transistors on Tape and Ammo Pack



SEC AA


DIM	MIN.	MAX.
A	4.32	5.33
B	4.45	5.20
C	3.18	4.19
D	0.41	0.55
E	0.35	0.50
F	5 DEG	
G	1.14	1.40
H	1.14	1.53
K	12.70	—
L	1.982	2.082

All diminsions in mm.



#### PIN CONFIGURATION

1. BASE
2. EMITTER
3. COLLECTOR



All dimensions in mm unless specified otherwise

ITEM	SYMBOL	SPECIFICATION				REMARKS
		MIN.	NOM.	MAX.	TOL.	
BODY WIDTH	A1	4.0		4.8		CUMULATIVE PITCH ERROR 1.0 mm/20 PITCH TO BE MEASURED AT BOTTOM OF CLINCH
BODY HEIGHT	A	4.8		5.2		
BODY THICKNESS	T	3.9		4.2		
PITCH OF COMPONENT	P		12.7		±1	
FEED HOLE PITCH	Po		12.7		±0.3	AT TOP OF BODY
FEED HOLE CENTRE TO COMPONENT CENTRE	P2		6.35		±0.4	
DISTANCE BETWEEN OUTER LEADS	F		5.08		+0.6 -0.2	
COMPONENT ALIGNMENT	Δh		0	1		
TAPE WIDTH	W		18		±0.5	t1 0.3 - 0.6
HOLD-DOWN TAPE WIDTH	Wo		6		±0.2	
HOLE POSITION	W1		9		+0.7 -0.5	
HOLD-DOWN TAPE POSITION	W2		0.5		±0.2	
LEAD WIRE CLINCH HEIGHT	Ho		16		±0.5	
COMPONENT HEIGHT	H1			23.25		
LENGTH OF SNIPPED LEADS	L			11.0		
FEED HOLE DIAMETER	Do		4		±0.2	
TOTAL TAPE THICKNESS	t			1.2		
LEAD - TO - LEAD DISTANCE F1,	F2		2.54		+0.4 -0.1	
CLINCH HEIGHT	H2			3		
PULL - OUT FORCE	(P)	6N				

#### NOTES

1. MAXIMUM ALIGNMENT DEVIATION BETWEEN LEADS NOT TO BE GREATER THAN 0.2 mm.
2. MAXIMUM NON-CUMULATIVE VARIATION BETWEEN TAPE FEED HOLES SHALL NOT EXCEED 1 mm IN 20 PITCHES.
3. HOLDDOWN TAPE NOT TO EXCEED BEYOND THE EDGE(S) OF CARRIER TAPE AND THERE SHALL BE NO EXPOSURE OF ADHESIVE.
4. NO MORE THAN 3 CONSECUTIVE MISSING COMPONENTS ARE PERMITTED.
5. A TAPE TRAILER, HAVING AT LEAST THREE FEED HOLES ARE REQUIRED AFTER THE LAST COMPONENT.
6. SPLICES SHALL NOT INTERFERE WITH THE SPROCKET FEED HOLES.

## Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-92 Bulk	1K/polybag	200 gm/1K pcs	3" x 7.5" x 7.5"	5K	17" x 15" x 13.5"	80K	23 kgs
TO-92 T&A	2K/ammo box	645 gm/2K pcs	12.5" x 8" x 1.8"	2K	17" x 15" x 13.5"	32K	12.5 kgs

**Notes**

**BF494**

**BF495**

**TO-92**

**Plastic Package**

### **Disclaimer**

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of

**Continental Device India Limited**

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290

e-mail [sales@cdil.com](mailto:sales@cdil.com) [www.cdil.com](http://www.cdil.com)