



CYStek Electronics Corp.


Spec. No. : C328N3C
Issued Date : 2003.05.14
Revised Date
Page No. : 1/4

High –speed double diode DAN202N3

Description

The DAN202N3 consists of two high-speed switching diodes with common cathodes, fabricated in planar technology, and encapsulated in the small SOT-23 plastic SMD package.

Equivalent Circuit



Features

- Small plastic SMD package
- High switching speed: max. 4ns
- Continuous reverse voltage: max. 80V
- Repetitive peak reverse voltage: max. 80V
- Repetitive peak forward current: max. 300mA.

Applications

- High-speed switching in thick and thin-film circuits.



Absolute Maximum Ratings @T_A=25°C

Parameters	Symbol	Min	Max	Unit
Repetitive peak reverse voltage	V _{RRM}	-	80	V
Continuous reverse voltage	V _R	-	80	V
Continuous forward current	I _F	-	100	mA
Repetitive peak forward current	I _{FRM}		300	mA
Non-repetitive peak forward current @square wave, T _j =125°C prior to surge	I _{FSM}	t=1μs	4	A
t=1ms		-	1	A
t=1s		-	0.5	A
Total power dissipation(Note 1)	P _{tot}		250	mW
Junction Temperature	T _j	-	150	°C
Storage Temperature	T _{stg}	-65	+150	°C

Note 1: Device mounted on an FR-4 PCB.

Electrical Characteristics @ T_j=25°C unless otherwise specified

Parameters	Symbol	Conditions	Min	Typ.	Max	Unit
Forward voltage	V _F	I _F =1mA	-	-	715	mV
		I _F =10mA			855	mV
		I _F =50mA			1	V
		I _F =150mA			1.25	V
Reverse current	I _R	V _R =25V	-	-	30	nA
		V _R =75V			2.5	μA
		V _R =25V, T _j =150°C			60	μA
		V _R =75V, T _j =150°C			100	μA
Diode capacitance	C _d	V _R =0V, f=1MHz	-	-	1.5	pF
Reverse recovery time	t _{rr}	when switched from I _F =10mA to I _R =10mA, R _L =100Ω, measured at I _R =1mA	-	-	4	ns
Forward recovery voltage	V _{fr}	when switched from I _F =10mA t _r =20ns	-	-	1.75	V

Thermal Characteristics


Symbol	Parameter	Conditions	Value	Unit
R _{th,j-tp}	thermal resistance from junction to tie-point		360	°C/W
R _{th, j-a}	thermal resistance from junction to ambient	Note 1	500	°C/W

Note 1: Device mounted on an FR-4 PCB.




Characteristic Curves


Forward Current vs Ambient Temperature




Forward Current vs Forward Voltage



Non-repetitive peak forward current vs pulse duration




Diode Capacitance vs Reverse Voltage





SOT-23 Dimension



*: Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1102	0.1204	2.80	3.04	J	0.0034	0.0070	0.085	0.177
B	0.0472	0.0630	1.20	1.60	K	0.0128	0.0266	0.32	0.67
C	0.0335	0.0512	0.89	1.30	L	0.0335	0.0453	0.85	1.15
D	0.0118	0.0197	0.30	0.50	S	0.0830	0.1083	2.10	2.75
G	0.0669	0.0910	1.70	2.30	V	0.0098	0.0256	0.25	0.65
H	0.0005	0.0040	0.013	0.10					

Notes: 1.Controlling dimension: millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: 42 Alloy ; solder plating
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.