

查询EL33供应商

捷多邦, 专业
PCB打样工厂

EL 33

OUTPUT PENTODE
PENTHODE DE SORTIE
ENDPENTODE

, 24小时加急出货

Heating: indirect by A.C. or D.C.;
parallel supply




Chauffage: indirect par C.A. ou C.C.;
alimentation en parallèle

Heizung: indirekt durch Wechsel-
oder Gleichstrom;
Parallelspeisung

$V_f = 6,3 \text{ V}$

$I_f = 0,9 \text{ A}$

Dimensions in mm
Dimensions en mm
Abmessungen in mm



Base, culot, Sockel: Octal

Operating characteristics class A

Caractéristiques d'utilisation classe A

Betriebsdaten Klasse A

V_a	=	250 V
V_{g2}	=	250 V
V_{g1}	=	-6 V
I_a	=	36 mA
I_{g2}	=	4 mA
S	=	9 mA/V
R_i	=	50 k Ω
$R_{a\omega}$	=	7 k Ω
W_o ($d_{tot} = 10\%$)	=	4,5 W
V_i ($d_{tot} = 10\%$)	=	4,2 V_{eff}
V_i ($W_o = 50mW$)	=	0,35 V_{eff}
$\mu g2g1$	=	23



EL 33**PHILIPS**

Operating characteristics classe AB
 Caractéristiques d'utilisation classe AB
 Betriebsdaten Klasse AB

V_a	=	250		V
V_{g2}	=	250		V
R_k	=	140		Ω
$R_{aa\sim}$	=	10		k Ω
V_i	=	0	6,7	V_{eff}
I_a	=	2x24	2x28,5	mA
I_{g2}	=	2x2,8	2x4,6	mA
W_o	=	0	8,2	W
dt_{tot}	=	-	3,1	%

Limiting values
 Caractéristiques limites
 Grenzdaten

V_{a_0}	= max.	550 V
V_a	= max.	300 V
W_a	= max.	9 W
V_{g2_0}	= max.	550 V
V_{g2}	= max.	300 V
$W_{g2} (V_i=0)$	= max.	1,2 W
$W_{g2} (W_o=\max.)$	= max.	2,5 W
I_k	= max.	55 mA
$V_{g1} (I_{g1}=+0,3\mu A)$	= max.	-1,3 V
R_{g1}	= max.	1 M Ω
V_{kf}	= max.	100 V
R_{kf}	= max.	5 k Ω

PHILIPS



*Electronic
Tube*

HANDBOOK

EL33

page

sheet

date

1

1

1953.10.10

2

2

1953.10.10

3

FP

1999.07.04