



Common Mode Choke

EPT7003 & EPT7003-RC




- Surface Mount Package
- Robust Construction for Reflow Processing
- Add "-RC" after part number for RoHS Compliant
- Operating Temperature : 0°C to 85°C
- Peak Solder Rating (See Note 2)

Electrical Parameters @ 25° C


Inductance ($\mu\text{H Min.}$)	DCR (Max.)	Hipot (Vrms)	CMRR
@100 KHz, 100 m Vrms			
5.0	0.250	300	See Graph
Pins 1-8, 2-7, 3-6 and 4-5	Pins 1-8, 2-7, 3-6 and 4-5		

Notes :	EPT7003	EPT7003-RC
1. Lead Finish	SnPb	Matte Tin
2. Peak Temperature Rating	225°C	260°C
3. Moisture Sensitive Levels	MSL = 3 (168 Hours, 30°C/60%RH)	MSL = 4 (72 Hours, 30°C/60%RH)
4. Weight	0.33 grams	0.33 grams
5. Packaging Information (*Add "TR" to end of part number when placing order)	1000 pieces/13" reel (*EPT7003-TR)	1000 pieces/13" reel (*EPT7003-RCTR)


Schematic



Package



Typical CMRR



Unless Otherwise Specified Dimensions are in Inches /mm ± .010 / .25

Product performance is limited to specified parameters. Data is subject to change without prior notice.

CST7003 & -RC Rev. H1 2/2/06 JDG

TEL: (818) 892-0761

FAX: (818) 894-5791

