

E-Series RF 1:1 Transformer
0.05 – 3 MHz

ETC1-1T-2
V2


Features

- 1:1 Impedance Ratio
- Surface Mount
- Tape and reel packaging available

Description

M/A-COM's ETC1-1T-2 is a 1:1 RF transformer in a low cost, surface mount package. Typical applications include single to balanced mode conversion and impedance matching. Parts are packaged in tape & reel.

SM - 22 Package



Electrical Specifications: $T_A = 25^\circ\text{C}$, $Z_0 = 50\Omega$ ¹

Parameter	Test Conditions	Frequency	Units	Min	Typ	Max
RF Frequency	—	0.05 - 3	MHz	—	—	—
Insertion Loss	—	0.05 - 3	dB	—	—	2.0
		0.2 - 3	dB	—	—	1.0
Amplitude Imbalance	—	0.05 - 3	dB	—	—	0.2
		0.2 - 3	dB	—	—	0.1
Phase Imbalance	—	0.05 - 3	Degrees	—	—	2°
		0.2 - 3	Degrees	—	—	1°

Absolute Maximum Ratings¹

Parameter	Absolute Maximum
RF Power	250 mW
DC Current	30 mA
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +125°C

Ordering Information

Part Number	Package
ETC1-1T-2TR	Tape and Reel (2000 piece Reel)

1. Operation of this device above any one of these parameters may cause permanent damage.

E-Series RF 1:1 Transformer
0.05 – 3 MHz

ETC1-1T-2
V2

Pin Configuration

Pin No.	Function
1	Secondary
2	Secondary CT
3	Secondary Dot
4	Primary Dot
5	Primary

Schematic

