

MINIATURE RELAY

1 POLE—1 to 2 A (FOR SIGNAL SWITCHING)

FBR211 SERIES

■ FEATURES

- 2 A maximum carrying current
Capable of 2 A maximum continuous carrying current in the contact
- Superior reliability gold-overlay contacts
P type: Gold-overlay silver-palladium contacts
- International terminal pitch of one inch grid terminal layout
- High sensitivity, low power dissipation types also available
Standard types: 0.45 W (A or B type)
High sensitivity types: 0.2 W (C or E type)
- Conforms to FCC 68.302 (high dielectric strength type)
- UL recognized (File number E63615)
- CSA recognized (File number LR64026)



■ ORDERING INFORMATION

[Example] $\frac{\text{FBR211}}{\text{(a)}} \frac{\text{S}}{\text{(b)}} \frac{\text{A}}{\text{(c)}} \frac{\text{D012}}{\text{(d)}} \frac{\text{U}}{\text{(e)}} - \frac{\text{P}}{\text{(f)}} \frac{\text{2}}{\text{(g)}} \frac{\text{(-CSA)}}{\text{(h)}}$

(a)	Series Name	FBR211
(b)	Enclosure	S: Flux free type N: Plastic sealed type
(c)	Coil Power and Schematics	A: Standard A type } (nominal power 0.45 W type) B: Standard B type } C: High sensitivity C type } (nominal power 0.2 W type) E: High sensitivity E type }
(d)	Nominal Voltage	(Example) D003: 3 VDC D012: 12 VDC (refer to the COIL DATA CHART)
(e)	UL Standard	Nil : Standard U : UL114 recognized
(f)	Contact Material	P : Gold-overlay silver-palladium M : Gold-overlay silver
(g)	Special Type	Nil : Standard 2 : High dielectric strength type
(h)	CSA Standard	Nil : Standard -CSA : UL114 + CSA recognized (e) is U

Note: The designation name is stamped on the top of the relay case as follows:

(Example) Designation ordered: FBR211SAD005-P

Stamp: 211SAD005-P

FBR211 SERIES

■ SAFETY STANDARD AND FILE NUMBERS

UL114 (File No. E63615)

C22.2 No. 14 (File No. LR40304 or LR64026)

Nominal voltage	Contact rating
1.5 to 24 VDC	1 A 28 VDC resistive 0.5 A 30 VAC resistive

■ SPECIFICATIONS

Item		Standard (A or B type)	High sensitive (C or E type)	
Contact	Arrangement	1 form C (SPDT)		
	Material	Gold-overlay silver-palladium or gold-overlay silver		
	Resistance (initial)	Maximum 100 mΩ (at 0.1 A 6 VDC)		
	Rating (resistive)	0.5 A 120 VAC or 1 A 28 VDC		
	Maximum Carrying Current	2 A		
	Maximum Switching Power	60 VA or 28 W		
	Max. Switching Voltage* ¹	220 VAC or 150 VDC		
	Maximum Switching Current	1.25 A (AC) or 2 A (DC)		
	Minimum Switching load* ² (reference)	Plastic sealed 1 mA 1 Flux free 1 mA 5		
Coil	Nominal Power (at 20°C)	Approximately 0.45 W	Approximately 0.2 W	
	Operate Power (at 20°C)	Approximately 0.315 W maximum	Approximately 0.14 W maximum	
	Operating Temperature	-25°C to +55°C (no frost)	-25°C to +75°C (no frost)	
	Operating Humidity	45 to 85%RH		
Time Value	Operate (at nominal voltage)	Maximum 5 ms		
	Release (at nominal voltage)	Maximum 5 ms		
Insulation	Resistance (initial)	Minimum 100 MΩ (at 500 VDC)		
	Dielectric Strength	between coil and contacts	500 VAC 1 minute (standard) 1,000 VAC 1 minute (high dielectric strength type)	
		between open contacts	500 VAC 1 minute	
Life	Mechanical	5 × 10 ⁶ operations minimum		
	Electrical (Refer to the REFERENCE DATA)	3 × 10 ⁵ operations minimum (at 1 A/ 28 VDC resistive load) 1 × 10 ⁵ operations minimum (at 2 A/ 12 VDC resistive load) 1 × 10 ⁵ operations minimum (at 0.5 A/120 VDC resistive load)		
Other	Vibration Resistance	10 to 55 Hz (double amplitude of 1.5 mm)		
	Shock Resistance	Misoperation	100 m/s ² (11± ¹ ms)	60 m/s ² (11± ¹ ms)
		Endurance	1,000 m/s ² (11± ¹ ms)	
	Weight	Approximately 4 g		

*¹ If the switching voltage exceeds the rated contact voltage, reduce the current. The current values vary according to the type of load.

*² Values when switching a resistive load at normal room temperature and humidity and in a clean environment. The minimum switching load varies with the switching frequency and operation environment.

FBR211 SERIES

COIL DATA CHART

1. STANDARD (A or B type)

MODEL				Nominal voltage	Coil resistance ($\pm 10\%$)	Nominal current (at nominal voltage) approx.	Must operate voltage	Must release voltage	Maximum allowable voltage	Nominal power	Coil temperature rise
A type		B type									
Flux free	Plastic sealed	Flux free	Plastic sealed								
FBR211SAD001-□	FBR211NAD001-□	FBR211SBD001-□	FBR211NBD001-□	1.5 VDC	5 Ω	300 mA	70% max. of nominal voltage	10% min. of nominal voltage	150% of nominal voltage	Approx. 450 mW (at nominal voltage)	Approx. 45 deg (at nominal voltage)
FBR211SAD003-□	FBR211NAD003-□	FBR211SBD003-□	FBR211NBD003-□	3 VDC	20 Ω	150 mA					
FBR211SAD005-□	FBR211NAD005-□	FBR211SBD005-□	FBR211NBD005-□	5 VDC	56 Ω	89 mA					
FBR211SAD006-□	FBR211NAD006-□	FBR211SBD006-□	FBR211NBD006-□	6 VDC	80 Ω	75 mA					
FBR211SAD009-□	FBR211NAD009-□	FBR211SBD009-□	FBR211NBD009-□	9 VDC	180 Ω	50 mA					
FBR211SAD012-□	FBR211NAD012-□	FBR211SBD012-□	FBR211NBD012-□	12 VDC	320 Ω	38 mA					
FBR211SAD024-□	FBR211NAD024-□	FBR211SBD024-□	FBR211NBD024-□	24 VDC	1,280 Ω	19 mA					

Note: All values in the table are measured at 20°C.

2. HIGH SENSITIVITY (C or E type)


MODEL				Nominal voltage	Coil resistance ($\pm 10\%$)	Nominal current (at nominal voltage) approx.	Must operate voltage	Must release voltage	Maximum allowable voltage	Nominal power	Coil temperature rise
C type		E type									
Flux free	Plastic sealed	Flux free	Plastic sealed								
FBR211SCD001-□	FBR211NCD001-□	FBR211SED001-□	FBR211NED001-□	1.5 VDC	12 Ω	125 mA	70% max. of nominal voltage	10% min. of nominal voltage	225% of nominal voltage	Approx. 200 mW (at nominal voltage)	Approx. 25 deg (at nominal voltage)
FBR211SCD003-□	FBR211NCD003-□	FBR211SED003-□	FBR211NED003-□	3 VDC	45 Ω	67 mA					
FBR211SCD005-□	FBR211NCD005-□	FBR211SED005-□	FBR211NED005-□	5 VDC	120 Ω	42 mA					
FBR211SCD006-□	FBR211NCD006-□	FBR211SED006-□	FBR211NED006-□	6 VDC	180 Ω	33 mA					
FBR211SCD009-□	FBR211NCD009-□	FBR211SED009-□	FBR211NED009-□	9 VDC	400 Ω	23 mA					
FBR211SCD012-□	FBR211NCD012-□	FBR211SED012-□	FBR211NED012-□	12 VDC	700 Ω	17 mA					
FBR211SCD024-□	FBR211NCD024-□	FBR211SED024-□	FBR211NED024-□	24 VDC	2,800 Ω	9 mA					

Note: All values in the table are measured at 20°C.


CHARACTERISTIC DATA

Range of operation temperature and voltage

(Standard 0.45 W type)




Coil temperature rise data




Range of operation temperature and voltage


(high sensitive 0.2 W type)




Maximum switching capacity



Operate and release time data




Life curve




FBR211 SERIES

REFERENCE DATA


Distribution of operate and release voltage



Distribution of operate and release time




Distribution of contact resistance



DIMENSIONS


1. STANDARD (Flux free type)

●Dimensions




●Schematics (BOTTOM VIEW)

(A type or C type)




(B type or E type)




2. N-TYPE (Plastic sealed type)

●Dimensions




●Schematics (BOTTOM VIEW)

(A type or C type)




(B type or E type)



3. PC BOARD MOUNTING HOLE LAYOUT

●PC board mounting hole layout (BOTTOM VIEW)



Unit: mm

FBR211 SERIES

Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@ft.ed.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: marcom@fcai.fujitsu.com
Web: www.fcai.fujitsu.com

Europe

Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info@fceu.fujitsu.com
Web: www.fceu.fujitsu.com

Asia Pacific

Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#04-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcal@fcal.fujitsu.com
www.fcal.fujitsu.com

© 2003 Fujitsu Components America, Inc. All company and product names are trademarks or registered trademarks of their respective owners. Rev. 02/18/2003