

FEATURES

- High Output Power: $P_{1dB} = 37.0\text{dBm}$ (Typ.)
- High Gain: $G_{1dB} = 5.5\text{dB}$ (Typ.)
- High PAE: $\eta_{add} = 20\%$ (Typ.)
- Low $IM_3 = -45\text{dBc}$ @ $P_o = 26.0\text{dBm}$ (Typ.)
- Broad Band: 14.5 ~ 15.3GHz
- Impedance Matched $Z_{in}/Z_{out} = 50\Omega$
- Hermetically Sealed

DESCRIPTION

The FLM1415-6F is a power GaAs FET that is internally matched for standard communication bands to provide optimum power and gain in a 50 ohm system.

Eudyna's stringent Quality Assurance Program assures the highest reliability and consistent performance.

ABSOLUTE MAXIMUM RATING (Ambient Temperature $T_a = 25^\circ\text{C}$)

Item	Symbol	Condition	Rating	Unit
Drain-Source Voltage	V_{DS}		15	V
Gate-Source Voltage	V_{GS}		-5	V
Total Power Dissipation	P_T	$T_c = 25^\circ\text{C}$	31.2	W
Storage Temperature	T_{stg}		-65 to +175	$^\circ\text{C}$
Channel Temperature	T_{ch}		175	$^\circ\text{C}$

Fujitsu recommends the following conditions for the reliable operation of GaAs FETs:


1. The drain-source operating voltage (V_{DS}) should not exceed 10 volts.
2. The forward and reverse gate currents should not exceed 26.0 and -2.8 mA respectively with gate resistance of 100 Ω .

ELECTRICAL CHARACTERISTICS (Ambient Temperature $T_a = 25^\circ\text{C}$)

Item	Symbol	Test Conditions	Limit			Unit
			Min.	Typ.	Max.	
Saturated Drain Current	I_{DSS}	$V_{DS} = 5\text{V}, V_{GS} = 0\text{V}$	-	2800	4200	mA
Transconductance	g_m	$V_{DS} = 5\text{V}, I_{DS} = 1800\text{mA}$	-	2350	-	mS
Pinch-off Voltage	V_p	$V_{DS} = 5\text{V}, I_{DS} = 120\text{mA}$	-0.5	-1.5	-3.0	V
Gate Source Breakdown Voltage	V_{GSO}	$I_{GS} = -120\mu\text{A}$	-5.0	-	-	V
Output Power at 1dB G.C.P.	P_{1dB}	$V_{DS} = 10\text{V},$ $I_{DS} = 0.6 I_{DSS}(\text{Typ.}),$ $f = 14.5 \sim 15.3 \text{GHz},$ $Z_S = Z_L = 50\Omega$	36.0	37.0	-	dBm
Power Gain at 1dB G.C.P.	G_{1dB}		4.5	5.5	-	dB
Drain Current	I_{dsr}		-	1800	2100	mA
Power-Added Efficiency	η_{add}		-	20	-	%
Gain Flatness	ΔG		-	-	± 0.6	dB
3rd Order Intermodulation Distortion	IM_3	$f = 15.3\text{GHz}, \Delta f = 10\text{MHz}$ 2-Tone Test $P_{out} = 26.0\text{dBm S.C.L.}$	-42	-45	-	dBc
Thermal Resistance	R_{th}	Channel to Case	-	4.0	4.5	$^\circ\text{C/W}$
Channel Temperature Rise	ΔT_{ch}	$10\text{V} \times I_{dsr} \times R_{th}$	-	-	80	$^\circ\text{C}$

CASE STYLE: IA


G.C.P.: Gain Compression Point, S.C.L.: Single Carrier Level




FLM1415-6F

Internally Matched Power GaAs FET


POWER DERATING CURVE




OUTPUT POWER & IM₃ vs. INPUT POWER



OUTPUT POWER vs. FREQUENCY




OUTPUT POWER vs. INPUT POWER



FLM1415-6F

Internally Matched Power GaAs FET



S-PARAMETERS

$V_{DS} = 10V$, $I_{DS} = 1800mA$


FREQUENCY (MHZ)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
14300	.487	65.7	1.862	123.5	.080	119.3	.676	-41.2
14400	.454	52.3	1.736	113.6	.087	108.0	.639	-47.6
14500	.422	37.2	1.858	103.3	.095	98.6	.591	-54.5
14600	.382	15.1	2.003	88.3	.106	82.3	.513	-65.1
14700	.355	-2.7	2.099	76.9	.116	71.5	.445	-73.6
14800	.333	-20.5	2.170	64.9	.122	60.2	.370	-82.7
14900	.317	-45.3	2.232	49.0	.129	44.3	.274	-96.6
15000	.309	-64.0	2.249	37.0	.132	33.9	.202	-109.1
15100	.302	-80.9	2.231	24.6	.133	22.5	.128	-124.1
15200	.301	-102.0	2.207	9.9	.137	7.5	.049	-171.9
15300	.308	-116.8	2.172	-1.7	.138	-3.1	.054	91.4
15400	.315	-130.4	2.108	-12.8	.139	-13.1	.118	59.1
15500	.316	-147.5	2.025	-26.9	.131	-27.7	.201	44.8

FLM1415-6F

Internally Matched Power GaAs FET

Case Style "IA"

Metal-Ceramic Hermetic Package



For further information please contact:

Eudyna Devices USA Inc.

2355 Zanker Rd.
San Jose, CA 95131-1138, U.S.A.
TEL: (408) 232-9500
FAX: (408) 428-9111
www.us.eudyna.com

Eudyna Devices Europe Ltd.

Network House
Norreys Drive
Maidenhead, Berkshire SL6 4FJ
United Kingdom
TEL: +44 (0) 1628 504800
FAX: +44 (0) 1628 504888

Eudyna Devices Asia Pte Ltd.

Hong Kong Branch
Rm. 1101, Ocean Centre, 5 Canton Rd.
Tsim Sha Tsui, Kowloon, Hong Kong
TEL: +852-2377-0227
FAX: +852-2377-3921

Eudyna Devices Inc.

Sales Division
1, Kanai-cho, Sakae-ku
Yokohama, 244-0845, Japan
TEL: +81-45-853-8156
FAX: +81-45-853-8170

CAUTION

Eudyna Devices Inc. products contain **gallium arsenide (GaAs)** which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- Do not put this product into the mouth.
- Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.
- Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.

Eudyna Devices Inc. reserves the right to change products and specifications without notice. The information does not convey any license under rights of Eudyna Devices Inc. or others.

© 2004 Eudyna Devices USA Inc.
Printed in U.S.A.