

MCC

Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

FRB2504

Features

- High Current($I_F(AV)=25A$)
- Low V_F for Forward Conduction Losses
- Glass Passivated Junction
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Marking:FRB2504

MAXIMUM RATINGS

Rating	Symbol	Value	Units
Peak Repetitive Reverse Voltage	V_{RRM}	400	V
Working Peak Reverse Voltage	V_{RRM}	400	V
DC Blocking Voltage	V_{DC}	400	V
Average Rectified Forward Current($T_C=100^\circ C$)	$I_{F(AV)}$	25	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	280	A
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-50 to 150	$^\circ C$

THERMAL CHARACTERISTICS

Rating	Symbol	Value	Units
Thermal Resistance Junction To Case	R_{thJC}	1	$^\circ C/watt$


ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	Conditions	Typical	Max	Units
Forward voltage(Note 1)	V_F	$I_F=25A$	1.17	1.3	V
		$I_F=50A$	1.35	1.5	
Reverse Leakage Current	I_R	$V_R=400V$	--	10	μA
Reverse Recovery Time	T_{rr}	$I_F=0.5A, I_R=1.0A$ $I_{RR}=0.25A$	110	250	ns

Note 1. Short duration pulse to minimize self-heating


25 Amp Surface Mount Fast Recovery Rectifier

D²-PACK



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.320	.359	8.13	9.14	
B	.380	.411	9.65	10.45	
C	.160	.190	4.06	4.83	
D	.020	.035	0.51	0.89	
E	.045	.055	1.14	1.40	
G	.095	.105	2.41	2.67	
H	.096	.120	2.43	3.03	
J	.014	.021	0.35	0.53	
K	.090	.110	2.29	2.79	
S	.575	.625	14.60	15.80	
V	.045	.055	1.14	1.40	

SUGGESTED SOLDER PAD LAYOUT



TYPICAL CHARACTERISTICS (T = 25°C unless otherwise noted)




Figure 1. Typical Forward Characteristics




Figure 2. Typical Reverse Characteristics




Figure 3. Current Derating Curves




Figure 4. Typical Capacitance



TM

Micro Commercial Components

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.