



HCMOS 32.768kHz 4x2.5mm SMD Oscillator

Model: F254 **RoHS Compliant / Pb Free** **Rev. 6/26/2008**

Page 1 of 2

http://www.foxonline.com/need_a_sample.htm

Need a Sample®

FEATURES

- Tight Stability
- HCMOS Output
- Operable 1.3V ~ 5.5V
- Tape and Reel (1,000 pcs. STD)


• PART NUMBER SELECTION [Learn More](#) - Internet Required

Part Number	Model Number	Frequency Stability	Operating Temperature (°C)	Frequency (kHz)
784-Frequency-xxxxx	F254	-120 ~ +10 PPM	-40 ~ +85	32.768

• ELECTRICAL CHARACTERISTICS


PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	32.768 kHz
Temperature Range	
Operating (TOPR)	-40°C ~ +85°C
Storage (TSTG)	-55°C ~ +125°C
Frequency Tolerance	
(VDD = 3.3V @ 25°C)	+5±20 PPM
Frequency Stability	
Over Temperature Range	
(-20°C ~ +70°C; ref @ 25°C)	-120 ~ +10 PPM
Supply Voltage (VDD)	3.3V ± 10% (+1.3V ~ +5.5V operable)
Input Current (IDD)	1.5 µA
Symmetry (50% VDD)	40/60%
Rise Time (TR)	200nS
Fall Time (TF)	200nS
Standby Current (IST)	250nA
Output Voltage (VOL)	0.4V
(VOH)	VDD - 0.4V Min
Output Load (HCMOS)	15pF
Start-up Time (Ts)	
(VDD = 1.3V ~ 5.5V, -40°C ~ +85°C)	1S
Reflow Soldering Temp	260°C x 10 Seconds
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au

¹ If Enable/Disable function is not used, please pull Pin 1 to a high potential.
Drawing is for reference to critical specifications defined by size measurements.
Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary. All specifications subject to change without notice.



• ENABLE / DISABLE FUNCTION

(Pin 1)	OUTPUT (Pin 3)
'1' Level VIH ≥ 90% VDD	ACTIVE ¹
'0' Level VIL ≤ 10% VDD	High Z



HCMOS 32.768kHz 4x2.5 SMD Oscillator



Model: F254

RoHS Compliant / Pb Free

Rev. 6/26/2008

Page 2 of 2

http://www.foxonline.com/need_a_sample.htm



• TAPE SPECIFICATIONS (millimeters)							
MODEL	A	B	C	D	E	F	STD Reel QTY
F254	∅1.5	4.0	4.0	5.5	12.0	1.3	1,000

• REEL SPECIFICATIONS (millimeters)							
MODEL	G	H	I	J	K	L	M
F254	2.0	∅13	∅21	∅80	∅178	13.0	1.5

