



GTM CORPORATION

GMBT5551 NPN EPITAXIAL PLANAR TRANSISTOR

Description

The GMBT5551 is designed for general purpose applications requiring high breakdown voltages.

Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0°	10°

Absolute Maximum Ratings


Parameter	Symbol	Ratings	Unit
Junction Temperature	T _j	+150	°C
Storage Temperature	T _{stg}	-55 ~ +150	°C
Collector to Base Voltage	VCBO	180	V
Collector to Emitter Voltage	VCES	160	V
Emitter to Base Voltage	VEBO	6.0	V
Collector Current	I _C	600	mA
Total Power Dissipation	PD	225	mW

Characteristics at Ta = 25°C

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BVCBO	180	-	-	V	I _C =100uA
BVCEO	160	-	-	V	I _C =1mA
BVEBO	6	-	-	V	I _E =10uA
ICBO	-	-	50	nA	V _{CB} =120V
IEBO	-	-	50	nA	V _{EB} =4V
VCE(sat)1	-	-	150	mV	I _C =10mA, I _B =1mA
VCE(sat)2	-	-	200	mV	I _C =50mA, I _B =5mA
VBE(sat)1	-	-	1	V	I _C =10mA, I _B =1mA
VBE(sat)2	-	-	1	V	I _C =50mA, I _B =5mA
hFE1	80	-	-		V _{CE} =5V, I _C =1mA
hFE2	80	-	250		V _{CE} =5V, I _C =10mA
hFE3	30	-	-		V _{CE} =5V, I _C =50mA
f _T	100	-	300	MHz	V _{CE} =10V, I _C =10mA, f=100MHz
Cob	-	-	6	pF	V _{CB} =10V, f=1MHz



Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 FAX : 86-21-38950165