

# GTM CORPORATION

ISSUED DATE :2004/11/24  
REVISED DATE :2005/12/02C

## GS3018

N-CHANNEL MOSFET

BVDSS	30V
RDS(ON)	8Ω
ID	115mA




### Description

N-channel enhancement-mode MOSFET

### Features

- Low on-resistance.
- Fast switching speed.
- Low voltage drive (2.5V) makes this device ideal for portable equipment.
- Easily designed drive circuits.
- Easy to parallel.

### Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	0.8	1.10	L1	0.42	REF.
A1	0	0.10	L	0.15	0.35
A2	0.8	1.00	b	0.25	0.40
D	1.80	2.20	c	0.10	0.25
E	1.15	1.35	e	0.65	REF.
HE	1.80	2.40	Q1	0.15	BSC.

### Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	±20	V
Continuous Drain Current <sup>3</sup>	$I_D @TA=25^{\circ}C$	115	mA
Continuous Drain Current <sup>3</sup>	$I_D @TA=100^{\circ}C$	75	mA
Pulsed Drain Current <sup>1,2</sup>	$I_{DM}$	800	mA
Power Dissipation	$P_D @TA=25^{\circ}C$	0.225	W
Linear Derating Factor		0.0018	W/°C
Operating Junction and Storage Temperature Range	$T_j, T_{stg}$	-40 ~ +150	°C

### Thermal Data

Parameter	Symbol	Ratings	Unit
Thermal Resistance Junction-ambient <sup>3</sup> Max.	$R_{thj-a}$	556	°C/W



**Electrical Characteristics(T<sub>j</sub> = 25°C Unless otherwise specified)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	30	-	-	V	V <sub>GS</sub> =0, I <sub>D</sub> =250uA
Gate Threshold Voltage	V <sub>GS(th)</sub>	0.8	-	2.0	V	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =0.1mA
Forward Transconductance	g <sub>fs</sub>	20	-	-	mS	V <sub>DS</sub> =3V, I <sub>D</sub> =10mA
Gate-Source Leakage Current	I <sub>GSS</sub>	-	-	±1	uA	V <sub>GS</sub> = ±20V
Drain-Source Leakage Current	I <sub>DSS</sub>	-	-	1	uA	V <sub>DS</sub> =30V, V <sub>GS</sub> =0
Static Drain-Source On-Resistance	R <sub>DS(ON)</sub>	-	5	8	Ω	V <sub>GS</sub> =4V, I <sub>D</sub> =10mA
		-	7	13		V <sub>GS</sub> =2.5V, I <sub>D</sub> =1mA
Input Capacitance	C <sub>iss</sub>	-	-	50	pF	V <sub>GS</sub> =0V V <sub>DS</sub> =5V f=1.0MHz
Output Capacitance	C <sub>oss</sub>	-	-	25		
Reverse Transfer Capacitance	C <sub>rss</sub>	-	-	5		

**Source-Drain Diode**







Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage <sup>2</sup>	V <sub>SD</sub>	-	0.84	1.5	V	I <sub>S</sub> =100mA, V <sub>GS</sub> =0V





Notes: 1. Pulse width limited by Max. junction temperature.

2. Pulse width ≤ 300us, duty cycle ≤ 2%.

3. Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board; 270°C/W when mounted on Min. copper pad.

## Characteristics Curve





**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165