查询HAT1048R供应商 捷多邦，专业PCB打样工厂，24小时加急出货

HAT1048R

Silicon P Channel Power MOS FET
Power Switching

ADE-208-1223A (Z)
2nd. Edition
Jan. 2001

Features

- Capable of -4.5 V gate drive
- Low drive current
- High density mounting
- Low on-resistance
  $R_{DS(on)}$ = 6.0 mΩ typ (at V_{GS} = -10V)

Outline

SOP-8



1, 2, 3	Source
4	Gate
5, 6, 7, 8	Drain

找PDF 维库一下 pdf.dzsc.com

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Drain to source voltage	V_{DSS}	-30	V
Gate to source voltage	V_{GSS}	± 20	V
Drain current	I_D	-16	A
Drain peak current	$I_{D(pulse)}$ Note1	-128	A
Body-drain diode reverse drain current	I_{DR}	-16	A
Channel dissipation	Pch Note2	2.5	W
Channel to Ambient Thermal Impedance	θch-a Note2	50	°C/W
Channel temperature	Tch	150	°C
Storage temperature	Tstg	– 55 to + 150	°C

Note: 1. PW ≤ 10 μs, duty cycle ≤ 1%
2. When using the glass epoxy board (FR4 40 x 40 x 1.6 mm), PW ≤ 10s

Electrical Characteristics (Ta = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Conditions
Drain to source breakdown voltage	$V_{(BR)DSS}$	-30	—	—	V	I_D = -10 mA, V_{GS} = 0
Gate to source breakdown voltage	$V_{(BR)GSS}$	± 20	—	—	V	I_G = ±100 μA, V_{DS} = 0
Gate to source leak current	I_{GSS}	—	—	± 10	μA	V_{GS} = ±16 V, V_{DS} = 0
Zero gate voltege drain current	I_{DSS}	—	—	-1	μA	V_{DS} = -30 V, V_{GS} = 0
Gate to source cutoff voltage	$V_{GS(off)}$	-1.0	—	-2.5	V	V_{DS} = -10 V, I_D = -1 mA
Static drain to source on state resistance	$R_{DS(on)}$	—	(6.0)	(7.0)	mΩ	I_D = -8 A, V_{GS} = -10 V Note3
	$R_{DS(on)}$	—	(9.5)	(13.5)	mΩ	I_D = -8 A, V_{GS} = -4.5V Note3
Forward transfer admittance	$\|y_{fs}\|$	(18)	(30)	—	S	I_D = -8 A, V_{DS} = -10 V Note3
Input capacitance	Ciss	—	(5700)	—	pF	V_{DS} = -10 V
Output capacitance	Coss	—	(1250)	—	pF	V_{GS} = 0
Reverse transfer capacitance	Crss	—	(710)	—	pF	f = 1 MHz
Total gate charge	Qg	—	(105)	—	nc	V_{DD} = -10 V
Gate to source charge	Qgs	—	(14)	—	nc	V_{GS} = -10 V
Gate to drain charge	Qgd	—	(20)	—	nc	I_D = -16 A
Turn-on delay time	$t_{d(on)}$	—	(25)	—	ns	V_{GS} = -10 V, I_D = -8 A
Rise time	t_r	—	(45)	—	ns	V_{DD} ≅ 10 V
Turn-off delay time	$t_{d(off)}$	—	(140)	—	ns	R_L = 1.25 Ω
Fall time	t_f	—	(55)	—	ns	R_g = 4.7 Ω
Body–drain diode forward voltage	V_{DF}	—	(-0.85)	(-1.10)	V	IF = -16 A, V_{GS} = 0 Note3
Body–drain diode reverse recovery time	t_{rr}	—	(50)	—	ns	IF = -16 A, V_{GS} = 0 diF/ dt = 50 A/ μs

Note: 3. Pulse test

Package Dimensions

As of January, 2001

Unit: mm



*Dimension including the plating thickness / Base material dimension

Hitachi Code	FP-8DA
JEDEC	Conforms
EIAJ	—
Mass (reference value)	0.085 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.
Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL NorthAmerica : http://semiconductor.hitachi.com/
Europe : http://www.hitachi-eu.com/hel/ecg
Asia : http://sicapac.hitachi-asia.com
Japan : http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor (America) Inc.
179 East Tasman Drive,
San Jose,CA 95134
Tel: <1> (408) 433-1990
Fax: <1>(408) 433-0223

Hitachi Europe GmbH
Electronic Components Group
Dornacher Straβe 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 585160

Hitachi Asia Ltd.
Hitachi Tower
16 Collyer Quay #20-00,
Singapore 049318
Tel : <65>-538-6533/538-8577
Fax : <65>-538-6933/538-3877
URL : http://www.hitachi.com.sg

Hitachi Asia Ltd.
(Taipei Branch Office)
4/F, No. 167, Tun Hwa North Road,
Hung-Kuo Building,
Taipei (105), Taiwan
Tel : <886>-(2)-2718-3666
Fax : <886>-(2)-2718-8180
Telex : 23222 HAS-TP
URL : http://www.hitachi.com.tw

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon,
Hong Kong
Tel : <852>-(2)-735-9218
Fax : <852>-(2)-730-0281
URL : http://www.hitachi.com.hk

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 2.0