

查询HMC435MS8G\_07供应商

捷多邦，专业PCB打样工厂，24小时加急出货



v03.0607



# HMC435MS8G / 435MS8GE

## SPDT NON-REFLECTIVE SWITCH, DC - 4.0 GHz

### Typical Applications

The HMC435MS8G / HMC435MS8GE is ideal for:

- Basestation Infrastructure
- MMDS & 3.5 GHz WLL
- CATV/CMTS
- Test Instrumentation

### Features

High Isolation: 60 dB @ 1 GHz  
50 dB @ 2 GHz


Positive Control: 0/+5V

51 dBm Input IP3

Non-Reflective Design

MS8G SMT Package, 14.8 mm<sup>2</sup>

### Functional Diagram



### General Description

The HMC435MS8G & HMC435MS8GE are non-reflective DC to 4 GHz GaAs MESFET SPDT switches in low cost 8 lead MSOP8G surface mount packages with exposed ground paddles. The switch is ideal for cellular/PCS/3G basestation applications yielding 50 to 60 dB isolation, low 0.8 dB insertion loss and +50 dBm input IP3. Power handling is excellent up through the 3.5 GHz WLL band with the switch offering a P1dB compression point of +31 dBm. On-chip circuitry allows positive voltage control of 0/+5 Volts at very low DC currents.


### Electrical Specifications, $T_A = +25^\circ \text{C}$ , $V_{ctl} = 0/+5 \text{ Vdc}$ , 50 Ohm System

Parameter	Frequency	Min.	Typ.	Max.	Units
Insertion Loss	DC - 2.5 GHz		0.8	1.0	dB
	DC - 3.6 GHz		1.2	1.5	dB
	DC - 4.0 GHz		1.5	1.8	dB
Isolation (RFC to RF1/RF2)	DC - 1.0 GHz	56	60		dB
	DC - 2.0 GHz	46	50		dB
	DC - 2.5 GHz	43	47		dB
	DC - 3.6 GHz	37	41		dB
	DC - 4.0 GHz	30	35		dB
Return Loss (On State)	DC - 2.5 GHz	15	20		dB
	DC - 3.6 GHz	13	17		dB
	DC - 4.0 GHz	11	15		dB
Return Loss (Off State)					
Return Loss (Off State)	0.5 - 4.0 GHz	16	21		dB
Input Power for 1 dB Compression	0.5 - 4.0 GHz	27	31		dBm
Input Third Order Intercept (Two-Tone Input Power = +7 dBm Each Tone)	0.5 - 1.0 GHz	48	51		dBm
	0.5 - 2.5 GHz	45	48		
	0.5 - 4.0 GHz	41	45		
Switching Speed	DC - 4.0 GHz				
	tRISE, tFALL (10/90% RF)		40		ns
	tON, tOFF (50% CTL to 10/90% RF)		60		ns


## HMC435MS8G / 435MS8GE

### SPDT NON-REFLECTIVE SWITCH, DC - 4.0 GHz


**Insertion Loss**




**Return Loss**




**Isolation Between  
Ports RFC and RF1 / RF2**




**Isolation Between Ports RF1 and RF2**



**0.1 and 1 dB Input Compression Point**



**Input Third Order Intercept Point**





MICROWAVE CORPORATION v03.0607



## HMC435MS8G / 435MS8GE

### SPDT NON-REFLECTIVE SWITCH, DC - 4.0 GHz

#### Absolute Maximum Ratings

Control Voltage Range	-0.5 to +7.5 Vdc
Storage Temperature	-65 to +150 °C
Operating Temperature	-40 to +85 °C
RF Input Power Vctl = 0/+5V	+31 dBm
ESD Sensitivity (HBM)	Class 1A



ELECTROSTATIC SENSITIVE DEVICE  
OBSERVE HANDLING PRECAUTIONS

#### Control Voltages

\*Control Input Tolerances are  $\pm 0.2$  Vdc

State	Bias Condition*
Low	0 Vdc @ 25 $\mu$ A Typical
High	+5 Vdc @ 25 $\mu$ A Typical

#### Truth Table

Control Input		Signal Path State
A	B	RFC to:
Low	High	RF1
High	Low	RF2

DC blocks are required at ports RFC, RF1, RF2.

Do not operate continuously at RF power input greater than 1 dB compression and do not **"Hot Switch"** power levels greater than +24 dBm (control = 0/+5 Vdc).



MICROWAVE CORPORATION


v03.0607



# HMC435MS8G / 435MS8GE

**SPDT NON-REFLECTIVE  
SWITCH, DC - 4.0 GHz**

## Outline Drawing



## Package Information

Part Number	Package Body Material	Lead Finish	MSL Rating	Package Marking <sup>[3]</sup>
HMC435MS8G	Low Stress Injection Molded Plastic	Sn/Pb Solder	MSL1 <sup>[1]</sup>	H435 XXXX
HMC435MS8GE	RoHS-compliant Low Stress Injection Molded Plastic	100% matte Sn	MSL1 <sup>[2]</sup>	H435 XXXX

[1] Max peak reflow temperature of 235 °C



[2] Max peak reflow temperature of 260 °C

[3] 4-Digit lot number XXXX

## HMC435MS8G / 435MS8GE

**SPDT NON-REFLECTIVE  
SWITCH, DC - 4.0 GHz**


### Pin Descriptions

Pin Number	Function	Description	Interface Schematic
1	A	See truth and control voltage tables.	
2	B	See truth and control voltage tables.	
3, 5, 8	RFC, RF1, RF2	These pins are DC coupled and matched to 50 Ohms. Blocking capacitors are required.	
4	N/C	Not Connected	
6, 7	GND	Package bottom has exposed metal paddle that must be connected to PCB RF ground as well.	

## HMC435MS8G / 435MS8GE

**SPDT NON-REFLECTIVE  
SWITCH, DC - 4.0 GHz**

### Evaluation PCB



### List of Materials for Evaluation PCB 105143 <sup>[1]</sup>

Item	Description
J1 - J3	PCB Mount SMA RF Connector
J4 - J7	DC Pin
C1 - C3	100 pF Capacitor, 0402 Pkg.
R1 - R2	100 Ohm Resistor, 0402 Pkg.
U1	HMC435MS8G / HMC435MS8GE SPDT Switch
PCB <sup>[2]</sup>	104122 Evaluation PCB

[1] Reference this number when ordering complete evaluation PCB

[2] Circuit Board Material: Rogers 4350

Note: Pin J6 is unused and need not be connected.

The circuit board used in the final application should be generated with proper RF circuit design techniques. Signal lines at the RF port should have 50 ohm impedance and the package ground leads and backside ground slug should be connected directly to the ground plane similar to that shown above. The evaluation circuit board shown above is available from Hittite Microwave Corporation upon request.