




## DUAL PNP SMALL SIGNAL SURFACE MOUNT TRANSISTOR

## Features

- Epitaxial Planar Die Construction
- Complementary NPN Type Available (IMX8)
- Small Surface Mount Package
- Lead Free/RoHS Compliant (Note 3)
- "Green" Device, Note 4 and 5

## Mechanical Data

- Case: SOT-26
- Case Material: Molded Plastic, "Green" Molding Compound, Note 5. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Copper leadframe).
- Marking: KX7, See Page 2
- Ordering & Date Code Information: See Page 2
- Weight: 0.016 grams (approximate)



SOT-26			
Dim	Min	Max	Typ
A	0.35	0.50	0.38
B	1.50	1.70	1.60
C	2.70	3.00	2.80
D			0.95
F			0.55
H	2.90	3.10	3.00
J	0.013	0.10	0.05
K	1.00	1.30	1.10
L	0.35	0.55	0.40
M	0.10	0.20	0.15
	0	8°	

All Dimensions in mm

Maximum Ratings @  $T_A = 25^\circ C$  unless otherwise specified

Characteristic	Symbol	Value		Unit
Collector-Base Voltage	$V_{CBO}$	-120		V
Collector-Emitter Voltage	$V_{CEO}$	-120		V
Emitter-Base Voltage	$V_{EBO}$	-5.0		V
Collector Current - Continuous	$I_C$	-50		mA
Power Dissipation (Note 1)	$P_d$	225		mW
Thermal Resistance, Junction to Ambient (Note 1)	$R_{JA}$	555		C/W
Operating and Storage Temperature Range	$T_j, T_{STG}$	-55 to +150		C

Electrical Characteristics @  $T_A = 25^\circ C$  unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS (Note 2)</b>						
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-120			V	$I_C = -50 \text{ A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-120			V	$I_C = -1.0 \text{ mA}$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5.0			V	$I_E = -50 \text{ A}$
Collector Cutoff Current	$I_{CBO}$			-0.5	A	$V_{CB} = -100V$
Emitter Cutoff Current	$I_{EBO}$			-0.5	A	$V_{EB} = -4.0V$
<b>ON CHARACTERISTICS (Note 2)</b>						
DC Current Gain	$h_{FE}$	180		820		$I_C = -2.0 \text{ mA}, V_{CE} = -6.0V$
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$			-0.5	V	$I_C = -10 \text{ mA}, I_B = -1.0 \text{ mA}$
<b>SMALL SIGNAL CHARACTERISTICS</b>						
Current Gain-Bandwidth Product	$f_T$		140		MHz	$V_{CE} = -12V, I_C = -2.0 \text{ mA}, f = 100 \text{ MHz}$

Notes: 1. Device mounted on FR-5 PCB 1.0 x 0.75 x 0.062 inch pad layout as shown on Diodes Inc. suggested pad layout AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>. 200mW per element must not be exceeded.

2. Short duration pulse test used to minimize self-heating effect.

3. No purposefully added lead.

4. Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).


5. Product manufactured with Date Code 0609 (week 9, 2006) and newer are built with Green Molding Compound. Product manufactured prior to Date Code 0609 are built with Non-Green Molding Compound and may contain Halogens or Sb<sub>2</sub>O<sub>3</sub> Fire Retardants.

## Ordering Information (Note 5 & 6)

Device	Packaging	Shipping
IMT4-7-F	SOT-26	3000/Tape & Reel



Notes: 5. Product manufactured with Date Code 0609 (week 9, 2006) and newer are built with Green Molding Compound. Product manufactured prior to Date Code 0609 are built with Non-Green Molding Compound and may contain Halogens or Sb<sub>2</sub>O<sub>3</sub> Fire Retardants.  
6. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



### Date Code Key

Year	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
Code	N	P	R	S	T	U	V	W	X	Y	Z	
Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D






Fig. 3 Typical Collector Current vs.  
Base-Emitter Voltage




Fig. 4 Typical Collector-Emitter Voltage  
vs. Collector Current




Fig. 5 Typical Gain Bandwidth Product  
vs. Collector Current




Fig. 6 Typical Collector Current vs.  
Collector-Emitter Voltage



#### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

#### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.