




# PolarHV™ Power MOSFET

IXTP 2N60P  
IXTY 2N60P


$$\begin{aligned} V_{DSS} &= 500 \text{ V} \\ I_{D25} &= 2 \text{ A} \\ R_{DS(on)} &\leq 5.1 \Omega \end{aligned}$$

N-Channel Enhancement Mode  
Avalanche Rated




| Symbol     | Test Conditions                                                                                                                          | Maximum Ratings |                  |
|------------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------------|
| $V_{DSS}$  | $T_J = 25^\circ\text{C to } 150^\circ\text{C}$                                                                                           | 600             | V                |
| $V_{DGR}$  | $T_J = 25^\circ\text{C to } 150^\circ\text{C}; R_{GS} = 1 \text{ M}\Omega$                                                               | 600             | V                |
| $V_{GSS}$  | Continuous                                                                                                                               | $\pm 30$        | V                |
| $V_{GSM}$  | Transient                                                                                                                                | $\pm 40$        | V                |
| $I_{D25}$  | $T_C = 25^\circ\text{C}$                                                                                                                 | 2               | A                |
| $I_{DM}$   | $T_C = 25^\circ\text{C}$ , pulse width limited by $T_{JM}$                                                                               | 4               | A                |
| $I_{AR}$   | $T_C = 25^\circ\text{C}$                                                                                                                 | 2               | A                |
| $E_{AR}$   | $T_C = 25^\circ\text{C}$                                                                                                                 | 10              | mJ               |
| $E_{AS}$   | $T_C = 25^\circ\text{C}$                                                                                                                 | 150             | mJ               |
| $dv/dt$    | $I_S \leq I_{DM}$ , $di/dt \leq 100 \text{ A}/\mu\text{s}$ , $V_{DD} \leq V_{DSS}$ ,<br>$T_J \leq 150^\circ\text{C}$ , $R_G = 50 \Omega$ | 10              | V/ns             |
| $P_D$      | $T_C = 25^\circ\text{C}$                                                                                                                 | 55              | W                |
| $T_J$      |                                                                                                                                          | -55 ... +150    | $^\circ\text{C}$ |
| $T_{JM}$   |                                                                                                                                          | 150             | $^\circ\text{C}$ |
| $T_{stg}$  |                                                                                                                                          | -55 ... +150    | $^\circ\text{C}$ |
| $T_L$      | 1.6 mm (0.062 in.) from case for 10 s                                                                                                    | 300             | $^\circ\text{C}$ |
| $T_{SOLD}$ | Plastic body for 10 s                                                                                                                    | 260             | $^\circ\text{C}$ |
| $M_d$      | Mounting torque (TO-220)                                                                                                                 | 1.13/10         | Nm/lb.in.        |
| Weight     | TO-220                                                                                                                                   | 4               | g                |
|            | TO-252                                                                                                                                   | 0.8             | g                |

TO-220 (IXTP)



TO-252 AA (IXTY)



G = Gate  
S = Source

D = Drain  
TAB = Drain

## Features

- International standard packages
- Unclamped Inductive Switching (UIS) rated
- Low package inductance
  - easy to drive and to protect

## Advantages

- Easy to mount
- Space savings
- High power density


| Symbol       | Test Conditions                                                                                                 | Characteristic Values |      |                     |
|--------------|-----------------------------------------------------------------------------------------------------------------|-----------------------|------|---------------------|
|              |                                                                                                                 | Min.                  | Typ. | Max.                |
| $BV_{DSS}$   | $V_{GS} = 0 \text{ V}$ , $I_D = 25 \mu\text{A}$                                                                 | 600                   |      | V                   |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$ , $I_D = 250 \mu\text{A}$                                                                     | 3.0                   |      | 5.0 V               |
| $I_{GSS}$    | $V_{GS} = \pm 30 \text{ V}$ , $V_{DS} = 0 \text{ V}$                                                            |                       |      | $\pm 50 \text{ nA}$ |
| $I_{DSS}$    | $V_{DS} = V_{DSS}$                                                                                              |                       |      | 1 $\mu\text{A}$     |
|              | $V_{GS} = 0 \text{ V}$ , $T_J = 125^\circ\text{C}$                                                              |                       |      | 50 $\mu\text{A}$    |
| $R_{DS(on)}$ | $V_{GS} = 10 \text{ V}$ , $I_D = 0.5 I_{D25}$<br>Pulse test, $t \leq 300 \mu\text{s}$ , duty cycle $d \leq 2\%$ |                       |      | 5.1 $\Omega$        |



| Symbol                    | Test Conditions                                                                                                                            | Characteristic Values<br>(T <sub>J</sub> = 25° C, unless otherwise specified) |      |           |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|------|-----------|
|                           |                                                                                                                                            | Min.                                                                          | Typ. | Max.      |
| <b>g<sub>fs</sub></b>     | V <sub>DS</sub> = 20 V; I <sub>D</sub> = 0.5 I <sub>D25</sub> , pulse test                                                                 | 1.4                                                                           | 2.2  | S         |
| <b>C<sub>iss</sub></b>    | V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 25 V, f = 1 MHz                                                                                   |                                                                               | 240  | pF        |
| <b>C<sub>oss</sub></b>    |                                                                                                                                            |                                                                               | 28   | pF        |
| <b>C<sub>rss</sub></b>    |                                                                                                                                            |                                                                               | 3.5  | pF        |
| <b>t<sub>d(on)</sub></b>  | V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 0.5 V <sub>DSS</sub> , I <sub>D</sub> = 0.5 I <sub>D25</sub><br>R <sub>G</sub> = 50 Ω (External) |                                                                               | 28   | ns        |
| <b>t<sub>r</sub></b>      |                                                                                                                                            |                                                                               | 20   | ns        |
| <b>t<sub>d(off)</sub></b> |                                                                                                                                            |                                                                               | 60   | ns        |
| <b>t<sub>f</sub></b>      |                                                                                                                                            |                                                                               | 23   | ns        |
| <b>Q<sub>g(on)</sub></b>  | V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 0.5 V <sub>DSS</sub> , I <sub>D</sub> = 0.5 I <sub>D25</sub>                                     |                                                                               | 7.0  | nC        |
| <b>Q<sub>gs</sub></b>     |                                                                                                                                            |                                                                               | 2.5  | nC        |
| <b>Q<sub>gd</sub></b>     |                                                                                                                                            |                                                                               | 2.1  | nC        |
| <b>R<sub>thJC</sub></b>   | (TO-220)                                                                                                                                   |                                                                               | 0.25 | 2.25° C/W |
| <b>R<sub>thCS</sub></b>   |                                                                                                                                            |                                                                               |      |           |

| Source-Drain Diode    |                                                                                                        | Characteristic Values<br>(T <sub>J</sub> = 25° C unless otherwise specified) |      |       |
|-----------------------|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------|-------|
| Symbol                | Test Conditions                                                                                        | Min.                                                                         | Typ. | Max.  |
| <b>I<sub>S</sub></b>  | V <sub>GS</sub> = 0 V                                                                                  |                                                                              |      | 2 A   |
| <b>I<sub>SM</sub></b> | Repetitive                                                                                             |                                                                              |      | 6 A   |
| <b>V<sub>SD</sub></b> | I <sub>F</sub> = I <sub>S</sub> , V <sub>GS</sub> = 0 V,<br>Pulse test, t ≤ 300 μs, duty cycle d ≤ 2 % |                                                                              |      | 1.5 V |
| <b>t<sub>rr</sub></b> | I <sub>F</sub> = 2 A<br>-di/dt = 100 A/μs                                                              |                                                                              | 400  | ns    |


## TO-220 (IXTP) Outline



Pins: 1 - Gate 2 - Drain  
3 - Source 4 - Drain

| SYM | INCHES   |      | MILLIMETERS |       |
|-----|----------|------|-------------|-------|
|     | MIN      | MAX  | MIN         | MAX   |
| A   | .170     | .190 | 4.32        | 4.83  |
| b   | .025     | .040 | 0.64        | 1.02  |
| b1  | .045     | .065 | 1.15        | 1.65  |
| c   | .014     | .022 | 0.35        | 0.56  |
| D   | .580     | .630 | 14.73       | 16.00 |
| E   | .390     | .420 | 9.91        | 10.66 |
| e   | .100 BSC |      | 2.54 BSC    |       |
| F   | .045     | .055 | 1.14        | 1.40  |
| H1  | .230     | .270 | 5.85        | 6.85  |
| J1  | .090     | .110 | 2.29        | 2.79  |
| k   | 0        | .015 | 0           | 0.38  |
| L   | .500     | .550 | 12.70       | 13.97 |
| L1  | .110     | .230 | 2.79        | 5.84  |
| ØP  | .139     | .161 | 3.53        | 4.08  |
| Q   | .100     | .125 | 2.54        | 3.18  |


## TO-252 AA (IXTY) Outline




Pins: 1 - Gate 3 - Source  
4 - Drain

| Dim. | Millimeter |       | Inches    |       |
|------|------------|-------|-----------|-------|
|      | Min.       | Max.  | Min.      | Max.  |
| A    | 2.19       | 2.38  | 0.086     | 0.094 |
| A1   | 0.89       | 1.14  | 0.035     | 0.045 |
| A2   | 0          | 0.13  | 0         | 0.005 |
| b    | 0.64       | 0.89  | 0.025     | 0.035 |
| b1   | 0.76       | 1.14  | 0.030     | 0.045 |
| b2   | 5.21       | 5.46  | 0.205     | 0.215 |
| c    | 0.46       | 0.58  | 0.018     | 0.023 |
| c1   | 0.46       | 0.58  | 0.018     | 0.023 |
| D    | 5.97       | 6.22  | 0.235     | 0.245 |
| D1   | 4.32       | 5.21  | 0.170     | 0.205 |
| E    | 6.35       | 6.73  | 0.250     | 0.265 |
| E1   | 4.32       | 5.21  | 0.170     | 0.205 |
| e    | 2.28 BSC   |       | 0.090 BSC |       |
| e1   | 4.57 BSC   |       | 0.180 BSC |       |
| H    | 9.40       | 10.42 | 0.370     | 0.410 |
| L    | 0.51       | 1.02  | 0.020     | 0.040 |
| L1   | 0.64       | 1.02  | 0.025     | 0.040 |
| L2   | 0.89       | 1.27  | 0.035     | 0.050 |
| L3   | 2.54       | 2.92  | 0.100     | 0.115 |


**Fig. 1. Output Characteristics**  
**@ 25°C**




**Fig. 2. Extended Output Characteristics**  
**@ 25°C**




**Fig. 3. Output Characteristics**  
**@ 125°C**




**Fig. 4.  $R_{DS(on)}$  Normalized to 0.5  $I_{D25}$  Value vs. Junction Temperature**




**Fig. 5.  $R_{DS(on)}$  Normalized to 0.5  $I_{D25}$  Value vs.  $I_D$**




**Fig. 6. Drain Current vs. Case Temperature**




**Fig. 7. Input Admittance**




**Fig. 8. Transconductance**




**Fig. 9. Source Current vs. Source-To-Drain Voltage**



**Fig. 10. Gate Charge**



**Fig. 11. Capacitance**



**Fig. 13. Maximum Transient Thermal Resistance**

