



TECHNICAL DATA

PNP SILICON SMALL SIGNAL TRANSISTOR

Qualified per MIL-PRF-19500/382

Devices

2N2944A 2N2945A 2N2946A


Qualified Level

JAN
JANTX
JANTV

MAXIMUM RATINGS

Ratings	Sym	2N2944A	2N2945A	2N2946A	Unit
Collector-Emitter Voltage	V_{CEO}	10	20	35	Vdc
Emitter-Collector Voltage	V_{ECO}	10	20	35	Vdc
Collector-Base Voltage	V_{CBO}	15	25	40	Vdc
Emitter-Base Voltage	V_{EBO}	15	25	40	Vdc
Collector Current	I_C	100			mAdc
Total Power Dissipation @ $T_A = +25^{\circ}C$	$P_T^{(1)}$	400			mW
Operating & Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200			$^{\circ}C$

1) Derate linearly 2.30 mW/ $^{\circ}C$ above $T_A = +25^{\circ}C$



*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_A = 25^{\circ}C$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage $I_C = 10 \mu A_{dc}$	$V_{(BR)CEO}$	10		Vdc
		20		
		35		
Emitter-Collector Breakdown Voltage $I_E = 10 \mu A_{dc}$	$V_{(BR)ECO}$	10		Vdc
		20		
		35		
Collector-Base Cutoff Current $I_C = 10 \mu A_{dc}, V_{CB} = -15 V_{dc}$	I_{CBO}	10		μA_{dc}
$I_C = 10 \mu A_{dc}, V_{CB} = -25 V_{dc}$		10		μA_{dc}
$I_C = 10 \mu A_{dc}, V_{CB} = -40 V_{dc}$		10		μA_{dc}



2N2944A, 2N2945A, 2N2946A JAN SERIES

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
Emitter-Base Cutoff Current	I_{EBO}			ηA_{dc}
$V_{EB} = 15 \text{ Vdc}$ 2N2944A				
$V_{EB} = 25 \text{ Vdc}$ 2N2945A				
$V_{EB} = 40 \text{ Vdc}$ 2N2946A				

ON CHARACTERISTICS (2)

Forward-Current Transfer Ratio $I_C = 1.0 \text{ mAdc}, V_{CE} = 0.5 \text{ Vdc}$	h_{FE}		100	
2N2944A			70	
2N2945A			50	
Forward-Current Transfer Ratio $I_B = 200 \mu\text{Adc}, V_{EC} = -0.5 \text{ Vdc}$	$h_{FE(INV)}$		50	
2N2944A			30	
2N2945A			20	
Emitter-Collector Offset Voltage $I_B = 200 \mu\text{Adc}, I_E = 0$	$V_{EC(OFS)}$			0.3
2N2944A			0.5	
2N2945A			0.8	
2N2946A			0.6	
$I_B = 1.0 \text{ mAdc}, I_E = 0$			1.0	
2N2944A			2.0	
2N2945A			1.0	
2N2946A			1.6	
$I_B = 2.0 \text{ mAdc}, I_E = 0$			2.5	
2N2944A				
2N2945A				
2N2946A				

DYNAMIC CHARACTERISTICS

Emitter-Collector On-State Resistance $I_B = 100 \mu\text{Adc}, I_E = 0, I_c = 100 \mu\text{Adc (rms)}$ $f = 1.0 \text{ kHz}$	$r_{ec^{(on)}}$			10	Ω
2N2944A			12		
2N2945A			14		
$I_B = 1.0 \text{ mAdc}, I_E = 0, I_c = 100 \mu\text{Adc (rms)}$ $f = 1.0 \text{ kHz}$				4.0	
2N2944A			6.0		
2N2945A			8.0		
2N2946A					
Magnitude of Small-Signal Forward Current Transfer Ratio $I_C = 1.0 \text{ mAdc}, V_{CE} = 6.0 \text{ Vdc}, f = 1.0 \text{ MHz}$	h_{fe}		15	55	
2N2944A			10	55	
2N2945A			5.0	55	
2N2946A					
Output Capacitance $V_{CB} = 6.0 \text{ Vdc}, I_E = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{obo}			10	pF
Input Capacitance $V_{EB} = 6.0 \text{ Vdc}, I_C = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{ibo}			6.0	pF

(2) Pulse Test: Pulse Width = 300 μ s, Duty Cycle \leq 2.0%.