



# COSMO High Voltage, Solid State Relay-MOSFET Output KAQW217/217A

UL 1577/ UL 508 (File No.E108430), FI EN60950 (File No.FI13698)


## Features

1. Normally Open, Single Pole Single Throw
2. Control 200VAC or DC Voltage
3. Switch 180mA Loads
4. LED control Current, 5mA
5. Low ON-Resistance
6. dv/dt, >500V/ms
7. Isolation Test Voltage, 3750VACrms



## Absolute Maximum Ratings (Ta=25°C)

| Emitter ( Input )                          | Detector ( Output )                          |
|--|--|
| Reverse Voltage.....5.0V                   | Output Breakdown Voltage .....±200V          |
| Continuous Forward Current .....50mA       | Continuous Load Current .....±180mA          |
| Peak Forward Current .....1A               | Power Dissipation .....450mW                 |
| Power Dissipation .....75mW                |  |
| Derate Linearly from 25°C .....1.3mW/°C    |  |
| <b>General Characteristics</b>             |  |
| Isolation Test Voltage .....3750VACrms     | Storage Temperature Range ...-40°C to +150°C |
| Isolation Resistance                       | Operating Temperature Range...-40°C to +85°C |
| Vio=500V, Ta=25°C .....≥10 <sup>10</sup> Ω | Junction Temperature.....100°C               |
| Total Power Dissipation .....500mW         | Soldering Temperature,                       |
| Derate Linearly from 25°C .....2.5mW/°C    | 2mm from case, 10 sec .....260°C             |



## Electro-optical Characteristics (Ta=25°C)


| Parameter                | Symbol            | Conditions  | Min. | Typ. | Max. | Unit |
|--------------------------|-------------------|---|------|------|------|------|
| <b>Emitter (Input)</b>   |                   |   |      |      |      |      |
| Forward Voltage          | V <sub>F</sub>    | I <sub>F</sub> =10mA                                |      | 1.2  | 1.5  | V    |
| Operation Input Current  | I <sub>IFON</sub> | V <sub>L</sub> =±20V, I <sub>L</sub> =100mA, t=10mS |      | 1.5  | 5    | mA   |
| Recovery Input Current   | I <sub>IOFF</sub> | V <sub>L</sub> =±20V, I <sub>L</sub> ≤5μA           | 0.2  |      |      | mA   |
| <b>Detector (Output)</b> |                   |   |      |      |      |      |
| Output Breakdown Voltage | V <sub>B</sub>    | I <sub>B</sub> =50μA                                | 200  |      |      | V    |
| Output Off-State Leakage | I <sub>IOFF</sub> | V <sub>T</sub> =100V, I <sub>F</sub> =0mA           | 0.2  | 1    | 10   | μA   |
| I/O Capacitance          | C <sub>ISO</sub>  | I <sub>r</sub> =0, f=1MHz                           | 6    |      |      | pF   |
| ON Resistance            | R <sub>ON</sub>   | I <sub>L</sub> =100mA, I <sub>F</sub> =10mA         | 6    | 15   | 15   | Ω    |
| Turn-On Time             | T <sub>ON</sub>   | I <sub>F</sub> =10mA, V <sub>L</sub> =±20V          | 0.4  | 1.0  | 1.0  | ms   |
| Turn-Off Time            | T <sub>OFF</sub>  | t=10ms, I <sub>L</sub> =±100mA                      | 0.3  | 1.0  | 1.0  | ms   |

## Schematic and Wiring Diagrams


| Type               | Schematic | Output configuration | Load  | Connection | Wiring Diagrams   |
|--------------------|-----------|----------------------|-------|------------|---|
| KAQW217 & KAQW217A |           | 2a                   | AC/DC | -          | <p>(1) Two independent 1 Form A use</p> <p>(2) 2 Form A use</p> |

**Data Curve**


**Fig.1** Load current vs. ambient temperature  
Allowable ambient temperature:  
-40°C to +85°C




**Fig.2** On resistance vs. ambient temperature  
Across terminals 5,7 and 6,8 pin  
LED current: 5mA  
Continuous load current: 180mA(DC)




**Fig.3** Turn on time vs. ambient temperature  
Load voltage: 200V(DC)  
LED current: 5mA  
Continuous load current: 180mA(DC)




**Fig.4** Turn off time vs. ambient temperature  
LED current: 5mA; Load voltage:  
200V(DC)  
Continuous load current: 180mA(DC)




**Fig.5** LED operate vs. ambient temperature  
Load voltage: 200V(DC)  
Continuous load current: 180mA(DC)




**Fig.6** LED turn off current vs. ambient temperature  
Load voltage: 200V(DC)  
Continuous load current: 180mA(DC)




**Fig.7** LED dropout voltage vs. ambient temperature  
LED current: 5 to 50mA




**Fig.8** Voltage vs. current characteristics of output at MOS FET portion  
Measured portion: across terminals 5,7 and 6,8 pin  
Ambient temperature: 25°C




**Fig.9** Off state leakage current  
Across terminals 5,7 and 6,8 pin  
Ambient temperature: 25°C



**Fig.10** LED forward current vs. turn on time  
Across terminals 5,7 and 6,8 pin;  
Load voltage: 200V (DC);  
Continuous load current: 180mA (DC);  
Ambient temperature: 25°C



**Fig.11** LED forward current vs. turn off time  
Across terminals 5,7 and 6,8 pin;  
Load voltage: 200V (DC);  
Continuous load current: 180mA (DC);  
Ambient temperature: 25°C



**Fig.12** Applied voltage vs. output capacitance  
Across terminals 5,7 and 6,8 pin  
Frequency: 1MHz  
Ambient temperature: 25°C

