

HIGH POWER BI-DIRECTIONAL COUPLERS

SYNSTRIP® SURFACE MOUNT



FREQUENCY RANGE LF-HF (MHz)	COUPLING (dB) MEAN	INSERTION LOSS (dB) MAX	FREQUENCY SENSITIVITY (dB) MAX	DIRECTIVITY (dB) TYP/MIN	VSWR TYP/MAX	PACKAGE	PIN-OUT (See Below)	MODEL
800 - 1000	21.5 ±1.0	0.25	0.6	22/15	1.20:1/1.25:1	217	6	SDC-8010
800 - 1200	10.0 ±1.0	0.25	0.6	22/18	1.20:1/1.25:1	226-1	6	SCS-8012B
800 - 1200	20.0 ±1.0	0.25	0.6	22/18	1.20:1/1.25:1	226-1	6	SCS-8012D
1500 - 2200	10.0 ±1.0	0.25	0.3	23/18	1.20:1/1.25:1	226-1	6	SCS-1522B
1500 - 2200	20.0 ±1.0	0.25	0.3	23/20	1.18:1/1.20:1	226-1	6	SCS-1522D
2100 - 2400	10.5 ±0.5	0.25	0.6	22/15	1.40:1/1.50:1	216	6	SDC-2124
2100 - 2500	10.0 ±1.0	0.25	0.3	23/18	1.18:1/1.20:1	226-1	6	SCS-2125B
2100 - 2500	20.0 ±1.0	0.25	0.3	22/20	1.18:1/1.20:1	226-1	6	SCS-2125D

Note(Synstrip Surface Mount Only) :
Power rating = 100 watts ave. cw (Max.)

PIN-OUT TABLE						
	IN	OUT	COUPLED	GND	NO CONN.	*ISOLATED
#6	1	2	4	All Other	-	3


* Terminate isolated port with 50 ohms.

COAXIAL CONNECTOR




COUPLING (dB)	FREQUENCY RANGE LF-HF	COUPLING FLATNESS	MAINLINE LOSS (dB)	DIRECTIVITY (dB)	INPUT POWER	VSWR TYP	IMPEDANCE	PACKAGE	MODEL
NOM.	(MHz)	(dB)	MAX.	MIN.	MAX.		(OHMS)		
30.0 ± 1.0	800 - 2000	± 0.4	0.4	20	100	1.25:1	50	210	KEK-706H
30.0 ± 0.75	850 - 960	± 0.25	0.2	30	500	1.15:1	50	207	KEK-704H
30.0 ± 0.75	1800 - 2000	± 0.25	0.2	30	500	1.15:1	50	208	KEK-705H
30.0 ± 0.75	1500 - 2200	± 1.0	0.5	30	500	1.15:1	50	208	KEK-707H


For pin location and package outline drawings, see back pages.




KEK-704H (COUPLING)



KEK-705H (COUPLING)



KEK-706H (COUPLING)



KEK-707H (COUPLING)