查询TC246CYM-B0供应商

捷多邦,专业PCB打样工厂,24小时加急出货

680 x 500 PIXEL IMPACTRON™ COMPLEMENTARY COLOR CCD IMAGE SENSOR SOCS089 – MAY 2005

- Very Low Noise, Very High Sensitivity, Electronically Variable Charge Domain Gain
- 1/2-in Format, Solid State Charge-Coupled Device (CCD) Frame Interline Transfer Color Image Sensor for Low Light Level Applications with 60 Fields/s readout speed
- Cy, Ye, Mg, and G Complementary Mosaic Filters on Chip
- 340,000 Pixels per Field
- Frame Memory
- 658 (H) x 496 (V) Active Pixels in Image Sensing Area
- Pseudo-Interlace Scan
- 0-8V Serial Operation Except
 CMG Gate
- Continuous Electronic Exposure Control from 1/60 s to 1/2,000 s
- Advanced Lateral Overflow
 Drain
- 10.0 um Square Pixels
- Low Dark Current



- High Photo response Uniformity Over a Wide Spectral Range
- Solid State Reliability With No Image Burn-in, Residual Imaging, Image Distortion, or Microphonics
- Package with built-in Peltier Cooler and Temperature Sensor

Description

The TC246CYM is a frame interline transfer CCD image sensor designed for use in single-chip color NTSC TV, computer, and special-purpose applications requiring low noise, high sensitivity, high speed and low smear.

The TC246CYM is a new device of the IMPACTRONTM family of very-low noise, high sensitivity, high speed and low smear sensors that multiply charge directly in the charge domain before conversion to voltage. The charge carrier multiplication (CCM) is achieved by using a low-noise single-carrier, impact ionization process that occurs during repeated carrier transfers through high field regions. Applying multiplication pulses to specially designed gates activates the CCM. Multiplication gain is variable by adjusting the amplitude of the multiplication pulses. The device function resembles the function of an image intensifier implemented in solid state.



The image-sensing area of the TC246CYM is configured into 500 lines with 680 pixels in each line. 20 pixels are reserved in each line for dark reference. The blooming protection is based on an advanced lateral overflow drain concept that does not reduce NIR response. The frame interline transfer from the image sensing area to the memory area is implemented to minimize image smear. After charge is integrated and stored in the memory it is available for readout in the next cycle. This is accomplished by using a unique serial register design that includes special charge multiplication pixels.

The TC246CYM sensor is built using TI-proprietary advanced Split-Gate Virtual-Phase CCD (SGVPCCD) technology, which provides devices with wide spectral response, high quantum efficiency (QE), low dark current, and high response uniformity.

This MOS device contains limited built-in protection. During storage or handling, the device leads should be shorted together or the device should be placed in conductive foam. In a circuit, unused inputs should always be connected to Vss. Under no circumstances should pin voltages exceed absolute maximum ratings. Avoid shorting OUT to Vss during operation to prevent damage to the amplifier. The device can also be damaged if the output and ADB terminals are reverse-biased and excessive current is allowed to flow. Specific guidelines for handling devices of this type are contained in the publication "Guidelines for Handling Electrostatic-Discharge-Sensitive (ESD) Devices and Assemblies" available from Texas Instruments.



For stable operation, a decoupling capacitor (1uF, >5V) needs to be connected externally from the package FP pin to SUB.





Terminal functions

Terminal name, No.		I/O	Description	
SUB	1,7,12,13,24		Chip substrate	
SRG1	2	Ι	Serial register gate-1	
SRG2	3	Ι	Serial register gate-2	
CMG	4	Ι	Charge multiplication gate	
RST	5	Ι	Reset gate	
THER	6	Ι	Thermistor (NTC: Negative Temperature Coefficient)	
NC	8	-	No connection	
VDD	9	Ι	Supply voltage for amplifiers	
OUT	10	Ο	Output signal, multiplier channel	
FP	11		Field plate (connect external capacitor)	
VCLD	14	Ι	Supply voltage for Clearing drain & ESD protect circuits	
SAG2	15	Ι	Storage area gate-2	
SAG1	16	Ι	Storage area gate-1	
P(-)	17,18	Ι	Peltier cooler power supply - negative	
P(+)	19,20	Ι	Peltier cooler power supply - positive	
IAG2	21	Ι	Image area gate-2	
IAG1	22	Ι	Image area gate-1	
ODB	23	Ι	Supply voltage for anti-blooming drain	

Detailed description

The TC246CYM consists of five basic functional blocks: The image-sensing area, the image-storage area, the serial register, the charge multiplier, and the charge detection node with buffer amplifier. The location of each of these blocks is identified in the functional block diagram.

Image-sensing and storage areas

As light enters the silicon in the image-sensing area, electrons are generated and collected in potential wells of the pixels. Color is accomplished by on-chip color mosaic filter. (see the sensor topology diagram for a mapping of the color filter) Applying a suitable DC bias to the antiblooming drain provides blooming protection. The electrons that exceed a specific level, determined by the ODB bias, are drained away from the pixels. After the integration cycle is completed by applying a PD-cell readout pulse to IAG2, charge is transferred from the PD-cell into the V-cell and then quickly transferred into the storage cell where it waits for readout. 2 lines can be summed together to implement the pseudointerlace scan.

TEXAS INSTRUMENTS POST OFFICE BOY 655303 * DALLAS TEYAS 75265

20 columns at the left edge and 2 columns at the right edge of the image-sensing area are shielded from the incident light. These pixels provide the dark reference used in subsequent video-processing circuits to restore the video-black level. Additionally, 4 dark lines, located between the image sensing area and the image-storage area, were added to the array for isolation.

Advanced lateral overflow drain

Each pixel is constructed with the advanced lateral overflow drain structure. By varying the DC bias of the anti-blooming drain it is possible to control the blooming protection level and trade it for well capacity.

Electronic exposure control

Precise exposure control timing on a frame-by-frame basis is possible. The integration time can be arbitrarily shortened from its nominal length by clearing residual charge from the PD-cell. To do this, apply a PD-cell clear pulse to IAG2, which marks the beginning of integration.

Serial register and charge multiplier

The serial register of TC246CYM image sensor consists of only poly-silicon gates. It operates at high speed, being clocked from 0V to 8V. This allows the sensor to work at 60 Fields/s. The serial register is used for transporting charge stored in the pixels of the memory lines to the output amplifier. The TC246CYM device has a serial register with twice the standard length. The first half has a conventional design that interfaces with the memory as it would in any other CCD sensor. The second half, however, is unique and includes 400 charge multiplication stages with a number of dummy pixels that are needed to transport charge between the active register blocks and the output amplifier. Charge is multiplied as it progresses from stage to stage in the multiplier toward the charge detection node. The charge multiplication level depends on the amplitude of the multiplication pulses (approximately 15V~22V) applied to the multiplication gate. Due to the double length of the register, first 2 lines in each field or frame scan do not contain valid data and should be discarded.

Charge detection node and buffer amplifier

The last element of the charge detection and readout chain is the charge detection node with the buffer amplifier. The charge detection node is using a standard Floating Diffusion (FD) concept followed by an on-chip, dual-stage, source-follower buffer. Applying a pulse to the RST pin resets the detection node. To achieve the ultimate sensor performance it is necessary to eliminate kTC noise. This is typically accomplished by using CDS (correlated double sampling) processing techniques. IMPACTRONTM devices have the potential for detecting single electrons (photons) when cooled sufficiently.

TEXAS INSTRUMENTS POST OFFICE BOX 655303 * DALLAS TEXAS 75265

Absolute maximum ratings over operating free-air temperature range (unless otherwise noted)*

Supply voltage range, Vss: VDD, VCLD (see Note1)	0V to 15V
Supply voltage range, Vss: ODB	0V to 22V
Input voltage range, Vi: IAG1, SAG1, SAG2	- 10V to 10V
Input voltage range, Vi: IAG2	- 10V to 13V
Input voltage range, Vi: SRG1, SRG2, RST	0V to 10V
Input voltage range, Vi: CMG	-5V to 22V
Supply voltage range, Vcool: P+ (see Note2)	0V to 5.5V
Supply current range, Icool: P+ (see Note2)	0A to 1.4A
Supply current range, Ith: THER	0A to 0.31mA
Operating free-air temperature range, Ta	-20°C to 55°C
Storage temperature range, Tstg	-30°C to 85°C
Dew point inside the package (see Note2)	Less than -20°C

* Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect the device reliability.

Notes:

- 1. All voltage values are with respect to substrate terminal.
- 2. The Peltier cooler generates heat during cooling process. Heat must be removed through an external heat sink. In order to avoid condensation upon the surface do not cool the CCD to less than -20 degrees C.

Description			MIN	NOM	MAX	UNIT
Substrate bias, Vss				0.0		
	VDD		13.5	14.0	14.5	V
Supply voltage, Vdd	VCLD		13.5	14.0	14.5	
	ODB*		4.5		6.5	
	IAG1	High	3.0	3.3	3.6	-
		Low	-5.8	-5.5	-5.2	
		High	9.5	10.0	10.5	
	IAG2	Mid	3.0	3.3	3.6	V
		Low	-5.8	-5.5	-5.2	
	SAG1	High	3.0	3.3	3.6	
		Low	-5.8	-5.5	-5.2	
	SAC2	High	3.0	3.3	3.6	
Input voltage, Vi	SAUZ	Low	-5.8	-5.5	-5.2	
	SRG1	High	7.5	8.0	8.5	
		Low		0.0		
	SRG2	High	7.5	8.0	8.5	
		Low		0.0		
	CMG**	High	7.0		22.0	
		Low	-3.0	-2.5	-2.0	
	RST	High	5.5	6.0	6.5	
		Low		0.0		
	SAG1, SAG2			1.5		MHz
Clask Fragueney, fak	IAG1, IAG2			1.5		
Clock Frequency, Ick	SRG1, SRG2, RST			12.5	25.0	
	CMG			12.5	25.0	
Load capacitance	OUT				6.0	PF
Dew point inside the package***					-20	°C
Operating free-air temperature			-20	25	55	°C

Recommended operating conditions

* Adjustment within the specified MIN – MAX range is required to optimize performance.

** Charge multiplication gain depends on high level of the CMG and temperature.

*** -20 degrees should be the minimum temperature of the cooled CCD.

Electrical characteristics over recommended operating ranges of supply voltage at operating free-air temperature (unless otherwise noted)

PARAMETER			ТҮР	MAX	UNIT	
Charge multiplication gain *	1	200	2000	-		
Excess noise factor for typical CC	CM gain (Note 3)	1	1.4		-	
Dynamic range without CCM gai	n		69		dB	
Dynamic range with typical CCM gain (Note 4)			75		dB	
Charge conversion gain without C	CCM gain (Note 5)		14		uV/e	
τ Signal-response delay time (Note 6)			16		ns	
Output resistance			320		Ω	
Amp. Noise-equivalent signal wit	thout CCM gain **		20		e	
Amp. Noise-equivalent signal wit	th typ. CCM gain **		1.0		e	
Response linearity with no CCM gain			1		-	
Response linearity with typ. CCM	1 gain		1		-	
Charge-transfer efficiency	Parallel transfer	0.9999	4	1.0	-	
(Note 7)	Serial transfer	0.9999	4	1.0	-	
Supply current			2.0		mA	
	IAG1		3			
	IAG2		7			
	IAG1-IAG2		3		nЕ	
	SAG1		4			
	SAG2		5			
Ci Input capacitance	SAG1-SAG2		3			
	SRG1	85				
	SRG2		55		pF	
	CMG		25			
	ODB		2,000			
	RST		7			

All typical values are at Ta = 25 °C unless otherwise noted.

- * Maximum CCM gain is not guaranteed.
- ** The values in the table are quoted using CDS = Correlated Double Sampling. CDS is a signal processing technique that improves performance by minimizing undesirable effects of reset noise.

Notes :

- 3. Excess Noise Factor "F" is defined as the ratio of noise sigma after multiplication divided by M times the noise sigma before multiplication where M is the charge multiplication gain.
- 4. Dynamic Range is -20 times the logarithm of the noise sigma divided by the saturation-output signal amplitude
- 5. Charge conversion factor is defined as the ratio of output signal to input number of electrons.
- 6. Signal-response delay time is the time between the falling edge of the SRG1 pulse and the outputsignal valid state.
- 7. Charge transfer efficiency is one minus the charge loss per transfer in the CCD register. The test is performed in the dark using either electrical or optical input.

PARAMETER		MIN TYP MAX	UNIT	
	No IR-cut filter : Cyan	4840		
	No IR-cut filter : Yellow	7470		
	No IR-cut filter : Magenta	6390		
Sensitivity with typical	No IR-cut filter : Green	4200		
CCM gain (Note 8)	With IR-cut filter : Cyan	560	V/Lx sec	
	With IR-cut filter : Yellow	950		
	With IR-cut filter : Magenta	550		
	With IR-cut filter : Green	480		
	No IR-cut filter : Cyan	24		
	No IR-cut filter : Yellow	37		
	No IR-cut filter : Magenta	32		
Sensitivity without	No IR-cut filter : Green	21		
CCM gain (Note 8)	With IR-cut filter : Cyan	2.8	V/Lx sec	
	With IR-cut filter : Yellow	4.8		
	With IR-cut filter : Magenta	2.7		
	With IR-cut filter : Green	2.4		
Saturation signal output	t no CCM gain (Note 9)	800		
Saturation signal output	t Anti blooming Enable	360		
no CCM gain(Note 9)			mV	
Saturation signal output	t with typ CCM gain (Note 9)	1500	_	
Zero input offset output	t (Note 10)	100		
Blooming overload rati	Blooming overload ratio (Note 11)		-	
Image area well capacity		28k	e	
Smear (Note 12)		-84	dB	
Dark current (Note 13)		0.01	nA/cm ²	
Dark signal (Note 14)		0.02	mV	
Spurious	Dark	5.0		
non-uniformity	Illuminated	-30 30	<u>%</u>	
Column uniformity (No	Column uniformity (Note 15)		%	
Electronic-shutter capa	1/2000 1/60	S		

Optical characteristics

Ta = 25°C, Integration time = 16.67msec (unless otherwise noted)

Notes:

- 8. Light source temperature is 2856 °K. The IR filter used is CM500 1mm thick.
- 9. Saturation is the condition in which further increase in exposure does not lead to further increases in output signal.
- 10. Zero input offset is the residual output signal measured from the reset level with no input charge present. This level is not caused by the dark current and remains approximately constant independent of temperature. It may vary with the amplitude of SRG1.
- 11. Blooming is the condition in which charge induced by light in one element spills over to the neighboring elements.

- 12. Smear is the measure of error signal introduced into the pixels by transferring them through the illuminated region into the memory. The illuminated region is 1/10 of the image area height. The value in the table is obtained for the integration time of 33.3ms and 1.5 MHz vertical clock transfer frequency.
- 13. Dark current depends on temperature and approximately doubles every 8 C°. Dark current is also multiplied by CCM operation. The value given in the table is with the multiplier turned off and it is a calculated value.
- 14. Dark signal is actual device output measured in dark.
- 15. Column uniformity is obtain by summing all the lines in the array, finding the maximum of the difference of two neighboring columns anywhere in the array, and dividing the result by the number of lines.



FIGURE 1. Serial Register Pixel Cross Section



FIGURE 2. Interlace Timing of Line Summing Mode



FIGURE 3. Serial register Clock Timing for CDS Implementation



FIGURE 4. Detailed output signal



FIGURE 5. Serial Transfer Timing (12.5HMz applications)



FIGURE 6. Vertical Transfer Timing (1.5 MHz application)



FIGURE 7. Typical Line Summing & Transfer Timing



FIGURE 8. Typical PD-Readout and Exposure Control Timing

TC246CYM-B0 680 x 500 PIXEL IMPACTRON™ COMPLEMENTARY COLOR CCD IMAGE SENSOR SOCS089 – MAY 2005



FIGURE 9. Typical Spectral Responsivity



FIGURE 10. Typical Spectral Quantum Efficiency without on-chip color filters

TEXAS INSTRUMENTS POST OFFICE BOY 655303 * DALLAS TEXAS 75265

TC246CYM-B0 680 x 500 PIXEL IMPACTRON™ COMPLEMENTARY COLOR CCD IMAGE SENSOR SOCS089 – MAY 2005



FIGURE 11. Typical Variation of Multiplication Gain with CMG High Voltage



FIGURE 12. Typical Cooling Capability

TC246CYM-B0 680 x 500 PIXEL IMPACTRON™ COMPLEMENTARY COLOR CCD IMAGE SENSOR SOCS089 – MAY 2005



FIGURE 13. Typical Thermistor Characteristics



FIGURE 14. Typical Thermistor Characteristics (Detail)

TEXAS INSTRUMENTS

TC246CYM-B0 680 x 500 PIXEL IMPACTRON™ COMPLEMENTARY COLOR CCD IMAGE SENSOR SOCS089 – MAY 2005



FIGURE 15. Typical IAG Driver Circuits

TC246CYM-B0 680 x 500 PIXEL IMPACTRON™ COMPLEMENTARY COLOR CCD IMAGE SENSOR SOCS089 – MAY 2005



FIGURE 16. Typical SAG Driver Circuits



FIGURE 17. Typical SRG and RST Driver Circuits

TEXAS INSTRUMENTS POST OFFICE BOY 655303 * DALLAS TEXAS 75265



FIGURE 18. Typical CMG Driver Circuits

Mechanical data

The package for the TC246CYM consists of a ceramic base, a glass window, and a 24pin lead frame. The glass window is hermetically sealed to the package. The package leads are configured in a dual-in-line arrangement and fit into mounting holes with 1,78 mm center-to-center spacing.

Attention

Be careful when attaching an external heat sink to the package. Fastening it too strongly may crack or puncture the package, making it susceptible to moisture or humidity.



IEAAG INSTRUMENTS

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products	
Amplifiers	am
Data Converters	dat
DSP	dsp
Clocks and Timers	ww
Interface	inte
Logic	log
Power Mgmt	pov
Microcontrollers	mic
RFID	ww
RF/IF and ZigBee® Solutions	ww

mplifier.ti.com ataconverter.ti.com sp.ti.com ww.ti.com/clocks terface.ti.com gic.ti.com ower.ti.com icrocontroller.ti.com ww.ti.rfid.com ww.ti.com/lprf

Applications Audio Automotive Broadband Digital Control Medical Military Optical Networking Security Telephony Video & Imaging

www.ti.com/audio www.ti.com/automotive www.ti.com/broadband www.ti.com/digitalcontrol www.ti.com/medical www.ti.com/military www.ti.com/opticalnetwork www.ti.com/security www.ti.com/security www.ti.com/video www.ti.com/video

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2008, Texas Instruments Incorporated

Wireless