

**NEC**

**NPN SILICON RF TWIN TRANSISTOR**  
 **$\mu$ PA831TC**

**NPN SILICON EPITAXIAL TRANSISTOR (WITH 2 DIFFERENT ELEMENTS)  
IN A FLAT-LEAD 6-PIN THIN-TYPE ULTRA SUPER MINIMOLD PACKAGE**

**DESCRIPTION**

The  $\mu$ PA831TC has built-in two different transistors (Q1 and Q2) for low noise amplification in the VHF band to UHF band.

**FEATURES**

- Low noise  
Q1 : NF = 1.2 dB TYP., Q2 : NF = 1.4 dB TYP.  
@f = 1 GHz, V<sub>CE</sub> = 3 V, I<sub>c</sub> = 7 mA
- High gain  
Q1 : |S<sub>21e</sub>|<sup>2</sup> = 9.0 dB TYP., Q2 : |S<sub>21e</sub>|<sup>2</sup> = 12.0 dB TYP.  
@f = 1 GHz, V<sub>CE</sub> = 3 V, I<sub>c</sub> = 7 mA
- Flat-lead 6-pin thin-type ultra super minimold package
- 2 different built-in transistors (2SC5006, 2SC5007)

**BUILT-IN TRANSISTORS**

	Q1	Q2
3-pin ultra super minimold part No.	2SC5006	2SC5007

**ORDERING INFORMATION**

Part Number	Package	Quantity	Supplying Form
$\mu$ PA831TC	Flat-lead 6-pin thin-type ultra super minimold	Loose products (50 pcs)	8 mm wide embossed tape. Pin 6 (Q1 Base), pin 5 (Q2 Emitter), pin 4 (Q2 Base) face to perforation side of the tape.
$\mu$ PA831TC-T1		Taping products (3 kp/reel)	

**Remark** To order evaluation samples, please contact your local NEC sales office. (Part number for sample order:  $\mu$ PA831TC.)

**Caution Electro-static sensitive devices**

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.  
Not all devices/types available in every country. Please check with local NEC representative for availability and additional information.



**ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = +25°C)**

Parameter	Symbol	Ratings		Unit
		Q1	Q2	
Collector to Base Voltage	V <sub>CBO</sub>	20	20	V
Collector to Emitter Voltage	V <sub>CEO</sub>	12	10	V
Emitter to Base Voltage	V <sub>EBO</sub>	3	1.5	V
Collector Current	I <sub>c</sub>	100	65	mA
Total Power Dissipation	P <sub>T</sub> <sup>Note</sup>	200 in 1 element	200 in 1 element	mW
		230 in 2 elements		
Junction Temperature	T <sub>j</sub>	150	150	°C
Storage Temperature	T <sub>stg</sub>	-65 to +150		°C

**Note** Mounted on 1.08 cm<sup>2</sup> × 1.0 mm glass epoxy substrate.

**ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = +25°C)**

**(1) Q1**

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector Cutoff Current	I <sub>CBO</sub>	V <sub>CB</sub> = 10 V, I <sub>E</sub> = 0	–	–	1.0	μA
Emitter Cutoff Current	I <sub>EBO</sub>	V <sub>EB</sub> = 1 V, I <sub>c</sub> = 0	–	–	1.0	μA
DC Current Gain	h <sub>FE</sub>	V <sub>CE</sub> = 3 V, I <sub>c</sub> = 7 mA <sup>Note 1</sup>	70	–	140	
Gain Bandwidth Product	f <sub>T</sub>	V <sub>CE</sub> = 3 V, I <sub>c</sub> = 7 mA, f = 1 GHz	3.0	4.5	–	GHz
Feedback Capacitance	C <sub>re</sub>	V <sub>CB</sub> = 3 V, I <sub>E</sub> = 0, f = 1 MHz <sup>Note 2</sup>	–	0.7	1.5	pF
Insertion Power Gain	S <sub>21e</sub>   <sup>2</sup>	V <sub>CE</sub> = 3 V, I <sub>c</sub> = 7 mA, f = 1 GHz	7.0	9.0	–	dB
Noise Figure	NF	V <sub>CE</sub> = 3 V, I <sub>c</sub> = 7 mA, f = 1 GHz	–	1.2	2.5	dB

**Notes** 1. Pulse Measurement: PW ≤ 350 μs, Duty Cycle ≤ 2%

2. Collector to base capacitance when measured with capacitance meter (automatic balanced bridge method), with emitter connected to guard pin of capacitance meter.

(2) Q2

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = 10\text{ V}, I_E = 0$	–	–	0.8	μA
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = 1\text{ V}, I_C = 0$	–	–	0.8	μA
DC Current Gain	$h_{FE}$	$V_{CE} = 3\text{ V}, I_C = 7\text{ mA}$ <sup>Note 1</sup>	70	–	150	
Gain Bandwidth Product	$f_T$	$V_{CE} = 3\text{ V}, I_C = 7\text{ mA}, f = 1\text{ GHz}$	4.5	7.0	–	GHz
Feedback Capacitance	$C_{re}$	$V_{CB} = 3\text{ V}, I_E = 0, f = 1\text{ MHz}$ <sup>Note 2</sup>	–	–	0.9	pF
Insertion Power Gain	$ S_{21e} ^2$	$V_{CE} = 3\text{ V}, I_C = 7\text{ mA}, f = 1\text{ GHz}$	10.0	12.0	–	dB
Noise Figure	NF	$V_{CE} = 3\text{ V}, I_C = 7\text{ mA}, f = 1\text{ GHz}$	–	1.4	2.7	dB

- Notes**
1. Pulse Measurement:  $PW \leq 350\ \mu s$ , Duty Cycle  $\leq 2\%$
  2. Collector to base capacitance when measured with capacitance meter (automatic balanced bridge method), with emitter connected to guard pin of capacitance meter.


**$h_{FE}$  CLASSIFICATION**

Rank	FB
Marking	24
$h_{FE}$ Value of Q1	70 to 140
$h_{FE}$ Value of Q2	70 to 150

TYPICAL CHARACTERISTICS ( $T_A = +25^\circ\text{C}$ )


Q1

TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




Q2


TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




COLLECTOR CURRENT vs. BASE TO EMITTER VOLTAGE




COLLECTOR CURRENT vs. BASE TO EMITTER VOLTAGE



COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE




COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE




Q1

DC CURRENT GAIN vs. COLLECTOR CURRENT




Q2


DC CURRENT GAIN vs. COLLECTOR CURRENT




GAIN BANDWIDTH PRODUCT vs. COLLECTOR CURRENT




GAIN BANDWIDTH PRODUCT vs. COLLECTOR CURRENT




INSERTION POWER GAIN vs. COLLECTOR CURRENT








INSERTION POWER GAIN vs. COLLECTOR CURRENT



Q1



Q2



**S-PARAMETERS Q1**

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 1 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.938	-29.5	3.703	157.3	0.052	50.2	0.981	-13.9
0.2	0.913	-56.4	3.348	137.5	0.082	51.5	0.946	-26.3
0.3	0.881	-81.6	3.052	119.6	0.110	36.2	0.902	-37.6
0.4	0.843	-104.6	2.745	102.4	0.130	20.9	0.844	-48.3
0.5	0.816	-125.7	2.497	86.6	0.141	8.9	0.792	-57.1
0.6	0.782	-145.2	2.241	72.3	0.154	-2.8	0.756	-66.1
0.7	0.759	-162.8	2.023	58.5	0.156	-14.1	0.715	-73.8
0.8	0.748	-178.8	1.852	46.3	0.161	-23.1	0.698	-82.0
0.9	0.739	165.9	1.700	34.1	0.158	-32.0	0.672	-90.0
1.0	0.730	152.1	1.572	22.7	0.158	-40.8	0.655	-97.8
1.1	0.731	138.6	1.461	11.8	0.158	-49.5	0.637	-106.0
1.2	0.726	125.8	1.364	1.0	0.153	-57.1	0.624	-113.7
1.3	0.730	113.7	1.277	-9.2	0.151	-63.5	0.616	-122.2
1.4	0.730	101.7	1.203	-19.4	0.141	-70.4	0.608	-130.2
1.5	0.735	90.6	1.131	-29.3	0.139	-75.7	0.600	-138.6
1.6	0.736	79.6	1.069	-38.9	0.132	-81.0	0.594	-147.4
1.7	0.741	69.1	1.017	-48.2	0.128	-85.1	0.590	-156.3
1.8	0.743	58.7	0.967	-57.6	0.123	-89.6	0.582	-165.0
1.9	0.750	48.8	0.925	-66.6	0.118	-92.7	0.580	-174.2
2.0	0.751	39.0	0.878	-75.7	0.117	-96.3	0.580	-177.3
2.1	0.757	29.6	0.840	-84.2	0.111	-99.5	0.571	-168.0
2.2	0.761	20.1	0.800	-93.1	0.111	-100.5	0.573	-158.1
2.3	0.767	11.3	0.770	-101.1	0.111	-101.6	0.567	-148.8
2.4	0.770	1.9556	0.734	-109.5	0.112	-102.9	0.569	-138.7
2.5	0.771	-6.6	0.704	-117.2	0.119	-104.3	0.564	-128.6
2.6	0.777	-15.2	0.677	-125.3	0.126	-107.2	0.564	-118.7
2.7	0.784	-23.9	0.646	-132.6	0.132	-108.9	0.566	-108.4
2.8	0.787	-32.0	0.621	-140.4	0.140	-113.5	0.567	-98.2
2.9	0.791	-40.2	0.600	-147.9	0.147	-116.1	0.563	-87.8
3.0	0.797	-48.2	0.575	-154.7	0.159	-121.2	0.573	-77.3

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 3 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.929	-27.6	5.790	157.9	0.050	42.1	0.987	-16.6
0.2	0.881	-53.5	5.401	138.4	0.085	57.3	0.929	-30.8
0.3	0.834	-77.2	4.951	120.9	0.107	41.0	0.865	-45.1
0.4	0.774	-99.8	4.477	103.7	0.130	28.1	0.785	-57.2
0.5	0.730	-120.0	4.065	88.5	0.147	16.9	0.713	-68.1
0.6	0.683	-138.9	3.641	74.6	0.161	6.4	0.660	-77.6
0.7	0.654	-156.1	3.309	61.7	0.168	-3.7	0.602	-86.9
0.8	0.632	-172.9	3.007	49.6	0.174	-12.5	0.560	-95.1
0.9	0.611	172.1	2.747	38.2	0.180	-20.3	0.524	-103.3
1.0	0.600	157.6	2.543	27.1	0.178	-27.6	0.495	-111.3
1.1	0.594	144.2	2.360	16.3	0.186	-35.4	0.467	-119.6
1.2	0.587	130.9	2.202	6.0	0.188	-41.6	0.444	-127.3
1.3	0.587	118.7	2.062	-4.0	0.193	-48.8	0.427	-135.3
1.4	0.588	106.5	1.943	-13.7	0.193	-55.1	0.410	-143.2
1.5	0.590	95.2	1.834	-23.4	0.194	-61.7	0.396	-151.1
1.6	0.595	84.0	1.731	-33.0	0.199	-67.2	0.380	-160.0
1.7	0.596	73.3	1.648	-42.2	0.199	-73.4	0.371	-168.2
1.8	0.600	62.7	1.571	-51.7	0.199	-79.2	0.359	-176.2
1.9	0.606	52.8	1.504	-60.4	0.204	-85.7	0.348	-175.1
2.0	0.614	42.6	1.436	-69.5	0.207	-90.8	0.340	-166.2
2.1	0.617	33.1	1.367	-78.4	0.208	-97.3	0.329	-157.2
2.2	0.623	23.8	1.309	-87.4	0.209	-102.8	0.322	-147.9
2.3	0.630	14.3	1.262	-95.6	0.211	-108.6	0.314	-138.5
2.4	0.635	5.4	1.210	-104.1	0.214	-113.6	0.310	-128.9
2.5	0.641	-3.3	1.162	-112.4	0.217	-119.5	0.303	-119.4
2.6	0.648	-11.7	1.121	-120.5	0.222	-124.6	0.300	-109.6
2.7	0.653	-20.4	1.080	-128.4	0.223	-130.4	0.295	-99.2
2.8	0.660	-28.6	1.044	-136.7	0.229	-136.0	0.297	-90.3
2.9	0.668	-36.6	1.014	-144.1	0.232	-141.5	0.295	-80.0
3.0	0.673	-44.9	0.977	-152.2	0.235	-147.8	0.301	-69.7

V<sub>CE</sub> = 3 V, I<sub>C</sub> = 5 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.787	-50.1	14.281	144.6	0.052	33.3	0.928	-29.0
0.2	0.708	-91.6	11.299	119.6	0.058	48.6	0.722	-48.1
0.3	0.662	-121.9	9.080	100.3	0.075	23.0	0.603	-63.3
0.4	0.619	-146.9	7.356	84.3	0.082	19.3	0.503	-73.0
0.5	0.603	-166.4	6.183	70.9	0.084	10.7	0.433	-81.0
0.6	0.591	176.8	5.269	58.8	0.090	3.6	0.378	-88.5
0.7	0.587	162.0	4.599	48.1	0.091	-1.5	0.346	-96.1
0.8	0.588	148.6	4.073	37.8	0.096	-8.8	0.314	-103.0
0.9	0.586	136.5	3.652	27.6	0.100	-10.5	0.294	-110.4
1.0	0.590	124.6	3.319	18.2	0.101	-16.9	0.274	-116.9
1.1	0.594	114.0	3.043	8.7	0.107	-23.1	0.264	-125.0
1.2	0.596	103.2	2.798	-0.5	0.114	-26.6	0.250	-132.5
1.3	0.603	93.4	2.603	-9.4	0.115	-31.4	0.244	-140.7
1.4	0.607	82.9	2.423	-18.4	0.122	-36.1	0.234	-148.4
1.5	0.614	73.6	2.274	-27.0	0.127	-41.7	0.221	-157.7
1.6	0.623	64.6	2.137	-36.0	0.133	-46.7	0.216	-166.3
1.7	0.628	55.6	2.018	-44.6	0.138	-51.2	0.209	-175.6
1.8	0.632	46.4	1.899	-53.1	0.142	-57.0	0.204	175.9
1.9	0.640	37.7	1.819	-61.3	0.148	-62.2	0.200	166.0
2.0	0.646	28.8	1.724	-69.8	0.155	-67.4	0.197	155.6
2.1	0.656	20.5	1.642	-78.0	0.164	-73.8	0.193	145.4
2.2	0.660	11.9	1.568	-86.6	0.168	-79.3	0.192	134.8
2.3	0.668	4.0	1.506	-94.4	0.173	-84.3	0.189	123.6
2.4	0.674	-4.0	1.442	-102.7	0.181	-90.6	0.190	113.2
2.5	0.677	-12.4	1.383	-110.4	0.187	-96.3	0.191	101.6
2.6	0.685	-20.1	1.330	-118.4	0.195	-101.7	0.195	90.0
2.7	0.693	-27.8	1.286	-126.3	0.201	-108.7	0.197	79.2
2.8	0.697	-35.6	1.235	-133.9	0.204	-114.4	0.205	68.3
2.9	0.706	-43.4	1.194	-141.8	0.213	-120.5	0.208	57.3
3.0	0.713	-50.6	1.151	-149.5	0.221	-125.8	0.217	47.6

V<sub>CE</sub> = 3 V, I<sub>C</sub> = 7 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.738	-60.7	18.140	139.9	0.035	26.0	0.865	-34.7
0.2	0.630	-104.2	13.504	113.5	0.060	38.6	0.653	-55.3
0.3	0.596	-134.1	10.414	95.1	0.067	29.9	0.509	-69.4
0.4	0.574	-158.5	8.249	79.9	0.073	19.5	0.414	-79.9
0.5	0.564	-176.7	6.877	67.4	0.072	14.3	0.348	-87.9
0.6	0.554	168.2	5.807	56.0	0.078	10.2	0.303	-95.0
0.7	0.553	154.2	5.036	45.7	0.083	5.7	0.270	-102.0
0.8	0.559	142.0	4.441	35.9	0.089	1.8	0.244	-109.8
0.9	0.558	130.1	3.988	26.3	0.096	-5.0	0.228	-117.6
1.0	0.562	119.3	3.609	17.0	0.100	-10.4	0.212	-124.3
1.1	0.569	108.6	3.300	7.7	0.107	-14.5	0.200	-132.7
1.2	0.574	98.8	3.039	-1.1	0.113	-19.7	0.188	-140.5
1.3	0.580	89.5	2.819	-9.8	0.119	-25.8	0.177	-149.6
1.4	0.583	79.8	2.622	-18.5	0.127	-29.0	0.172	-157.7
1.5	0.594	70.9	2.463	-27.1	0.133	-35.1	0.164	-168.1
1.6	0.598	61.7	2.307	-35.7	0.138	-40.2	0.157	-177.4
1.7	0.605	53.1	2.180	-44.1	0.148	-46.3	0.154	172.2
1.8	0.611	44.2	2.053	-52.8	0.154	-52.4	0.148	162.6
1.9	0.619	35.8	1.965	-60.8	0.160	-59.2	0.145	151.6
2.0	0.625	27.0	1.862	-69.2	0.168	-64.7	0.143	140.3
2.1	0.634	18.7	1.778	-77.2	0.173	-71.1	0.142	128.1
2.2	0.642	10.7	1.695	-85.5	0.182	-76.6	0.141	116.6
2.3	0.652	2.7	1.626	-93.4	0.186	-82.8	0.144	104.7
2.4	0.652	-5.636	1.557	-101.5	0.196	-88.7	0.146	92.0
2.5	0.662	-13.2	1.496	-109.3	0.200	-95.0	0.149	80.2
2.6	0.669	-21.1	1.440	-117.0	0.209	-101.6	0.155	70.2
2.7	0.677	-28.8	1.387	-124.7	0.214	-107.6	0.164	58.7
2.8	0.682	-36.1	1.337	-132.2	0.221	-114.5	0.169	47.8
2.9	0.688	-44.2	1.294	-140.2	0.228	-121.1	0.177	36.9
3.0	0.696	-51.1	1.242	-147.7	0.234	-127.0	0.186	27.6



**S-PARAMETERS Q2**

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 1 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.960	-19.1	3.823	163.5	0.020	74.9	0.984	-9.7
0.2	0.943	-37.8	3.597	148.4	0.051	62.2	0.981	-20.2
0.3	0.922	-54.3	3.422	134.7	0.065	48.6	0.961	-30.3
0.4	0.885	-72.3	3.252	120.1	0.084	40.6	0.926	-39.8
0.5	0.862	-89.0	3.105	106.6	0.101	28.1	0.899	-48.5
0.6	0.821	-105.0	2.916	93.3	0.114	17.6	0.860	-56.8
0.7	0.790	-120.6	2.754	80.8	0.124	7.1	0.833	-65.2
0.8	0.759	-135.5	2.595	69.1	0.130	-5.0	0.803	-73.5
0.9	0.728	-150.2	2.445	57.4	0.139	-13.2	0.775	-81.0
1.0	0.706	-164.6	2.316	46.0	0.141	-20.7	0.748	-88.4
1.1	0.685	-178.3	2.194	35.2	0.144	-29.9	0.724	-95.7
1.2	0.671	168.5	2.087	24.7	0.148	-38.6	0.708	-102.9
1.3	0.659	155.7	1.979	14.5	0.147	-46.7	0.688	-110.4
1.4	0.645	143.1	1.891	4.6	0.145	-53.0	0.672	-117.7
1.5	0.641	131.1	1.808	-5.2	0.147	-59.4	0.655	-124.7
1.6	0.635	119.1	1.730	-15.4	0.144	-66.9	0.639	-132.1
1.7	0.629	107.2	1.652	-24.8	0.143	-72.8	0.627	-139.3
1.8	0.623	96.0	1.592	-34.3	0.142	-79.1	0.614	-146.6
1.9	0.626	85.0	1.532	-43.4	0.139	-84.4	0.603	-154.2
2.0	0.621	74.1	1.468	-52.7	0.138	-89.5	0.597	-161.5
2.1	0.620	63.5	1.413	-61.4	0.135	-94.7	0.585	-168.4
2.2	0.620	53.5	1.362	-70.6	0.133	-99.6	0.576	-176.4
2.3	0.623	43.7	1.318	-79.0	0.131	-104.2	0.568	-175.4
2.4	0.621	33.6	1.270	-87.8	0.131	-107.7	0.560	-167.6
2.5	0.626	24.3	1.230	-96.2	0.133	-112.2	0.551	-159.1
2.6	0.626	15.2	1.195	-104.9	0.137	-114.3	0.544	-150.8
2.7	0.635	6.4	1.161	-113.3	0.138	-116.8	0.533	-142.3
2.8	0.635	-2.2	1.122	-121.7	0.146	-120.9	0.526	-133.9
2.9	0.639	-10.6	1.095	-130.0	0.154	-124.0	0.511	-125.7
3.0	0.647	-18.5	1.050	-138.3	0.164	-131.3	0.504	-117.6

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 3 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.897	-26.0	9.698	157.7	0.025	23.3	0.992	-15.1
0.2	0.844	-49.9	8.841	139.5	0.047	65.0	0.918	-27.5
0.3	0.784	-72.1	8.028	122.8	0.055	47.4	0.858	-39.8
0.4	0.723	-92.8	7.209	106.8	0.072	32.5	0.791	-50.3
0.5	0.670	-111.3	6.534	92.7	0.079	25.9	0.724	-59.4
0.6	0.616	-128.8	5.822	79.6	0.088	14.8	0.669	-67.3
0.7	0.580	-144.9	5.287	67.8	0.093	5.7	0.628	-74.8
0.8	0.547	-160.4	4.812	56.6	0.095	-2.3	0.585	-81.7
0.9	0.528	-175.1	4.391	45.7	0.102	-5.5	0.551	-88.2
1.0	0.510	171.3	4.051	35.6	0.104	-14.3	0.528	-94.4
1.1	0.496	158.6	3.749	25.6	0.107	-20.1	0.501	-101.4
1.2	0.483	145.7	3.501	16.2	0.112	-25.1	0.482	-107.5
1.3	0.480	133.8	3.273	6.9	0.114	-31.7	0.463	-114.4
1.4	0.477	122.6	3.086	-2.2	0.116	-36.0	0.452	-120.8
1.5	0.475	111.1	2.907	-11.1	0.122	-41.3	0.436	-127.5
1.6	0.474	100.0	2.752	-20.2	0.124	-47.3	0.421	-134.4
1.7	0.477	89.8	2.617	-28.8	0.130	-53.2	0.410	-140.9
1.8	0.477	79.4	2.477	-37.4	0.132	-57.9	0.402	-147.9
1.9	0.481	69.6	2.381	-45.7	0.136	-63.7	0.384	-155.0
2.0	0.484	59.9	2.271	-54.4	0.141	-68.1	0.379	-161.4
2.1	0.489	50.1	2.176	-62.8	0.142	-75.1	0.365	-168.6
2.2	0.493	41.2	2.084	-71.4	0.150	-78.8	0.354	-175.9
2.3	0.499	32.1	2.011	-79.4	0.155	-84.0	0.343	-176.0
2.4	0.506	23.4	1.933	-87.7	0.162	-90.6	0.337	-168.9
2.5	0.508	14.9	1.862	-95.8	0.167	-95.4	0.323	-161.0
2.6	0.517	6.4	1.801	-104.1	0.175	-101.4	0.313	-153.4
2.7	0.526	-1.2	1.742	-111.9	0.179	-106.8	0.306	-145.3
2.8	0.535	-9.4	1.688	-119.8	0.186	-113.6	0.299	-137.0
2.9	0.543	-17.1	1.629	-127.5	0.192	-119.9	0.290	-129.0
3.0	0.556	-25.0	1.572	-135.3	0.197	-126.4	0.286	-120.7

V<sub>CE</sub> = 3 V, I<sub>C</sub> = 5 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.853	-30.1	13.631	154.4	0.030	42.5	0.975	-17.5
0.2	0.761	-58.0	12.026	133.7	0.042	60.6	0.870	-32.4
0.3	0.693	-82.4	10.531	115.9	0.052	41.9	0.781	-45.3
0.4	0.619	-105.0	9.123	99.6	0.062	32.6	0.700	-54.9
0.5	0.568	-124.2	7.999	85.6	0.072	23.5	0.623	-63.4
0.6	0.522	-141.3	7.036	73.1	0.075	16.0	0.571	-70.6
0.7	0.489	-157.8	6.236	61.8	0.079	7.6	0.526	-76.8
0.8	0.467	-172.5	5.612	51.3	0.088	4.3	0.490	-83.3
0.9	0.451	173.6	5.105	41.2	0.091	-2.7	0.464	-89.8
1.0	0.438	160.1	4.661	31.5	0.092	-7.0	0.439	-95.3
1.1	0.428	147.5	4.292	22.1	0.099	-14.7	0.419	-101.9
1.2	0.423	135.7	3.989	12.9	0.106	-18.6	0.401	-107.8
1.3	0.425	124.5	3.720	4.1	0.110	-25.5	0.390	-114.5
1.4	0.422	113.3	3.477	-4.6	0.116	-29.7	0.372	-120.6
1.5	0.425	102.7	3.265	-13.4	0.119	-34.5	0.359	-127.4
1.6	0.430	92.3	3.101	-22.2	0.125	-41.4	0.346	-133.8
1.7	0.434	82.7	2.925	-30.4	0.132	-45.4	0.337	-140.6
1.8	0.436	72.8	2.782	-39.1	0.136	-51.6	0.326	-147.0
1.9	0.443	63.4	2.656	-46.9	0.141	-56.3	0.314	-153.9
2.0	0.444	54.1	2.533	-55.3	0.147	-62.7	0.307	-160.7
2.1	0.453	45.0	2.422	-63.6	0.150	-69.0	0.292	-166.9
2.2	0.457	35.9	2.319	-72.0	0.157	-74.2	0.284	-174.8
2.3	0.464	27.9	2.233	-79.6	0.163	-80.1	0.269	-177.4
2.4	0.470	19.6	2.148	-87.8	0.171	-86.5	0.263	-170.3
2.5	0.478	11.2	2.066	-95.7	0.179	-92.6	0.251	-162.8
2.6	0.487	3.1	1.989	-103.8	0.187	-98.4	0.240	-154.5
2.7	0.492	-4.3	1.925	-111.5	0.195	-104.8	0.233	-147.6
2.8	0.502	-11.8	1.858	-119.2	0.199	-111.3	0.224	-138.8
2.9	0.513	-19.5	1.800	-127.1	0.207	-117.7	0.216	-131.2
3.0	0.528	-26.9	1.742	-134.5	0.212	-125.0	0.212	-122.8

V<sub>CE</sub> = 3 V, I<sub>C</sub> = 7 mA



FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.877	-27.1	18.049	149.6	0.034	55.5	0.978	-16.4
0.2	0.801	-51.8	15.160	127.2	0.041	50.5	0.897	-31.8
0.3	0.736	-74.3	12.633	108.8	0.056	40.2	0.823	-44.8
0.4	0.662	-94.3	10.579	92.9	0.070	36.1	0.733	-55.1
0.5	0.600	-112.8	9.065	79.3	0.076	28.3	0.657	-64.4
0.6	0.551	-130.4	7.838	67.4	0.084	18.4	0.601	-72.8
0.7	0.511	-146.4	6.848	56.8	0.089	10.3	0.553	-80.1
0.8	0.483	-161.7	6.110	46.6	0.096	3.1	0.513	-86.7
0.9	0.457	-175.8	5.518	37.0	0.102	-3.0	0.476	-93.6
1.0	0.441	170.6	5.024	27.8	0.108	-8.6	0.445	-100.0
1.1	0.430	157.9	4.604	18.7	0.113	-14.8	0.423	-106.3
1.2	0.418	144.9	4.256	9.9	0.117	-21.3	0.402	-113.1
1.3	0.416	133.5	3.965	1.4	0.120	-26.5	0.381	-119.0
1.4	0.411	121.9	3.709	-7.0	0.128	-30.6	0.363	-125.5
1.5	0.412	110.8	3.481	-15.6	0.131	-37.1	0.348	-131.8
1.6	0.411	99.8	3.273	-23.9	0.139	-43.4	0.332	-138.4
1.7	0.415	89.7	3.108	-31.9	0.146	-48.8	0.321	-145.7
1.8	0.416	79.2	2.952	-40.5	0.149	-54.1	0.306	-151.5
1.9	0.421	69.7	2.819	-48.3	0.156	-60.5	0.292	-158.9
2.0	0.426	60.0	2.676	-56.4	0.161	-65.8	0.283	-165.2
2.1	0.431	50.5	2.560	-64.6	0.164	-72.3	0.268	-171.6
2.2	0.434	41.7	2.452	-72.6	0.175	-78.0	0.259	-178.7
2.3	0.439	32.7	2.360	-80.4	0.178	-84.3	0.244	-173.6
2.4	0.446	24.2	2.270	-88.3	0.187	-89.9	0.235	-166.6
2.5	0.450	15.6	2.187	-96.0	0.193	-95.8	0.222	-159.0
2.6	0.461	7.2	2.117	-104.1	0.204	-102.5	0.213	-151.9
2.7	0.467	0.2	2.037	-111.5	0.210	-108.0	0.203	-143.8
2.8	0.474	-7.7	1.969	-119.4	0.219	-115.1	0.194	-136.2
2.9	0.488	-14.6	1.919	-127.1	0.225	-122.8	0.189	-129.6
3.0	0.513	-21.5	1.856	-134.7	0.230	-131.1	0.188	-120.8

V<sub>CE</sub> = 3 V, I<sub>c</sub> = 10 mA

FREQUENCY GHz	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.871	-27.4	23.109	145.2	0.023	28.8	0.963	-18.1
0.2	0.797	-50.9	18.315	120.2	0.042	60.1	0.893	-31.7
0.3	0.731	-72.7	14.604	101.8	0.059	43.2	0.824	-45.6
0.4	0.656	-93.2	11.812	86.7	0.069	34.2	0.738	-56.4
0.5	0.597	-111.6	9.921	74.1	0.073	27.5	0.661	-65.9
0.6	0.541	-128.1	8.442	63.1	0.084	18.4	0.593	-73.9
0.7	0.503	-144.8	7.366	52.6	0.090	9.5	0.542	-82.0
0.8	0.472	-159.6	6.535	43.2	0.101	2.9	0.502	-88.7
0.9	0.449	-173.5	5.869	34.1	0.106	-0.5	0.467	-95.6
1.0	0.427	172.7	5.319	25.1	0.110	-6.8	0.435	-101.8
1.1	0.415	159.9	4.860	16.3	0.116	-14.7	0.408	-108.7
1.2	0.405	147.0	4.488	7.8	0.120	-19.4	0.385	-114.6
1.3	0.403	135.3	4.168	-0.6	0.128	-25.5	0.367	-121.7
1.4	0.400	123.6	3.885	-8.7	0.133	-31.0	0.344	-128.3
1.5	0.399	112.4	3.652	-16.8	0.140	-36.3	0.329	-134.9
1.6	0.396	101.8	3.440	-25.3	0.146	-43.6	0.314	-141.4
1.7	0.402	91.4	3.246	-33.4	0.152	-48.1	0.300	-148.6
1.8	0.406	80.7	3.084	-41.7	0.159	-54.6	0.285	-154.9
1.9	0.411	70.3	2.936	-49.1	0.163	-60.4	0.268	-161.9
2.0	0.413	60.6	2.795	-57.3	0.169	-66.3	0.258	-168.3
2.1	0.420	50.8	2.681	-65.2	0.173	-72.5	0.238	-175.3
2.2	0.425	41.5	2.558	-73.3	0.181	-78.7	0.232	177.6
2.3	0.434	32.5	2.460	-80.9	0.185	-84.5	0.216	169.6
2.4	0.438	23.7	2.368	-88.6	0.194	-91.0	0.208	162.4
2.5	0.446	14.8	2.275	-96.3	0.198	-97.5	0.192	154.5
2.6	0.459	6.8	2.204	-104.1	0.206	-102.5	0.180	146.1
2.7	0.467	-1.7	2.122	-111.8	0.213	-109.1	0.170	138.9
2.8	0.476	-10.2	2.050	-119.3	0.217	-115.4	0.162	129.4
2.9	0.480	-18.4	1.999	-126.9	0.221	-121.6	0.147	120.9
3.0	0.489	-26.4	1.931	-134.4	0.228	-128.2	0.141	110.8

PACKAGE DIMENSIONS

FLAT-LEAD 6 PIN THIN-TYPE ULTRA SUPER MINIMOLD (UNIT: mm)



PIN CONNECTIONS

- |                   |                 |
|-------------------|-----------------|
| 1. Collector (Q1) | 4. Base (Q2)    |
| 2. Emitter (Q1)   | 5. Emitter (Q2) |
| 3. Collector (Q2) | 6. Base (Q1)    |

[MEMO]

[MEMO]

[MEMO]

- **The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.**

- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.
- NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.
- Descriptions of circuits, software, and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software, and information in the design of the customer's equipment shall be done under the full responsibility of the customer. NEC Corporation assumes no responsibility for any losses incurred by the customer or third parties arising from the use of these circuits, software, and information.
- While NEC Corporation has been making continuous effort to enhance the reliability of its semiconductor devices, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC semiconductor device, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.
- NEC devices are classified into the following three quality grades:  
"Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.

Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots

Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)

Specific: Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.

The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books. If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.