


UTC US108S/N

SCR

SCRs

DESCRIPTION

The UTC US108S/N is suitable to fit all modes of control, found in applications such as overvoltage crowbar protection, motor control circuits in power tools and kitchen aids, inrush current limiting circuits, capacitive discharge ignition and voltage regulation circuits.



1: CATHODE 2: ANODE 3: GATE

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATING		UNIT
		US108S	US108N	
Repetitive peak off-state voltages US108S/N-4 US108S/N-6 US108S/N-8	V_{DRM} V_{RRM}	400 600 800		V
RMS on-state current (180° conduction angle) (Tc = 110°C)	$I_{T(RMS)}$	8		A
Average on-state current (180° conduction angle) (Tc = 110°C)	$I_{T(AV)}$	5		A
Non repetitive surge peak on-state current (Tj = 25°C) tp=8.3ms tp=10ms	I_{TSM}	73 70	100 95	A
I²t Value for fusing (tp = 10 ms ,Tj = 25°C)	I^2t	24.5	45	A²S
Critical rate of rise of on-state current (IG = 2 x IGT , tr ≤ 100 n s, Tj = 125°C, F = 60 Hz)	dI/dt	50		A/μs
Peak gate current (tp=20μs, Tj = 125°C)	I_{GM}	4		A
Maximum peak reverse gate voltage	V_{RGM}		5	V
Average gate power dissipation (Tj = 125°C)	$P_{G(AV)}$	1		W
Storage junction temperature range	Tstg	-40 ~ +150		°C
Operating junction temperature range	Tj	-40 ~ +125		°C



UTC US108S(SENSITIVE) ELECTRICAL CHARACTERISTICS

(Tj=25°C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	MAX.	UNIT
Gate trigger Current	I _{GT}	V _D = 12 V, R _L = 140Ω		200	μA
Gate trigger Voltage	V _{GT}	V _D = 12 V, R _L = 140Ω		0.8	V
Gate non-trigger voltage	V _{GD}	V _D = V _{DRM} , R _L = 3.3 kΩ, R _{GK} = 220Ω T _J = 125°C	0.1		V
Reverse gate voltage	V _{RG}	I _{RG} = 10 μA	8		V
Holding Current	I _H	I _T = 50 mA, R _{GK} = 1 kΩ		5	mA
Latching Current	I _L	I _G = 1 mA, R _{GK} = 1 kΩ		6	mA
Circuit Rate Of Change Of off-state Voltage	dV/dt	V _D = 65 % V _{DRM} , R _{GK} = 220 Ω T _J = 125°C	5		V/μs
On-state voltage	V _{TM}	I _{TM} = 16A, t _p = 380 μs T _J = 25°C		1.6	V
Threshold Voltage	V _{th}	T _J = 125°C		0.85	V
Dynamic Resistance	R _d	T _J = 125°C		46	mΩ
Off-state Leakage Current	I _{DRM} I _{RRM}	V _{DRM} = V _{RRM} , R _{GK} = 220 Ω T _J = 25°C T _J = 125°C		5 1	μA mA

UTC US108N(STANDARD) ELECTRICAL CHARACTERISTICS

(Tj=25°C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	MAX.	UNIT
Gate trigger Current	I _{GT}	V _D = 12 V, R _L = 33Ω	2	15	mA
Gate trigger Voltage	V _{GT}	V _D = 12 V, R _L = 33Ω		1.3	V
Gate non-trigger voltage	V _{GD}	V _D = V _{DRM} , R _L = 3.3 kΩ, T _J = 125°C	0.2		V
Holding Current	I _H	I _T = 100 mA, Gate open		30	mA
Latching Current	I _L	I _G = 1.2 I _{GT}		70	mA
Circuit Rate Of Change Of off-state Voltage	dV/dt	V _D = 67 % V _{DRM} , Gate open, T _J = 125°C	150		V/μs
On-state voltage	V _{TM}	I _{TM} = 16A, t _p = 380 μs, T _J = 25°C		1.6	V
Threshold Voltage	V _{th}	T _J = 125°C		0.85	V
Dynamic Resistance	R _d	T _J = 125°C		46	mΩ
Off-state Leakage Current	I _{DRM} I _{RRM}	V _{DRM} = V _{RRM} T _J = 25°C T _J = 125°C		5 2	μA mA

THERMAL RESISTANCES

PARAMETER	SYMBOL	VALUE	UNIT
Junction to case (DC)	R _{th(j-c)}	20	K/W
Junction to ambient (DC)	R _{th(j-a)}	60	K/W

Fig.1:Maximum average power dissipation vs average on-state current




Figure.2:Average and D.C. on-state current vs case temperature




Figure.3: Relative variation of thermal impedance juncto to case vs pulse duration




Figure.4:Relative variation of gate trigger current,holding current and latching vs junction temperature .(US108S)




Figure.4-2:Relative variation of gate trigger current,holding current and latching vs junction temperature .(US108N)




Figure.5:Relative variation of holding current vs gate-cathode resistance(typical values) (US108S)




Fig.6: Relative variation of dV/dt immunity vs gate-cathode resistance (typical values) (US108S)




Fig.7: Relative variation of dV/dt immunity vs gate-cathode resistance (typical values) (US108S)




Figure.8: Surge peak on-state current vs number of cycles.




Fig.9: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $tp < 10ms$, and corresponding values of I^2t .





Fig.10: On-state characteristics (maximum values).



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.