



SAW Components

SAW bandpass Filter

Low loss bandpass filter for terrestrial TV applications

Series/type: X 7550 D

Ordering code:

Date: July 17, 2006

Version: 1.1

© EPCOS AG 2006. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



SAW Components

X 7550 D

SAW bandpass Filter

44.00 MHz

Data sheet


Application

- IF filter for digital terrestrial TV
- Usable bandwidth 5.7 MHz
- Low insertion attenuation




Features

- Duraplast package **SIP5D**
- Approximate weight 0.5 g
- Standard IC package
- RoHS compatible
- Tinned CuFe alloy terminals



Pin configuration

- 1 Input
- 2 Input
- 3 Chip carrier - ground
- 4 Output
- 5 Output





SAW Components

X 7550 D

SAW bandpass Filter

44.00 MHz

Data sheet

Characteristics


Reference temperature: $T_A = 25 (45) ^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \Omega$ and matching network
 Terminating load impedance: $Z_L = 2 \text{ k}\Omega \parallel 3 \text{ pF}$ and matching network

	min.	typ. @ 25 °C	max.	
Insertion attenuation α				
Reference level for 44.06(44.00) MHz the following data	5.0	7.0	9.0	dB
Amplitude ripple (p-p) $\Delta\alpha$				
41.66 ... 46.46 (41.60 ... 46.40) MHz	—	1.5	—	dB
Pass bandwidth				
$\alpha_{\text{rel}} \leq 3 \text{ dB}$ $B_{3\text{dB}}$	—	5.7	—	MHz
Relative attenuation α_{rel}				
39.81 (39.75) MHz	32.0	41.0	—	dB
41.26 (41.20) MHz	—	2.1	—	dB
46.86 (46.80) MHz	—	0.4	—	dB
47.31 (47.25) MHz	20.0	27.0	—	dB
Lower sidelobe				
35.06 ... 40.41 (35.00 ... 40.35) MHz	32.0	38.0	—	dB
Upper sidelobe				
47.71 ... 55.06 (47.65 ... 55.00) MHz	27.0	33.0	—	dB
Reflected wave signal suppression				
1.3 μs ... 6.0 μs after main pulse (test pulse 250 ns, carrier frequency 44.06 MHz)	24.0	34.0	—	dB
Group delay ripple (p-p) Δt				
41.66 ... 46.46 (41.60 ... 46.40) MHz	—	190	—	ns
Impedance at 44.06 MHz				
Input: $Z_{\text{IN}} = R_{\text{IN}} \parallel C_{\text{IN}}$	—	1.0 \parallel 21.7	—	k Ω \parallel pF
Output: $Z_{\text{OUT}} = R_{\text{OUT}} \parallel C_{\text{OUT}}$	—	8.0 \parallel 3.6	—	k Ω \parallel pF
Temperature coefficient of frequency TC_f	—	-72	—	ppm/K



SAW Components	X 7550 D
SAW bandpass Filter	44.00 MHz

Data sheet



Maximum ratings

Operable temperature range	T	-25 / +65	°C	
Storage temperature range	T _{stg}	-40 / +85	°C	
DC voltage	V _{DC}	5	V	
AC voltage	V _{pp}	10	V	between any terminals



SAW Components



X 7550 D

SAW bandpass Filter

44.00 MHz

Data sheet

Frequency response



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components


X 7550 D

SAW bandpass Filter


44.00 MHz

Data sheet

Frequency response



Time domain response





SAW Components

X 7550 D

SAW bandpass Filter

44.00 MHz

Data sheet

References

Type	X 7550 D
Ordering code	
Marking and package	C61157-A1-A21
Packaging	F61074-V8049-Z000
Date codes	L_1126
S-parameters	X7550D_NB.s4p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

**Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2006. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, Silver-Cap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.