




ZPY3V9 to ZPY100

Vishay Semiconductors

Zener Diodes

Features

- Silicon Planar Power Zener Diodes
- For use in stabilizing and clipping circuits with high power rating
- The Zener voltages are graded according to the international E 12 standard. Smaller voltage tolerances are available upon request
- These diodes are also available in the MELF case with the type designation ZMY3V9 to ZMY100
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



17173

Mechanical Data

Case: DO41 Glass case

Weight: approx. 310 mg

Cathode Band Color: black

Packaging Codes/Options:

TR/5 k per 13" reel (52 mm tape), 25 k/box

TAP/5 k per Ammo mag. (52 mm tape), 25 k/box

Absolute Maximum Ratings

T_{amb} = 25 °C, unless otherwise specified

| Parameter | Test condition | Symbol | Value | Unit |
|--|----------------|------------------|-------------------|------|
| Zener current (see Table "Characteristics") | | | | |
| Power dissipation | | P _{tot} | 1.3 ¹⁾ | W |

¹⁾ Valid provided that leads at a distance of 4 mm from case are kept at ambient temperature

Thermal Characteristics

T_{amb} = 25 °C, unless otherwise specified

| Parameter | Test condition | Symbol | Value | Unit |
|--|----------------|-------------------|-------------------|------|
| Thermal resistance junction to ambient air | | R _{thJA} | 110 ¹⁾ | K/W |
| Maximum junction temperature | | T _j | 175 | °C |
| Storage temperature range | | T _{stg} | - 55 to + 175 | °C |

¹⁾ Valid provided that leads at a distance of 4 mm from case are kept at ambient temperature



ZPY3V9 to ZPY100



Vishay Semiconductors

Electrical Characteristics

| Partnumber | Zener Voltage Range ²⁾ | | Dynamic Resistance | Temperature Coefficient of Zener Voltage | | Test Current | Reverse Voltage | Admissible Zener Current ¹⁾ |
|------------|-----------------------------------|------|--|--|-----|--------------|----------------------------|--|
| | V_Z at I_{ZT} | | r_{zi} at I_{ZT1} , $f = 1$ kHz | TC_{VZ} at I_{ZT} | | I_{ZT} | V_R at $I_R = 0.5 \mu A$ | I_Z at $T_{amb} = 25^\circ C$ |
| | V | | Ω | $10^{-4}/^\circ C$ | | mA | V | mA |
| | min | max | typ | min | max | | | |
| ZPY3V9 | 3.7 | 4.1 | 4 (< 7) | - 7 | 2 | 100 | - | 290 |
| ZPY4V3 | 4.0 | 4.6 | 4 (< 7) | - 7 | 3 | 100 | - | 260 |
| ZPY4V7 | 4.4 | 5.0 | 4 (< 7) | - 7 | 4 | 100 | - | 235 |
| ZPY5V1 | 4.8 | 5.4 | 2 (< 5) | - 6 | 5 | 100 | > 0.7 | 215 |
| ZPY5V6 | 5.2 | 6.0 | 1 (< 2) | - 3 | 5 | 100 | > 1.5 | 193 |
| ZPY6V2 | 5.8 | 6.6 | 1 (< 2) | - 1 | 6 | 100 | > 2.0 | 183 |
| ZPY6V8 | 6.4 | 7.2 | 1 (< 2) | 0 | 7 | 100 | > 3.0 | 157 |
| ZPY7V5 | 7.0 | 7.9 | 1 (< 2) | 0 | 7 | 100 | > 5.0 | 143 |
| ZPY8V2 | 7.7 | 8.7 | 1 (< 2) | 3 | 8 | 100 | > 6.0 | 127 |
| ZPY9V1 | 8.5 | 9.6 | 2 (< 4) | 3 | 8 | 50 | > 7.0 | 117 |
| ZPY10 | 9.41 | 10.6 | 2 (< 4) | 5 | 9 | 50 | > 7.5 | 105 |
| ZPY11 | 10.4 | 11.6 | 3 (< 7) | 5 | 10 | 50 | > 8.5 | 94 |
| ZPY12 | 11.4 | 12.7 | 3 (< 7) | 5 | 10 | 50 | > 9.0 | 85 |
| ZPY13 | 12.4 | 14.1 | 4 (< 9) | 5 | 10 | 50 | > 10 | 78 |
| ZPY15 | 13.8 | 15.8 | 4 (< 9) | 5 | 10 | 50 | > 11 | 70 |
| ZPY16 | 15.3 | 17.1 | 5 (< 10) | 7 | 11 | 25 | > 12 | 63 |
| ZPY18 | 16.8 | 19.1 | 5 (< 11) | 7 | 11 | 25 | > 14 | 57 |
| ZPY20 | 18.8 | 21.2 | 6 (< 12) | 7 | 11 | 25 | > 15 | 52 |
| ZPY22 | 20.8 | 23.3 | 7 (< 13) | 7 | 11 | 25 | > 17 | 48 |
| ZPY24 | 22.8 | 25.6 | 8 (< 14) | 7 | 12 | 25 | > 18 | 42 |
| ZPY27 | 25.1 | 28.9 | 9 (< 15) | 7 | 12 | 25 | > 20 | 38 |
| ZPY30 | 28 | 32 | 10 (< 20) | 7 | 12 | 25 | > 22.5 | 35 |
| ZPY33 | 31 | 35 | 11 (< 20) | 7 | 12 | 25 | > 25 | 31 |
| ZPY36 | 34 | 38 | 25 (< 60) | 7 | 12 | 10 | > 27 | 29 |
| ZPY39 | 37 | 41 | 30 (< 60) | 8 | 12 | 10 | > 29 | 26 |
| ZPY43 | 40 | 46 | 35 (< 80) | 8 | 13 | 10 | > 32 | 24 |
| ZPY47 | 44 | 50 | 40 (< 80) | 8 | 13 | 10 | > 35 | 22 |
| ZPY51 | 48 | 54 | 45 (< 100) | 8 | 13 | 10 | > 38 | 20 |
| ZPY56 | 52 | 60 | 50 (< 100) | 8 | 13 | 10 | > 42 | 18 |
| ZPY62 | 58 | 66 | 60 (< 130) | 8 | 13 | 10 | > 47 | 16 |
| ZPY68 | 64 | 72 | 65 (< 130) | 8 | 13 | 10 | > 51 | 14 |
| ZPY75 | 70 | 79 | 70 (< 160) | 8 | 13 | 10 | > 56 | 13 |
| ZPY82 | 77 | 88 | 80 (< 160) | 8 | 13 | 10 | > 61 | 12 |
| ZPY91 | 85 | 96 | 120 (< 250) | 9 | 13 | 5 | > 68 | 11 |
| ZPY100 | 94 | 106 | 130 (< 250) | 9 | 13 | 5 | > 75 | 10 |

¹⁾ Valid provided that leads are kept at ambient temperature at a distance of 10 mm from case

²⁾ Tested with pulses $t_p = 5$ ms



ZPY3V9 to ZPY100

Vishay Semiconductors

Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified




Figure 1. Admissible Power Dissipation vs. Ambient Temperature




Figure 4. Dynamic Resistance vs. Zener Current




Figure 2. Pulse Thermal Resistance vs. Pulse Duration




Figure 5. Dynamic Resistance vs. Zener Current




Figure 3. Dynamic Resistance vs. Zener Current




Figure 6. Thermal Resistance vs. Lead Length

ZPY3V9 to ZPY100

Vishay Semiconductors




Figure 7. Breakdown Characteristics




Figure 9. Breakdown Characteristics





Figure 8. Breakdown Characteristics

Package Dimensions in mm (Inches): DO41





Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.