


200 V - 1,000 V Single Phase Bridge
3.0 A Forward Current
70 ns - 3000 ns Recovery Time


1202C - 1210C
1202FC - 1210FC
1202UFC - 1210UFC



ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage (Vrwm)	Average Rectified Current @TC (Io)		Reverse Current @ Vrwm (Ir)		Forward Voltage (Vf)		1 Cycle Surge Current tp=8.3ms (Ifsm)	Repetitive Surge Current (Ifrm)	Reverse Recovery Time (1) (Trr)	Thermal Impd. θ_{J-C}
		55°C	100°C	25°C	100°C	25°C	25°C	25°C	25°C	25°C	°C/W
		Amps	Amps	μ A	μ A	Volts	Amps	Amps	Amps	ns	
1202C	200	3.0	1.8	1.0	25	1.1	3.0	150	25	3000	21
1206C	600	3.0	1.8	1.0	25	1.1	3.0	150	25	3000	21
1210C	1000	3.0	1.8	1.0	25	1.1	3.0	150	25	3000	21
1202FC	200	3.0	1.8	1.0	25	1.5	3.0	100	20	150	21
1206FC	600	3.0	1.8	1.0	25	1.5	3.0	100	20	150	21
1210FC	1000	3.0	1.8	1.0	25	1.5	3.0	100	20	150	21
1202UFC	200	3.0	1.8	1.0	25	1.7	3.0	100	20	70	21
1206UFC	600	3.0	1.8	1.0	25	1.7	3.0	100	20	70	21
1210UFC	1000	3.0	1.8	1.0	25	1.7	3.0	100	20	70	21

(1)Trr Testing: If=0.5A, Ir=1.0A, Irr=0.25A *Op. Temp.= -55°C to +150°C Stg. Temp.= -55°C to +150°C



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



VOLTAGE MULTIPLIERS INC.
 8711 W. Roosevelt Ave.
 Visalia, CA 93291

TEL 559-651-1402
 FAX 559-651-0740
 www.voltagemultipliers.com

1202C - 1210C • 1202FC - 1210FC • 1202UFC - 1210UFC

