




Data Sheet No. 2C2222A

Chip Type 2C2222A
Geometry 0400
Polarity NPN

Generic Packaged Parts:

2N2219, 2N2219A, 2N2222, 2N2222A



[Request Quotation](#)

Chip type **2C2222A** by Semicoa Semiconductors provides performance similar to these devices.

Product Summary:

APPLICATIONS: Designed for general purpose switching and amplifier applications.

Part Numbers:

2N2222A, 2N2222, 2N2219, 2N2219A, 2N2219AL, 2N2222AUB, SD2222A, SD2222AF, SQ2222A, SQ2222AF, 2N5582, 2N6989, 2N6990

Features: Medium power ratings

Mechanical Specifications		
Metallization	Top	Al - 24 kÅ min.
	Backside	Au - 6.5 kÅ nom.
Bonding Pad Size	Emitter	4.0 mils x 4.0 mils
	Base	4.0 mils x 4.0 mils
Die Thickness	8 mils nominal	
Chip Area	20 mils x 20 mils	
Top Surface	Silox Passivated	

Electrical Characteristics				
$T_A = 25^\circ\text{C}$				
Parameter	Test conditions	Min	Max	Unit
BV_{CEO}	$I_C = 10\text{ mA}, I_B = 0$	40	---	V dc
BV_{CBO}	$I_C = 10\ \mu\text{A}, I_E = 0$	75	---	V dc
BV_{EBO}	$I_E = 10\ \mu\text{A}, I_C = 0$	6.0	---	V dc
I_{CBO}	$V_{CB} = 50\text{ V}, I_E = 0$	---	10	nA dc
h_{FE}	$I_C = 150\text{ mA dc}, V_{CE} = 10\text{ V}$	100	300	---

Due to limitations of probe testing, only dc parameters are tested. This must be done with pulse width less than 300 μs , duty cycle less than 2%.

