

TO-92 Plastic Package Transistors (NPN)

Maximum Ratings										Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)															
Type No.	V _{CEO} (V)	V _{CE0} (V)	V _{CE0} (V)	P _D (W)	I _C (A)	I _{CEO} (μA)	V _{CE0} (V)	I _{CEO} (μA)	V _{CE0} (V)	f _{re} (MHz)	β	I _C & I _{CE} (mA)	V _{CE0} (V)	V _{CE(sat)} (V)	V _{CE(sat)} (V)	I _C (mA)	C _{ob} (pF)	f _T (MHz)	β	I _C (mA)	f _{sw} (kHz)	S _F (dB)	Freq (MHz)	C _{ob} (pF)	CDE Case Style
	Min	Min	Min	@Tc=25°C	Max	Max	Max	Min	Max																
2SC2274D	100	80	5	0.6	0.5	1	40			80	120	50	5	0.6	1.2	400	5	120	10						TO-92-1
2SC2274E	100	80	5	0.8	0.5	1	40			100	200	50	5	0.6	1.2	400	5	120	10						TO-92-1
2SC2274F	100	80	5	0.6	0.5	1	40			160	320	50	5	0.6	1.2	400	5	120	10						TO-92-1
2SC2274K	100	80	5	0.6	0.5	1	40			60	320	50	5	0.6	1.2	400	5	120	10						TO-92-1
2SC2300	55	50	5	0.2	0.1	0.5	18			250	1200	2	12	0.2		10	3.5	150	230	2					TO-92-1
2SC2300D	55	50	5	0.2	0.1	0.5	18			250	500	2	12	0.2		10	3.5	150	230	2					TO-92-1
2SC2300E	55	50	5	0.2	0.1	0.5	18			400	800	2	12	0.2		10	3.5	150	230	2					TO-92-1
2SC2300F	55	50	5	0.2	0.1	0.5	18			600	1200	2	12	0.2		10	3.5	150	230	2					TO-92-1
2SC2458	50	50	5	0.2	0.15	0.1	50			70	700	2	6	0.25	100	3.5	80			1		10			TO-92-1
2SC2458BL	50	50	5	0.2	0.2	0.1	50			350	700	2	6	0.25	100	3.5	80			1		10			TO-92-1
2SC2458GF	50	50	5	0.2	0.15	0.1	50			200	400	2	6	0.25	100	3.5	80			1		10			TO-92-1
2SC2458D	50	50	5	0.2	0.15	0.1	50			70	140	2	6	0.25	100	3.5	80			1		10			TO-92-1
2SC2458Y	50	50	5	0.2	0.15	0.1	50			120	240	2	6	0.25	100	3.5	80			1		10			TO-92-1
2SC2462	300	300	7	0.9	0.1	1	240			20		4	10	1	1	10	3	50		20					TO-92-1
2SC3114	60	50	7	0.4	0.15	0.1	40			100	560	1	6	0.5	50	3	100			1					TO-92-1
2SC3114R	60	50	7	0.4	0.15	0.1	40			100	200	1	6	0.5	50	3	100			1					TO-92-1
2SC3114S	60	50	7	0.4	0.15	0.1	40			140	280	1	6	0.5	50	3	100			1					TO-92-1
2SC3114T	60	50	7	0.4	0.15	0.1	40			200	400	1	6	0.5	50	3	100			1					TO-92-1
2SC3114U	60	50	7	0.4	0.15	0.1	40			280	560	1	6	0.5	50	3	100			1					TO-92-1
2SC3187	30	25	4	0.3	0.05	0.1	30			20	200	12.5	12.5	0.2	1.5	13	0.8	2	300		13				TO-92-1
2SC3198	60	50	5	0.625	0.15	0.1	60			70	700	2	6	0.25	1	100	2	3.5	80		1		10		TO-92-1
2SC3198BL	60	50	5	0.625	0.15	0.1	60			350	700	2	6	0.25	1	100	2	3.5	80		1		10		TO-92-1
2SC3198GF	60	50	5	0.625	0.15	0.1	60			200	400	2	6	0.2	1	100	2	3.5	80		1		10		TO-92-1
2SC3198D	60	50	5	0.625	0.15	0.1	60			70	140	2	6	0.25	1	100	2	3.5	80		1		10		TO-92-1
2SC3198Y	60	50	5	0.625	0.15	0.1	60			120	240	2	6	0.25	1	100	2	3.5	80		1		10		TO-92-1
2SC3199	50	50	5	0.4	0.15	0.1	50			70	700	2	6	0.25		100	2	3.5	80		1		10		TO-92-1
2SC3199C	50	50	5	0.4	0.15	0.1	50			200	400	2	6	0.25		100	2	3.5	80		1				TO-92-1
2SC3199D	50	50	5	0.4	0.15	0.1	50			70	140	2	6	0.25		100	2	3.5	80		1		10		TO-92-1

