



2223-1.7

1.7 Watts - 24 Volts, Class C
Microwave 2200 - 2300 MHz

GENERAL DESCRIPTION

The 2223-1.7 is a COMMON BASE transistor capable of providing 1.7 Watts of Class C, RF output power over the band 2200 - 2300 MHz. This transistor is designed for Microwave Broadband Class C amplifier applications. It includes input prematching and utilizes Gold metalization and diffused ballasting to provide high reliability and supreme ruggedness. The transistor uses a fully hermetic High Temperature Solder sealed package.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C 7 Watts


Maximum Voltage and Current

BVces	Collector to Emitter Voltage	45 Volts
BVebo	Emitter to Base Voltage	3.5 Volts
Ic	Collector Current	.25 Amps

Maximum Temperatures

Storage Temperature	- 65 to + 200°C
Operating Junction Temperature	+ 200°C

CASE OUTLINE 55LV, STYLE 1



ELECTRICAL CHARACTERISTICS @ 25°C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout	Power Output	F = 2.2 - 2.3 GHz	1.7		.25	Watts
Pin	Power Input	Vcc = 24 Volts	8.3	35		Watts
Pg	Power Gain					dB
ηc	Efficiency					%
VSWR	Load Mismatch Tolerance				10:1	

BVces	Collector to Base Breakdown	Ic = 10 mA	40		100	Volts
BVebo	Emitter to Base Breakdown	Ie = 2 mA	3.5			Volts
Hfe	Current Gain	Vce = 5 V, Ic = 160mA	10			
Cob	Output Capacitance	Vcb = 28V, 1MHz				pF
θjc	Thermal Resistance	Tc = 25 °C			24	°C/W

Issue A June 1997

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

GHz Technology Inc. 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120




GHz TECHNOLOGY
RF·MICROWAVE SILICON POWER TRANSISTORS

2223-1.7


EFFICIENCY VS POWER IN

FREQUENCY=2.25 GHz




POWER OUTPUT VS POWER INPUT

FREQUENCY=2.25 GHz




INPUT IMPEDANCE

Vcc=22V, Pin=.25Wk



LOAD IMPEDANCE

Vcc=22V, Pin=.25W




August 1996




REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED



DIM	INCHES
A	.200
B	.350
C	.160
D	.053
E	.100
F	.455
G	.230
H	.300
I	.245
J	.330
K	.270
L	.500
M	.445
N	.150
O	.800
P	.150
Q	.190
R	.053

2223-1.7 TEST CIRCUIT



DIELECTRIC = 19.4 MIL THICK TFE Er = 2.43
 C1, C2 = 62pF CHIP ATC "A"
 C3 = 10MFD @ 35V
 RFC = 4 turns #22 wire on 1/16" dia.



CHz TECHNOLOGY

CAGE
OPJR2

DWG NO.

2223-1.7

REV

A

SCALE 1/1 CHEET