



工程文件 ■ 製訂 / □ 變更 通知單
Engineer document formulated or modified Notice

文件編號: (Device Number)	CDLE-033-1550
ECN#	
2005年9月21日	頁數 page
共6頁 total 6	

名稱: No.	333-2UYC/H3/S400-A7	版次 REV.	原 1 版變更 為 -- 版	日期 date
---------	---------------------	---------	----------------	---------

製訂 / 變更內容摘要: (篇幅不足, 請以另紙附上):
document workout / revise content

訂項目 Workout Item:

- ☐ 新產品
New product
- ☐ 衍生機種
Serial device
- ☒ 新制訂規格
New specification

變更項目 Revise Item:

- ☐ 材料變更
change material
- ☐ 製程變更
change process
- ☐ 設備、治具 fixture、tool
- ☐ 規格變更
change specification

處理方式 Disposition:

- ☐ 舊材料處理方式
Old material
- ☐ WIP WIP
- ☐ 舊庫存 old storage

製訂 / 變更理由: (請詳細說明): File formulating/modifying reasons: (Please detailed explain)

規格依據 (Specification basis):

此規格依據客戶需求制作 (Specification basis formulate on the customer sheweichile

工程編號 (Engineer Number) 業務編號 (Sales umber):

捷多邦, 专业PCB加工厂, 24小时加急出货

製六	制三	制二	制一	工程二	工程一	資材	生技	复印 COPY			人資部	業務部	資材部	維護審核	台北品保	台北研一部	台北審核	製六
chpd3	chpd3	chpd2	chpd1	chrd2	chrd1	chpc	chie	制三部	制二部	制一部	Chpn	cm	chpc	R/M	qp	rd1	chqa	chpd3
／	／	／	／	／	1	／	／	／	／	／	／	／	／	／	／	／	／	／
台北 TP				人資 chpn	業務 CM	維護 R/M	品保 chqa					制六部 chie	生技 chie	工程二 chrd2 check	工程一 chrd1 check	部門主管 Department Charger	提案人 assigner	1



EVERLIGHT ELECTRONICS CO.,LTD.

DATA SHEET

1.1000PCS/ PART NO. : 333-2UYC/H3/S400-A7

DATE : 2005/9/21

DEPARTMENT : CHR&D1

REVISION : 1

RECEIVED			
☒ MASS PRODUCTION			
☐ PRELIMINARY			
☐ CUSTOMER DESIGN			
DEVICE NUMBER : CDLE-033-1550			
PAGE : 6			
CUSTOMER	DESIGNER	CHECKER	APPROVER

REV.	DESCRIPTION	RELEASE DATE

OFFICE: 7C BUILDING, LIAN HUA PORT INDUSTRIAL DISTRICT, LIAN HUA SHAN

BONDED PRICESSING ZONE PAN YU, GUANG ZHU, CHINA

TEL. : (020)84860913,84860914

FAX : (020)84860600

[http : //www.everlight.com](http://www.everlight.com)



Technical Data Sheet

5.0mm Round Type LED Lamps

333-2UYC/H3/S400-A7

■ Features :

- Choice of various viewing angles
- Available on tape and reel.
- Reliable and robust
- Pb free
- The product itself will remain within RoHS compliant version.



■ Descriptions :

- The series is specially designed for applications requiring higher brightness
- The led lamps are available with different colors, intensities.

■ Applications :

- TV set
- Monitor
- Telephone
- Computer


PART NO.	Material	Emitted Color	Lens Color
333-2UYC/H3/S400-A7	AlGaInP	Super Yellow	Water Clear



Technical Data Sheet
5.0mm Round Type LED Lamps

333-2UYC/H3/S400-A7

Package Dimensions



- Notes: 1. All dimensions are in millimetres
2. The height of flange must be less than 1.5mm(0.059").
3. Without special declared,the tolerance is ±0.25mm.

■ Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit
Forward Current	IF	50	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Electrostatic Discharge	ESD	2000	V
Power Dissipation	Pd	120	mW
Reverse Voltage	VR	5	V

Note: *1:Soldering time ≤ 5 seconds.



Technical Data Sheet

5.0mm Round Type LED Lamps

333-2UYC/H3/S400-A7

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V _F	I _F = 20 mA	2.0	/	2.4	V
Reverse Current	I _R	V _R = 5 V	/	/	10	μA
Luminous Intensity	I _v	I _F = 20 mA	2000	3200	/	mcd
Viewing Angle	2θ 1/2	I _F = 20 mA	/	20	/	deg
Peak Wavelength	λ _p	I _F = 20 mA	/	591	/	nm
Dominant Wavelength	λ _d	I _F = 20 mA	/	589	/	nm
Spectrum Radiation Bandwidth	△λ	I _F = 20 mA	/	15	/	nm









Technical Data Sheet

5.0mm Round Type LED Lamps

333-2UYC/H3/S400-A7

Typical Electro-Optical Characteristic Curves:

(UY)





Technical Data Sheet

5.0mm Round Type LED Lamps

333-2UYC/H3/S400-A7

■ Reliability test items and conditions:

The reliability of products shall be satisfied with items listed below.

Confidence level : 97%

LTPD : 3%

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Failure Judgment Criteria	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	10 SEC	76 PCS	$I_v \leq I_{vt} * 0.5$ or $V_f \geq U$ or $V_f \leq L$	0/1
2	Temperature Cycle	H : +100°C 15min § 5 min L : -40°C 15min	300 CYCLES	76 PCS		0/1
3	Thermal Shock	H : +100°C 5min § 10 sec L : -10°C 5min	300 CYCLES	76 PCS		0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS		0/1
5	Low Temperature Storage	TEMP : -40°C	1000 HRS	76 PCS		0/1
6	DC Operating Life	TEMP : 25°C $I_F = 20\text{mA}$	1000 HRS	76 PCS		0/1
7	High Temperature / High Humidity	85°C / 85% RH	1000 HRS	76 PCS		0/1

Note : I_{vt} : To test I_v value of the chip before the reliability test

I_v : The test value of the chip that has completed the reliability test

U : Upper Specification Limit

L : Lower Specification Limit



Technical Data Sheet

5.0mm Round Type LED Lamps


333-2UYC/H3/S400-A7

Packing Quantity Specification

1.500PCS/1Bag , 5Bags/1Box

2.10Boxes/1Carton

Label Form Specification



CPN: Customer's Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: Ranks

HUE: Dominant Wavelength

REF: Reference

LOT No: Lot Number

MADE IN TAIWAN: Production Place

MADE IN TAIWAN

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT ELECTRONICS CO., LTD. Tel: 886-2-2267-2000, 2267-9936
Office: No 25, Lane 76, Sec 3, Chung Yang Rd, Fax: 886-2267-6244, 2267-6189, 2267-6306
Tucheng, Taipei 236, Taiwan, R.O.C <http://www.everlight.com>