



7830-0000-CD 780nm 3 mW Laser Diodes

Specifications

Device Laser Diode

Package Type TO-18(5.6mm)

●Absolute maximum ratings ($T_c = 25^\circ\text{C}$)

Parameter	Symbol	Limits	Unit
Output	P_o	5	mW
Reverse voltage	V_R	2	V
PIN photodiode	$V_{R(PIN)}$	30	V
Operating temperature	T_{opr}	-10~+60	°C
Storage temperature	T_{stg}	-40~+85	°C

●Electrical and optical characteristics ($T_c = 25^\circ\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Threshold current	I_{th}	—	35	60	mA	—
Operating current	I_{op}	—	45	70	mA	$P_o=3\text{mW}$
Operating voltage	V_{op}	—	1.9	2.3	V	$P_o=3\text{mW}$
Differential efficiency	η	0.1	0.25	0.6	mW/mA	$\frac{2\text{mW}}{I(3\text{mW})-I(1\text{mW})}$
Monitor current	I_m	0.1	0.2	0.6	mA	$P_o=3\text{mW}, V_{R(PIN)}=15\text{V}$
Parallel divergence angle	$\theta_{//}^*$	8	11	15	deg	$P_o=3\text{mW}$
Perpendicular divergence angle	θ_{\perp}^*	20	37	45	deg	
Parallel deviation angle	$\Delta \theta_{//}$	—	—	±2	deg	
Perpendicular deviation angle	$\Delta \theta_{\perp}$	—	—	±3	deg	
Emission point accuracy	ΔX ΔY ΔZ	—	—	±80	μm	—
Peak emission wavelength	λ	770	785	810	nm	$P_o=3\text{mW}$
Signal-to-noise ratio	S / N	60	—	—	dB	$f=720\text{kHz}, \Delta f=10\text{kHz}$

* $\theta_{//}$ and θ_{\perp} are defined as the angle within which the intensity is 50% of the peak value.