

查询8034供应商

捷多邦, 专业

Choke

Surface Mount Common Mode Chokes

8033 8034



PCB打样

, 24小时加急出货


- For use with LAN and Telecom applications
- Reduce radiated EMI emissions
- Filters common mode noise for EMI reduction
- Common mode attenuation from 100 kHz to 1 GHz
- 500 Vrms isolation





MECHANICAL AND SCHEMATIC (All dimensions in inches)



SUGGESTED PAD LAYOUT



SCHEMATICS



UNLESS OTHERWISE SPECIFIED, ALL TOLERANCES ARE ±0.010

ELECTRICAL SPECIFICATION @ 25°C

Part Number	No. of Lines	Primary Inductance (µH MIN)	DCR (Ω MAX)	Common Mode Attenuation (dB TYP)								
				100 kHz	1 MHz	10 MHz	30 MHz	50 MHz	100 MHz	300 MHz	500 MHz	1 GHz
8033	4	24	0.30	-7	-20	-30	-37	-38	-34	-24	-13	-
8034	4	100	0.60	-14	-33	-44	-48	-49	-44	-34	-29	-20

1. Leakage Inductance: 0.23µH MAX @ 0.1 V, 100 kHz
2. Interwinding Capacitance: 15 pF MAX @ 0.1V, 100 kHz

ISSUE: C, 00, 0/03 8033-3/4



找PDF
维库一下