



7.2~15W AC-DC Single Output Desktop

GS15B series



■ Features :

- Universal AC input / Full range
- No load power consumption <0.5W
- Meet energy star level IV(CEC) for 5 ~ 48V
- Meet EISA 2007 (Energy Independence and Security Act) for 5 ~ 48V
- 2 pole AC inlet IEC320-C8
- Class II power (without earth pin)
- Full output 3~48V safety approval
- Protections: Short circuit / Overload / Over voltage
- Pass LPS
- Fully enclosed plastic case
- Approvals: UL / CUL / TUV / CB / FCC / CE
- 2 years warranty



SPECIFICATION

| ORDER NO. | GS15B-0P1J | GS15B-1P1J | GS15B-11P1J | GS15B-2P1J | GS15B-3P1J | GS15B-4P1J | GS15B-5P1J | GS15B-6P1J | GS15B-8P1J | |
|------------------------|---|--|-------------|-------------|------------|------------|------------|------------|------------|-----------|
| OUTPUT | SAFETY MODEL NO. | GPSU15B-0 | GPSU15B-1 | GPSU15B-1-1 | GPSU15B-2 | GPSU15B-3 | GPSU15B-4 | GPSU15B-5 | GPSU15B-6 | GPSU15B-8 |
| | DC VOLTAGE Note.2 | 3.3V | 5V | 7.5V | 9V | 12V | 15V | 18V | 24V | 48V |
| | RATED CURRENT | 2.18A | 2.40A | 1.60A | 1.66A | 1.25A | 1.00A | 0.83A | 0.62A | 0.31A |
| | CURRENT RANGE | 0 ~ 2.18A | 0 ~ 2.40A | 0 ~ 1.60A | 0 ~ 1.66A | 0 ~ 1.25A | 0 ~ 1.00A | 0 ~ 0.83A | 0 ~ 0.62A | 0 ~ 0.31A |
| | RATED POWER | 7.2W | 12W | 12W | 15W | 15W | 15W | 15W | 15W | 15W |
| | RIPPLE & NOISE (max.) Note.3 | 50mVp-p | 50mVp-p | 80mVp-p | 80mVp-p | 80mVp-p | 100mVp-p | 120mVp-p | 150mVp-p | 240mVp-p |
| | VOLTAGE ADJ. RANGE | 3 ~ 5V | 5 ~ 6V | 6 ~ 8V | 8 ~ 11V | 11 ~ 13V | 13 ~ 16V | 16 ~ 21V | 21 ~ 27V | 33 ~ 48V |
| | | Fixed | | | | | | | | |
| | VOLTAGE TOLERANCE Note.4 | ±6.0% | ±5.0% | ±5.0% | ±5.0% | ±3.0% | ±3.0% | ±3.0% | ±2.0% | ±2.0% |
| | LINE REGULATION Note.5 | ±1.0% | ±0.5% | ±0.5% | ±0.5% | ±0.5% | ±0.5% | ±0.5% | ±0.5% | ±0.5% |
| | LOAD REGULATION Note.6 | ±6.0% | ±5.0% | ±5.0% | ±5.0% | ±3.0% | ±3.0% | ±3.0% | ±2.0% | ±2.0% |
| INPUT | SETUP, RISE, HOLD UP TIME | 3000ms, 50ms, 16ms at full load | | | | | | | | |
| | VOLTAGE RANGE | 90 ~ 264VAC 135 ~ 370VDC | | | | | | | | |
| | FREQUENCY RANGE | 47 ~ 63Hz | | | | | | | | |
| | EFFICIENCY (Typ.) Note.7 | 55% | 65% | 72% | 74% | 76% | 77% | 78% | 80% | 81% |
| | AC CURRENT | 0.5A / 100VAC | | | | | | | | |
| | INRUSH CURRENT (max.) | 50A / 230VAC | | | | | | | | |
| PROTECTION | LEAKAGE CURRENT(max.) | 0.25mA / 240VAC | | | | | | | | |
| | OVERLOAD | 115 ~ 250% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed | | | | | | | | |
| | OVER VOLTAGE | >120% rated output voltage Protection type : Clamp by zener diode | | | | | | | | |
| | WORKING TEMP. | 0 ~ +50°C (Refer to output load derating curve) | | | | | | | | |
| ENVIRONMENT | WORKING HUMIDITY | 20% ~ 90% RH non-condensing | | | | | | | | |
| | STORAGE TEMP., HUMIDITY | -20 ~ +85°C, 10 ~ 95% RH | | | | | | | | |
| | TEMP. COEFFICIENT | ±0.03% / °C (0 ~ 50°C) | | | | | | | | |
| | VIBRATION | 10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes | | | | | | | | |
| SAFETY & EMC (Note. 8) | SAFETY STANDARDS | UL60950-1, CSA22.2, EN60950-1 approved | | | | | | | | |
| | WITHSTAND VOLTAGE | I/P-O/P:3KVAC | | | | | | | | |
| | ISOLATION RESISTANCE | I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH | | | | | | | | |
| | EMI CONDUCTION & RADIATION | Compliance to EN55022 class B, FCC part 15 Class B | | | | | | | | |
| | HARMONIC CURRENT | Compliance to EN61000-3-2,3 | | | | | | | | |
| | EMS IMMUNITY | Compliance to EN61000-4-2,3,4,5,6,11, light industry level, criteria A | | | | | | | | |
| OTHERS | MTBF | 500Khrs min. MIL-HDBK-217F(25°C) | | | | | | | | |
| | DIMENSION | 100*58.5*32.8mm (L*W*H) | | | | | | | | |
| | PACKING | 190g ; 90pcs / 18Kg / CARTON | | | | | | | | |
| CONNECTOR | PLUG | Standard type P1J: 2.1φ * 5.5φ * 11mm, tuning fork type center positive for stock ; Other type available by customer requested | | | | | | | | |
| | CABLE | Standard type 18Awg UL1185 6ft and 5ft for 3.3V output only for stock ; Other type available by customer requested | | | | | | | | |
| NOTE | 1. All parameters are specified at 230VAC input, rated load, 25°C 70% RH ambient. 2. DC voltage: The output voltage set at point measure by plug terminal & 50% load. 3. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor. 4. Tolerance: includes set up tolerance, line regulation, load regulation. 5. Line regulation is measured from low line to high line at rated load. 6. Load regulation is measured from 0% to 100% rated load. 7. Efficiency is measured at 230VAC. 8. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. | | | | | | | | | |

