


SMD Type

Diodes


ULTRA HIGH SPEED SWITCHING APPLICATION

1SS336



■ Features

- Small package
- Low forward voltage: $V_{F3} = 0.84$ V(Typ).
- Fast reverse recovery time: $t_{rr} = 7$ ns(Typ).
- Small total capacitance : $C_T = 7$ pF(Typ).

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Maximum(Peak) Reverse Voltage	V_{RM}	85	V
Reverse Voltage	V_R	80	V
Maximum(Peak) Forward Current	I_{FM}	600*	mA
Average Rectified Current	I_o	200*	mA
Surge Current (10 ms)	I_{FSM}	6*	A
Power Dissipation	P	150	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55 to +150	°C

* Unit Rating.Total Rating = Unit Rating \times 1.5

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Continuous reverse voltage	V_F	$I_F = 10$ mA		0.64		V
		$I_F = 100$ mA		0.78		
		$I_F = 200$ mA		0.84	1.2	
Reverse current	I_R	$V_R = 30$ V			0.25	μA
	I_R	$V_R = 80$ V			0.5	
capacitance	C_T	$V_R = 0$, $f = 1.0$ MHz		7		pF
Reverse recovery time	t_{rr}	$I_F = 30$ mA		7	20	ns

■ Marking

Marking	I9
---------	----