



SMD Type

Diodes

Silicon Epitaxial Planar Diode

HSM2694



■ Features

- Low forward resistance. ($r_f = 0.9$ max)
- Low capacitance. ($C = 1.2\text{pF}_{\text{max}}$)
- MPAK package is suitable for high density surface mounting and high speed assembly.

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Value | Unit |
|-----------------------|-----------|-------------|------|
| Reverse Voltage | V_R | 35 | V |
| Power dissipation | P_d | 150 | mW |
| Junction temperature | T_j | 125 | °C |
| Storage temperature | T_{stg} | -45 to +125 | °C |
| Operation temperature | T_{opr} | -20 to +60 | °C |

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--------------------|--------|---|-----|-----|-----|------|
| Reverse voltage | V_R | $I_R = 10 \mu\text{A}$ | 35 | | | V |
| Reverse current | I_R | $V_R = 25 \text{ V}$ | | | 50 | nA |
| Forward voltage | V_F | $I_F = 10 \text{ mA}$ | | | 1.0 | V |
| Capacitance | C | $V_R = 6 \text{ V}, f = 1 \text{ MHz}$ | | | 1.2 | pF |
| Forward resistance | r_f | $I_F = 2 \text{ mA}, f = 100 \text{ MHz}$ | | | 0.9 | Ω |

■ Marking

| | |
|---------|----|
| Marking | B3 |
|---------|----|