



NOTES:
1. ALL MODELS HAVE AN RF POWER RATING OF 100W AVERAGE & 3 KW PEAK.

TYPE-N (F) CONNECTOR 2 PLCS. SHOWN, SMA AVAILABLE

4-40 THREAD MOUNTING HOLES THRU RIB 8 PLCS

.95 MAX (TYPE-N)
.51 MAX (SMA)

Ø1.25 KNOB

| | | |
|--------|---------------|-----------------|
| REV. A | DATE MM/DD/YY | INITIAL RELEASE |
|--------|---------------|-----------------|

| | | | | | | | |
|---|---------------|-----------|----------------|---|----------|----------|---------|
| MATERIAL | - | TREATMENT | - | DRAWN | R. LYNCH | DATE | 7/16/01 |
| FINISH | ATM STD. GRAY | MOD NO. | P11DXX, P21DXX | CHECKED | | DATE | |
| 24" PHASESHIFTER OUTLINE - DIGITAL COUNTING DIAL | | | | APPROVED | | DATE | |
| ADVANCED TECHNICAL MATERIALS, INC. 49 RIDER AVE., PATCHOGUE N.Y. 11772 TEL: (631) 289-0386 FAX: (631) 289-0358 http://www.atmmicrowave.com | | | | UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES FRACTIONS ±1/64 DECIMALS ±.01 ANGLES ±1/2° | | | |
| PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT THE WRITTEN CONSENT OF ATM, INC. | | | | SCALE | 1 : 4 | DWG. NO. | 4442 |
| | | | | SHEET 1 OF 1 | | | |