

**INCHANGE Semiconductor**

**isc Product Specification**

**isc Silicon NPN Power Transistor**

**BU426A**

**DESCRIPTION**

- Collector-Emitter Sustaining Voltage-  
:  $V_{CEO(SUS)} = 400V(\text{Min})$
- High Switching Speed

**APPLICATIONS**



- Designed for switch-mode CTV supply systems applications.

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	900	V
$V_{CES}$	Collector-Emitter Voltage $V_{BE} = 0$	900	V
$V_{CEO}$	Collector-Emitter Voltage	400	V
$V_{EBO}$	Emitter-Base Voltage	10	V
$I_C$	Collector Current-Continuous	6	A
$I_{CM}$	Collector Current-Peak	10	A
$I_B$	Base Current-Continuous	2	A
$I_{BM}$	Base Current-Peak	3	A
$P_C$	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	70	W
$T_J$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ\text{C}$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.1	$^\circ\text{C/W}$



DIM	mm	
	MIN	MAX
A	19.90	20.10
B	15.50	15.70
C	4.70	4.90
D	0.90	1.10
E	1.90	2.10
F	3.40	3.60
G	2.90	3.10
H	3.20	3.40
J	0.595	0.605
K	20.50	20.70
L	1.90	2.10
N	10.89	10.91
Q	4.90	5.10
R	3.35	3.45
S	1.995	2.005
U	5.90	6.10
Y	9.90	10.10



## isc Silicon NPN Power Transistor

## BU426A

## ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CE(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=0.1\text{A}; I_B=0; L=25\text{mH}$	400			V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=2.5\text{A}; I_B=0.5\text{A}$			1.5	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=4\text{A}; I_B=1.25\text{A}$			3.0	V
$V_{BE(sat)-1}$	Base-Emitter Saturation Voltage	$I_C=2.5\text{A}; I_B=0.5\text{A}$			1.4	V
$V_{BE(sat)-2}$	Base-Emitter Saturation Voltage	$I_C=4\text{A}; I_B=1.25\text{A}$			1.6	V
$I_{CES}$	Collector Cutoff Current	$V_{CE}=900\text{V}; V_{BE}=0$ $V_{CE}=900\text{V}; V_{BE}=0; T_J=125^{\circ}\text{C}$			1.0 2.0	mA
$I_{EBO}$	Emitter Cutoff Current	$V_{EB}=10\text{V}; I_C=0$			10	mA
$h_{FE}$	DC Current Gain	$I_C=0.6\text{A}; V_{CE}=5\text{V}$	15		60	

## Switching Times

$t_{on}$	Turn-On Time	$I_C=2.5\text{A}; I_{B1}=0.5\text{A}; I_{B2}=-1\text{A};$ $V_{CC}=250\text{V}$			0.6	$\mu\text{s}$
$t_{stg}$	Storage Time				3.5	$\mu\text{s}$
$t_f$	Fall Time			0.15		$\mu\text{s}$