

Inchange Semiconductor

Product Specification

Silicon NPN Power Transistors

TIP41D/41E/41F

DESCRIPTION


- With TO-220C package
- Complement to type TIP42D/42E/42F

APPLICATIONS

- For medium power linear switching applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter



Absolute maximum ratings($T_c=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	TIP41D	160	V
		TIP41E	180	
		TIP41F	200	
V_{CEO}	Collector-emitter voltage	TIP41D	120	V
		TIP41E	140	
		TIP41F	160	
V_{EBO}	Emitter-base voltage	Open collector	5	V
I_C	Collector current (DC)		6	A
I_{CM}	Collector current-Pulse		10	A
I_B	Base current		3	A
P_C	Collector power dissipation	$T_c=25^\circ\text{C}$	65	W
		$T_a=25^\circ\text{C}$	2	
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-65~150	$^\circ\text{C}$

Silicon NPN Power Transistors

TIP41D/41E/41F

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	TIP41D	I _C =30mA; I _B =0	120			V
		TIP41E		140			
		TIP41F		160			
V _{CEsat}	Collector-emitter saturation voltage		I _C =6A; I _B =1.5A			1.5	V
V _{BE}	Base-emitter on voltage		I _C =6A; V _{CE} =4V			2.0	V
I _{CES}	Collector cut-off current	TIP41D	V _{CE} =120V; V _{EB} =0			0.4	mA
		TIP41E	V _{CE} =140V; V _{EB} =0				
		TIP41F	V _{CE} =160V; V _{EB} =0				
I _{CEO}	Collector cut-off current		V _{CE} =90V; I _B =0			0.7	mA
I _{EBO}	Emitter cut-off current		V _{EB} =5V; I _C =0			1.0	mA
h _{FE-1}	DC current gain		I _C =0.3A; V _{CE} =4V	30			
h _{FE-2}	DC current gain		I _C =3A; V _{CE} =4V	15			
f _T	Transiton frequency		I _C =0.5A; V _{CE} =10V	3			MHz

Silicon NPN Power Transistors

TIP41D/41E/41F

PACKAGE OUTLINE




Fig.2 Outline dimensions