

Inchange Semiconductor

Product Specification

Silicon NPN Power Transistors

2SC3868

DESCRIPTION


- With TO-220Fa package
- High breakdown voltage
- Wide area of safe operation

APPLICATIONS

- For high speed switching applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter



Absolute maximum ratings(Ta=25)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	500	V
V _{CEO}	Collector-emitter voltage	Open base	400	V
V _{EBO}	Emitter-base voltage	Open collector	7	V
I _C	Collector current (DC)		2	A
I _{CM}	Collector current (pulse)		4	A
I _B	Base current (DC)		0.5	A
P _C	Collector power dissipation	T _a =25	2	W
		T _C =25	25	
T _j	Junction temperature		150	
T _{stg}	Storage temperature		-55~150	

Silicon NPN Power Transistors

2SC3868

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	I _C =10mA ; I _B =0	400			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =1A ; I _B =0.2A			1.0	V
V _{BEsat}	Base-emitter saturation voltage	I _C =1A ; I _B =0.2A			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =500V ; I _E =0			100	μA
I _{EBO}	Emitter cut-off current	V _{EB} =5V ; I _C =0			100	μA
h _{FE-1}	DC current gain	I _C =0.1A ; V _{CE} =5V	15			
h _{FE-2}	DC current gain	I _C =1A ; V _{CE} =5V	8			
f _T	Transition frequency	I _C =0.2A ; V _{CE} =10V		30		MHz
Switching times						
t _{on}	Turn-on time	I _C =1A ; I _B =0.2A ; I _{B2} =-0.4A V _{CC} =150V			0.7	μs
t _s	Storage time				2.0	μs
t _f	Fall time				0.3	μs

Silicon NPN Power Transistors

2SC3868

PACKAGE OUTLINE

